

A07872 ZEP PRO HI PERF ADH R34901 20n14

Version 3.0 Revision Date 08/31/2015 Print Date 09/08/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A07872 ZEP PRO HI PERF ADH R34901 20n14

Material number : 0000000001046691

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW

Atlanta, GA 30318

Telephone : 404-352-1680

For SDS Information : Compliance Services 1-877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	colourless, light yellow
Odour	solvent-like

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Skin irritation : Category 2
Eye irritation : Category 2A

Specific target organ toxicity - : Category 3 (Central nervous system)

single exposure

GHS Label element

Hazard pictograms





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.
H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements : Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.



Version 3.0 Revision Date 08/31/2015 Print Date 09/08/2015

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after

use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

Dispose of contents/container in accordance with local regulation.

Potential Health Effects

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 10 - < 20



A07872 ZEP PRO HI PERF ADH R34901 20n14

Version 3.0 Revision Date 08/31/2015 Print Date 09/08/2015

propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 10 - < 20
cyclohexane	110-82-7	>= 10 - < 20
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 5 - < 10
Aromatic Hydrocarbon Resin	68410-16-2	>= 5 - < 10
methyl acetate	79-20-9	>= 5 - < 10

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water for at least 15 minutes.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This



Version 3.0 Revision Date 08/31/2015 Print Date 09/08/2015

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Do not breathe vapours or spray mist.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Always replace cap after use.

Conditions for safe storage

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Keep in a dry, cool and well-ventilated place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Strong oxidizing agents



Version 3.0 Revision Date 08/31/2015 Print Date 09/08/2015

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
cyclohexane	110-82-7	TWA	100 ppm	ACGIH
		TWA	300 ppm 1,050 mg/m3	NIOSH REL
		TWA	300 ppm 1,050 mg/m3	OSHA Z-1
		TWA	300 ppm 1,050 mg/m3	OSHA P0
methyl acetate	79-20-9	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 610 mg/m3	NIOSH REL
		ST	250 ppm 760 mg/m3	NIOSH REL
		TWA	200 ppm 610 mg/m3	OSHA Z-1
		TWA	200 ppm 610 mg/m3	OSHA P0
		STEL	250 ppm 760 mg/m3	OSHA P0

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-PROPANONE	67-64-1	Acetone	Urine	End of	50 mg/l	ACGIH BEI
				shift (As		



Version 3.0 Revision Date 08/31/2015 Print Date 09/08/2015

		_
	soon as	
	possible	
	after	
	exposure	
	ceases)	

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to

the workstation location.

Safety glasses

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : colourless, light yellow

Odour : solvent-like

Odour Threshold : No data available
pH : Not applicable
Melting point/freezing point : No data available

Boiling point : No data available

No data available

Evaporation rate : > 1

Flash point

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available



A07872 ZEP PRO HI PERF ADH R34901 20n14

Version 3.0 Revision Date 08/31/2015 Print Date 09/08/2015

Density : 0.86 g/cm3

Solubility(ies)

Water solubility : soluble in cold water, soluble in hot water

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Components:

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l

Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit > 7,426 mg/kg

propane:



Version 3.0 Revision Date 08/31/2015 Print Date 09/08/2015

Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l

Exposure time: 2 h

LC50 Rat: 658 mg/l Exposure time: 4 h

LC50 Rat: 1,355 mg/l

butane:

Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l

Exposure time: 2 h

LC50 Rat: 1,355 mg/l

cyclohexane:

Acute oral toxicity : LD50 Oral Rat: 12,705 mg/kg

Acute inhalation toxicity : LC50 Rat: 13,900 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Dermal Rabbit: > 2,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: May irritate skin.

Serious eye damage/eye irritation

Product:

Remarks: Irritating to eyes.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

acetone:

propane:

butane:

cyclohexane:

Naphtha (petroleum), hydrotreated light:

Aromatic Hydrocarbon Resin:

methyl acetate:



A07872 ZEP PRO HI PERF ADH R34901 20n14

Version 3.0 Revision Date 08/31/2015 Print Date 09/08/2015

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water Components: butane :

Partition coefficient: n- : Pow: 2.89

octanol/water

cyclohexane:

Partition coefficient: n- : log Pow: 3.44

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

: Remarks: No data available

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).



A07872 ZEP PRO HI PERF ADH R34901 20n14

Version 3.0 Revision Date 08/31/2015 Print Date 09/08/2015

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to

aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
cyclohexane	110-82-7	1000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity



Revision Date 08/31/2015 Print Date 09/08/2015 Version 3.0

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Sudden Release of Pressure Hazard

Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

cyclohexane 110-82-7 10.0749 %

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer.

91-20-3 naphthalene benzene

71-43-2

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive

harm.

71-43-2 benzene toluene 108-88-3

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

DSL This product contains one or several components that are not on the

Canadian DSL nor NDSL.

AICS Not in compliance with the inventory **NZIoC** Not in compliance with the inventory **PICCS** Not in compliance with the inventory **IECSC** Not in compliance with the inventory

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)


SECTION 16. OTHER INFORMATION



Revision Date 08/31/2015 Version 3.0 Print Date 09/08/2015

Further information

NFPA:



Special hazard.

HMIS III:

HEALTH	3
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic

OSHA GHS Label Information:

Hazard pictograms







Signal word

Hazard statements Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or

Precautionary statements

Prevention: Keep aw ay from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection face protection. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	3.0
Revision Date:	08/31/2015
Print Date:	09/08/2015

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next



A07872 ZEP PRO HI PERF ADH R34901 20n14

Version 3.0 Revision Date 08/31/2015 Print Date 09/08/2015

Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.