

Safety Data Sheet

24 Hour Emergency Phone Numbers:

Medical/Poison Control:

In U.S.: Call 1-800-222-1222

Outside U.S.: Call your local poison

control center

Transportation/National Response

Center:

1-800-535-5053 1-352-323-3500

NOTE: The National ResponseCenter emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.

1. Identification

This Material Safety Data Sheet is available in American Spanish upon request. Los Datos de Serguridad del Producto pueden obtenerse en Espanol si lo riquiere.

Product Name: Beats The Nail All Purpose VOC Construction Revision Date: 5/1/2015

Adhesive

Product UPC Number: 27050, 27480, 27058, 27450, 27458, 27050 Supercedes Date: 3/4/2013

Product Use/Class: Construction Adhesive SDS No: 00077095001

Manufacturer: DAP Products Inc.

2400 Boston Street Suite 200 Baltimore, MD 21224-4723

888-327-8477 (non-emergency matters)

Preparer: Regulatory Department

2. Hazards Identification

EMERGENCY OVERVIEW: May cause eye, skin, nose, throat and respiratory tract irritation. Harmful if swallowed or absorbed through the skin.

GHS Classification

Not a hazardous substance or mixture.

Symbol(s) of Product

Not a hazardous substance or mixture.

Signal Word

Not a hazardous substance or mixture.

3. Composition/Information on Ingredients

Chemical Name	CAS-No.	Wt. %	GHS Symbols	GHS Statements
Limestone	1317-65-3	25-50	GHS07	H332
Calcium Carbonate	471-34-1	25-50	GHS07	H332
Magnesite	546-93-0	2.5-10	No Information	No Information
Diethylene glycol dibenzoate	120-55-8	1.0-2.5	GHS07	H312
Magnesium aluminum silicate	12174-11-7	1.0-2.5	No Information	No Information
Urea	57-13-6	1.0-2.5	No Information	No Information
Quartz	14808-60-7	0.1-1.0	GHS07	H302

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: If inhaled, remove to fresh air. If breathing is difficult, leave the area to obtain fresh air. If continued breathing difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: Remove and wash contaminated clothing. Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical aid if symptoms persist.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Scrape up dried material and place into containers. Use personal protective equipment as necessary.

7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN!DO NOT TAKE INTERNALLY. Avoid breathing vapor and contact with eyes, skin and clothing. Use only with adequate ventilation. Open all windows and doors or use other means to ensure cross-ventilation and fresh air entry during application and drying. Odor is not an adequate warning for hazardous conditions. Wash thoroughly after handling.

STORAGE: Avoid excessive heat and freezing. Do not store at temperatures above 120 degrees F. Store away from caustics and oxidizers.

8. Exposure Controls/Personal Protection

ingrealents with	Occupational	⊨xposure	Limits
Chemical Name			ACCIH T

<u>Chemical Name</u>	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
Limestone	N.E.	N.E.	15 mg/m3 TWA total dust, 5 mg/m3 TWA respirable fraction	
Calcium Carbonate	N.E.	N.E.	N.E.	N.E.

N.E. N.E. 15 mg/m3 TWA Magnesite N.E.

total dust, 5 mg/m3 TWA respirable

fraction

N.F. N.E. N.E. N.E. Diethylene glycol dibenzoate Magnesium aluminum silicate N.E. N.E. N.E. N.E. Urea N.E. N.E. N.E. N.E. Quartz 0.025 mg/m3 TWA N.E. N.E. N.E.

respirable fraction

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required. In case of insufficient ventilation, wear suitable respiratory equipment. National Institute for Occupational Safety and Health (NIOSH) has recommended that the permissible exposure limit be changed to 50 micrograms respirable free silica per cubic meter of air (0.05 mg/m3) as determined by a full shift sample up to 10-hour work shift.



SKIN PROTECTION: Rubber gloves.



EYE PROTECTION: Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Not required under normal use.



HYGIENIC PRACTICES: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

9. Physical and Chemical Properties

White to Off-White Appearance: **Physical State:** Paste

Not Established Odor: Very Slight Ammonia **Odor Threshold:** Density, g/cm3: 1.46 - 1.48 Between 7.0 and 12.0 pH: Not Established Freeze Point, °C: Not Established Viscosity (mPa.s): Solubility in Water: Not Established Partition Coeff., n-octanol/water: Not Established Not Established N.I. - N.I.

Decomposition Temperature, °C: Explosive Limits, %:

Boiling Range, °C: N.I. - N.I. Auto-Ignition Temperature, °C Not Established Minimum Flash Point, °C: 93.3 Vapor Pressure, mmHg: No Information Slower Than n-Butyl Acetate **Evaporation Rate:** Flash Method: Seta Closed Cup

Heavier Than Air Vapor Density:

Combustibility: Does not Support Combustion

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Excessive heat and freezing.

INCOMPATIBILITY: Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., COx, NOx.

11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: May be harmful if inhaled. Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated contact with skin may cause mild irritation.

EFFECT OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation of susceptible persons.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful if swallowed.

CARCINOGENICITY: No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Inhalation, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u> 1317-65-3	<u>Chemical Name</u> Limestone	Oral LD50 6450 mg/kg Rat	Dermal LD50 >2000 mg/kg	Vapor LC50 >20 mg/L
471-34-1	Calcium Carbonate	6450 mg/kg Rat	>2000 mg/kg Rat	>20 mg/L
546-93-0	Magnesite	>2000 mg/kg Rat	>2000 mg/kg	>20 mg/L
120-55-8	Diethylene glycol dibenzoate	2830 mg/kg Rat	2000 mg/kg Rabbit	> 200 mg/L Rat
12174-11-7	Magnesium aluminum silicate	N.I.	N.I.	N.I.
57-13-6	Urea	8471 mg/kg Rat	N.I.	N.I.
14808-60-7	Quartz	500 mg/kg Rat	>2000 mg/kg	>20 mg/L

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

13. Disposal Information

DISPOSAL METHOD: This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Scrape up dried material and place into containers. Use personal protective equipment as necessary.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT Proper Shipping Name:Not Regulated.

DOT Technical Name: N.A. Hazard SubClass: N.A.

DOT Hazard Class: N.A.

DOT UN/NA Number: N.A.

Packing Group: N.A.

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA12(b) components exist in this product in concentrations at or above their thresholds.

CALIFORNIA PROPOSITION 65 CARCINOGENS

WARNING: This product contains chemicals known to the State of California to cause cancer.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

WARNING: This product contains chemicals known to the State of California to cause birth defects or other reproductive harm.

International Regulations: As follows -

CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class Consumer Commodity

16. Other Information

Revision Date: 5/1/2015 Supersedes Date: 3/4/2013

Reason for revision: HazCom2012/GHS Conversion

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	1	Flammability:	0	Reactivity:	0	Personal Protection:	X

VOC Less Water Less Exempt, g/L:7.7

VOC, Material, g/L:5

VOC as Defined by California Consumer Product Regulation, Wt/Wt%:0.3

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H302 Harmful if swallowed.
H312 Harmful in contact with skin.

H332 Harmful if inhaled.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS07



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.