

# **Safety Data Sheet**

Issue date 09-Jun-2015 Version 1

# 1. Identification of the Substance/Preparation and of the Company/Undertaking

**Product Identifier** 

Product name CHAMPION SPRAYON OVEN CLEANER

Chemical name 7-7603-1

Other means of identification

Product code FG 438-5177-3 Synonyms Oven and grill cleaner

Recommended use of the chemical and restrictions on use Recommended Use Stoves, ovens and grills.

Uses advised against DO NOT USE ON FLOORS Do not use on tile, plastic, leather, copper, painted and

varnished surfaces.

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressChase Products Co.Chase Products Co.2727 Gardner Road2727 Gardner RoadBroadview, IL 60155Broadview, IL 60155708-273-1121708-273-1121

**Emergency Telephone Number** 

Company Phone Number 708-865-1000 24 Hour Emergency Phone Number 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

### 2. Hazards Identification

# Classification

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 2A
Gases Under Pressure	liquefied gas

### **Label Elements**

### **EMERGENCY OVERVIEW**

# DANGER

hazard statements

Causes severe skin burns and eye damage

Causes serious eye irritation

Contains gas under pressure; may explode if heated



Appearance Yellowish, viscous liquid Physical State Aerosol Odor Strong, characteristic odor

**Precautionary Statements - Prevention** 

\_\_\_\_\_\_

Do not breathe fumes, mist, vapors or spray.

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing, eye protection and face protection.

### **Precautionary Statements - Response**

Specific measures. See additional cautionary statements on this label.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a POISON CENTER or doctor

IF SWALLOWED: rinse mouth. Do NOT induce vomiting

### **Precautionary Statements - Storage**

Store locked up

Protect from sunlight. Store in a well-ventilated place

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

#### Other Information

- Toxic to aquatic life with long lasting effects
- · Toxic to aquatic life

-

# 3. Composition/information on Ingredients

Common NameOven and grill cleaner.SynonymsOven and grill cleaner.

Chemical FamilyMIXTURES.Formula7-7603-1

Chemical nature Aqueous alkaline solution.

Chemical name	CAS No	weight-%	Trade secret
Water	7732-18-5	80-85	*
Triethylene Glycol	112-27-6	1-5	*
N-Butane	106-97-8	1-5	*
Sodium hydroxide	1310-73-2	1-5	*
Potassium hydroxide	1310-58-3	1-5	*
Propane	74-98-6	1-5	*

Chemical Additions

Hazardous components according to OSHA, are listed when present at 1% or greater. Carcinoges are listed when present at 0.1% or greater.

### 4. First aid measures

### **FIRST AID MEASURES**

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact

lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control

center or doctor for treatment advice.

Skin contact Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20

minutes. Call a poison control center or doctor for treatment advise.

inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

<sup>\*</sup> The exact percentage (concentration) of composition has been withheld as a trade secret.

poison control center or doctor for further treatment advise.

**INGESTION**Call a poison control center or doctor for treatment advice. Have person sip a glass of water

if able to swallow. Do not induce vomiting unless told to do so by a poison control center or

doctor. Do not give anything by mouth to an unconscious person.

### Most important symptoms and effects, both acute and delayed

Symptoms Acute: Danger - contains sodium hydroxide. Injurious if sprayed on yes. Contact with eyes

may result on eye damage. Irritant to skin. Prolonged contact with skin may cause severe burns. Inhalation of vapor or mist may cause headaches, dizziness and nausea. Vapors

may irritate the upper-respiratory tract system.

# Indication of any immediate medical attention and special treatment needed

Note to physicians None needed.

# 5. Fire-fighting measures

#### Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may release carbon monoxide and carbon dioxide.

### **Explosion data**

Sensitivity to Mechanical Impact Contents under pressure, keep away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

**Personal precautions**Use with adequate general or local exhaust ventilation.

For emergency responders Remove all sources of ignition.

**Environmental Precautions** 

**Environmental Precautions** See Section 12 for additional Ecological Information.

#### Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

# 7. Handling and Storage

### Precautions for safe handling

Advice on safe handling Avoid contact with skin. Avoid getting spray into eyes. Do not deliberately inhale vapor or

mist. Do not contaminate food or food handling surfaces. Keep out of reach of children.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a cool, dry place away from heat and open flame. Keep out of reach of children.

**AEROSOL STORAGE LEVEL I (NFPA-30B).** 

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers. Avoid contact with tile, plastic,

leather, copper, painted and varnished surfaces.

# 8. Exposure Controls/Personal Protection

#### Control parameters

**Exposure guidelines** See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
Potassium hydroxide 1310-58-3	Ceiling: 2 mg/m <sup>3</sup>	(vacated) Ceiling: 2 mg/m <sup>3</sup>	Ceiling: 2 mg/m <sup>3</sup>
Sodium hydroxide 1310-73-2	Ceiling: 2 mg/m <sup>3</sup>	TWA: 2 mg/m³ (vacated) Ceiling: 2 mg/m³	IDLH: 10 mg/m <sup>3</sup> Ceiling: 2 mg/m <sup>3</sup>
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³

### **Appropriate engineering controls**

**Engineering controls**Use with adequate general or local exhaust ventilation.

#### Individual protection measures, such as personal protective equipment

**Eye/face Protection** Conventional eyeglasses to guard against splashing.

**Skin and Body Protection** Rubber, vinyl or household type gloves required.

fumes disipate.

**General hygiene considerations** Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

# 9. Physical and Chemical Properties

#### Information on basic physical and chemical properties

Physical State Aerosol

 Appearance
 Yellowish, viscous liquid
 Odor
 Strong, characteristic

odor

Color light yellow Odor threshold No information available

Property Values Remarks • Method

pH12.9 to 13.5No information availableMelting point/freezing pointNot applicableNo information availableBoiling point/boiling rangeWater 212 °F/100 °CNo information availableFlash PointNot applicable. This is an aerosolNo information available

product for which Flame Projection is 0 in. with 0 in flashback. Product was tested for Enclosed Space Ignition Test and is not a flammable aerosol as defined on 29CFR 1910.122 Appendix

B.3.

**Evaporation Rate** Faster than butyl acetate No information available

Flammability (solid, gas)

Flammability Limits in Air

No information available
No information available

Upper flammability limits Not available Lower Flammability Limit Not available

Vapor pressureNo information availableVapor DensityNo information available

Specific gravity

1.056 concentrate

No information available

Water solubility Soluble in water

Solubility in other solventsNo information availablePartition coefficientNo information availableAutoignition TemperatureNo information availableDecomposition temperatureNo information availableKinematic viscosityNo information availableDynamic viscosityNo information available

Dynamic viscosity
Explosive properties
No information available

Oxidizing properties

No information available
No information available

**Other Information** 

Softening point No information available Molecular weight No information available

 VOC content (%)
 7.84%

 Density
 8.80 lb/gal

Bulk Density No information available

# 10. Stability and Reactivity

# Reactivity

Not applicable Not applicable

### **Chemical stability**

Stable.

#### Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

#### **Conditions to Avoid**

Temperatures above 122 °F (50 °C).

#### **Incompatible Materials**

Avoid heat, open flame and contact with strong oxidizers. Avoid contact with tile, plastic, leather, copper, painted and varnished surfaces.

#### Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

### 11. Toxicological Information

#### Information on likely routes of exposure

Product Information Danger contains Sodium Hydroxide

inhalation Vapors may irritate the upper-respiratory tract system. Inhalation of vapor or mist may

cause headaches, dizziness and nausea.

**Eve Contact** Injurious if sprayed on eyes. Contact with eyes may result on eye damage.

Skin contact Danger, contains sodium hydroxide. Irritant to skin. Prolonged contact with skin may cause

severe burns.

INGESTION This is an aerosol product, ingestion is unlikely to occur. MAY BE HARMFUL IF

\_\_\_\_\_

#### SWALLOWED.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Water 7732-18-5	> 90 mL/kg ( Rat )	-	-
Triethylene Glycol 112-27-6	= 15000 mg/kg ( Rat )	> 20 mL/kg(Rabbit)	-
N-Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Sodium hydroxide 1310-73-2	-	= 1350 mg/kg ( Rabbit )	-
Potassium hydroxide 1310-58-3	= 284 mg/kg ( Rat )	-	-
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h

### Information on toxicological effects

**Symptoms** Vapors may be irritating to eyes, nose, throat, and lungs.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause severe burns after prolonged contact with skin.

Serious eye damage/eye irritation Ri

Risk of serious damage to eyes.

corrosivity

Contains sodium hydroxide, can be corrosive to skin and eyes.

sensitization No information available.

Germ Cell Mutagenicity

No information available.

carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Aspiration Hazard Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and

nausea.

### Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 17749 mg/kg
ATEmix (dermal) 46056 mg/kg
ATEmix (inhalation-gas) 8757000 mg/l
ATEmix (inhalation-dust/mist) 46.1 mg/l
ATEmix (inhalation-vapor) 14403 mg/l

# 12. Ecological Information

This product does not contain marine pollutants.

#### ecotoxicity

7.790000000001% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Triethylene Glycol		56200 - 63700: 96 h		42426: 48 h Daphnia magna
112-27-6		Pimephales promelas mg/L		mg/L EC50
		LC50 flow-through 10000:		-
		96 h Lepomis macrochirus		
		mg/L LC50 static 61000: 96		
		h Lepomis macrochirus mg/L		
		LC50 flow-through		

Sodium hydroxide	45.4: 96 h Oncorhynchus
1310-73-2	mykiss mg/L LC50 static
Potassium hydroxide	80: 96 h Gambusia affinis
1310-58-3	mg/L LC50 static

#### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

Chemical name	Partition coefficient
Triethylene Glycol 112-27-6	-1.98
N-Butane 106-97-8	2.89
Potassium hydroxide 1310-58-3	0.65 0.83
Propane 74-98-6	2.3

Other adverse effects No information available

# 13. Disposal Considerations

#### Waste treatment methods

**Disposal of wastes**Dispose of in accordance with federal, state and local regulations.

**Contaminated packaging** Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate

container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

Chemical name	California Hazardous Waste Status
Sodium hydroxide	Toxic
1310-73-2	Corrosive
Potassium hydroxide	Toxic
1310-58-3	Corrosive

# 14. Transport Information

**DOT** Limited quantity (LQ) Oven and grill cleaner

UN/ID no UN1950

Proper Shipping Name Limited quantity (LQ)

Hazard Class 2.1

Marine pollutant This product does not contain marine pollutants.

# 15. Regulatory information

**International Inventories** 

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

#### DSL

All ingredients are listed or are excluded from listing on the DSL.

### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

# **US Federal Regulations**

# **SARA 313**

This product does not contain toxic chemicals (above the de minimis level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

### SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sodium hydroxide 1310-73-2	1000 lb			Х
Potassium hydroxide 1310-58-3	1000 lb			Х

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Sodium hydroxide 1310-73-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Potassium hydroxide	1000 lb		RQ 1000 lb final RQ
1310-58-3			RQ 454 kg final RQ

### **US State Regulations**

### **California Proposition 65**

This product does not contain any Proposition 65 chemicals

### U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water 7732-18-5			X
Triethylene Glycol 112-27-6			X
N-Butane 106-97-8	X	X	X
Sodium hydroxide 1310-73-2	X	X	X
Potassium hydroxide 1310-58-3	X	X	X
Propane 74-98-6	X	X	X

#### U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information	

NFPA Health Hazards 3 Flammability 1 Instability 1 Physical and chemical

**properties** Not applicable

HMIS Health Hazards 3 Flammability 2 Physical Hazards 1 Personal Protection B -

Eyes and hands

protection

Issue date 09-Jun-2015

**Revision note** 

This SDS supersedes a previous MSDS dated May 05, 2013.

**Disclaimer** 

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**