# **SAFETY DATA SHEET**



Date of issue/Date of revision 1 July 2015 Version 4

Section 1. Identification		
Product name	: PM ARCH SG PMK CALIM BG MPN6345	
Product code	: 00414556	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	: Industrial applications, Used by spraying.	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Supplier	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272	
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)	
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)	

: This material is considered hazardous by the OSHA Hazard Communication Standard

Classification of the

**OSHA/HCS** status

(29 CFR 1910.1200). : CARCINOGENICITY - Category 2

substance or mixture

GHS label elements Hazard pictograms



2

Signal word Hazard statements <u>Precautionary statements</u> : Marning

: Suspected of causing cancer.

### Product name PM ARCH SG PMK CALIM BG MPN6345

### Section 2. Hazards identification

Prevention	<ul> <li>Øbtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing.</li> </ul>
Response	: IF exposed or concerned: Get medical attention.
Storage	: Store locked up.
Disposal	<ul> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> </ul>
Supplemental label elements	: Emits toxic fumes when heated.
Hazards not otherwise classified	: None known.

### Section 3. Composition/information on ingredients

Substance/mixture	Vixture	
Product name	PM ARCH SG I	PMK CALIM BG MPN6345

Ingredient name	%	CAS number
Manium dioxide Kaolin		13463-67-7
Raolili	≥1 - <3	1332-58-7

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

### Description of necessary first aid measures

Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

Ey	/e contact	1	No known significant effects or critical hazards.

Date of issue 1 July 2015

### Product name PM ARCH SG PMK CALIM BG MPN6345

### Section 4. First aid measures

Inhalation	: No known significant effects or critical hazards.	
Skin contact	: No known significant effects or critical hazards.	
Ingestion	: No known significant effects or critical hazards.	
Over-exposure signs/sym	<u>ptoms</u>	
Eye contact	: No specific data.	
Inhalation	: No specific data.	
Skin contact	: No specific data.	
Ingestion	: No specific data.	
Indication of immediate me	dical attention and special treatment needed, if necessary	
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.	

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Product name PM ARCH SG PMK CALIM BG MPN6345

# Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
	United States Page: 4/12

Product code 00414556	Date of issue 1 July 2015 Version 4			
Product name PM ARCH SG PMK CALIM BG MPN6345				
Section 7. Handling	g and storage			
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental			

# Section 8. Exposure controls/personal protection

contamination.

### **Control parameters**

### **Occupational exposure limits**

Ingredient name	Exposure limits		
titanium dioxide	OSHA PEL (United States, 2/2013).		
	TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust		
	ACGIH TLV (United States, 4/2014).		
	TWA: 10 mg/m <sup>3</sup> 8 hours.		
Kaolin	ACGIH TLV (United States, 4/2014).		
	TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable		
	fraction		
	OSHA PEL (United States, 2/2013).		
	TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable		
	fraction		
	TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust		

	Key to abbreviations		
А	= Acceptable Maximum Peak	S	<ul> <li>Potential skin absorption</li> </ul>
ACGIH	<ul> <li>American Conference of Governmental Industrial Hygienists.</li> </ul>	SR	<ul> <li>Respiratory sensitization</li> </ul>
С	= Ceiling Limit	SS	<ul> <li>Skin sensitization</li> </ul>
F	= Fume	STEL	<ul> <li>Short term Exposure limit values</li> </ul>
IPEL	<ul> <li>Internal Permissible Exposure Limit</li> </ul>	TD	= Total dust
OSHA	<ul> <li>Occupational Safety and Health Administration.</li> </ul>	TLV	<ul> <li>Threshold Limit Value</li> </ul>
R	= Respirable	TWA	= Time Weighted Average
Z	= OSHA 29CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances		
Concult	local authorities for accontable exposure limits		

### Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Product name PM ARCH SG PMK CALIM BG MPN6345

# Section 8. Exposure controls/personal protection

### Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection <u>Skin protection</u>	: Safety glasses with side shields.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# Section 9. Physical and chemical properties

Appearance		
Physical state	1	Liquid.
Color	1	Not available.
Odor	1	Characteristic.
Odor threshold	:	Not available.
рН	1	Not available.
Melting point	1	Not available.
Boiling point	1	>37.78°C (>100°F)
Flash point	1	Closed cup: Not applicable. [Product does not sustain combustion.]
Auto-ignition temperature	1	Not available.
Decomposition temperature	1	Not available.
Flammability (solid, gas)	1	Not available.
Lower and upper explosive (flammable) limits	:	Upper: 0%
Evaporation rate	1	Not available.
Vapor pressure	1	Not available.
Vapor density	1	Not available.
Relative density	:	1.19

Version 4

### Product name PM ARCH SG PMK CALIM BG MPN6345

# Section 9. Physical and chemical properties

Density ( lbs / gal )	: 9.93
Solubility	: Soluble in the following materials: cold water.
Partition coefficient: n- octanol/water	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >0.21 cm <sup>2</sup> /s (>21 cSt)
Volatility	: 69% (v/v), 57.428% (w/w)
% Solid. (w/w)	: 42.572

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

# Section 11. Toxicological information

### Information on toxicological effects

Acute	toxicity

Product/ingredient name	Result	Species	Dose	Exposure
titanium dioxide	LD50 Oral	Rat	>10 g/kg	-
Kaolin	LD50 Oral	Rat	>5000 mg/kg	-
Conclusion/Summary	: There are no data available on	the mixture itself.		
rritation/Corrosion				
Conclusion/Summary				
Skin	: There are no data available on	the mixture itself.		
Eyes	There are no data available on the mixture itself.			
Respiratory	: There are no data available on	the mixture itself.		
Sensitization				
Conclusion/Summary				
Skin	: There are no data available on	the mixture itself.		
Respiratory	: There are no data available on	the mixture itself.		
<u>Mutagenicity</u>				
			United States	Daga: 7/12

Date of issue 1 July 2015

Version 4

### Product name PM ARCH SG PMK CALIM BG MPN6345

### Section 11. Toxicological information

Conclusion/Summary	: There are no data available on the mixture itself.		
Carcinogenicity			
Conclusion/Summary	: There a	re no data	available on the mixture itself.
<b>Classification</b>			
Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-
Carcinogen Classification	code:		

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

#### **Reproductive toxicity**

<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
---------------------------	--

### **Teratogenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

Target organs

: Contains material which causes damage to the following organs: eyes. Contains material which may cause damage to the following organs: lungs, upper respiratory tract, stomach.

#### Aspiration hazard

Not available.

#### Information on the likely routes of exposure

### Potential acute health effects

	United States Page: 8/12
Conclusion/Summary	There are no data available on the mixture itself. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
•	fects and also chronic effects from short and long term exposure
Ingestion	: No specific data.
Skin contact	: No specific data.
Inhalation	: No specific data.
Eye contact	: No specific data.
Over-exposure signs/syn	<u>nptoms</u>
Ingestion	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Eye contact	: No known significant effects or critical hazards.

Version 4

### Product name PM ARCH SG PMK CALIM BG MPN6345

# Section 11. Toxicological information

Short term exposure						
Potential immediate effects	There are no data available on the mixture itself.					
Potential delayed effects	There are no data available on the mixture itself.					
<u>Long term exposure</u>						
Potential immediate effects	: There are no data available on the mixture itself.					
Potential delayed effects	: There are no data available on the mixture itself.					
Potential chronic health effe	Potential chronic health effects					
General	: No known significant effects or critical hazards.					
Carcinogenicity	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.					
Mutagenicity	No known significant effects or critical hazards.					
Teratogenicity	No known significant effects or critical hazards.					
Developmental effects	: No known significant effects or critical hazards.					
Fertility effects	: No known significant effects or critical hazards.					
Numerical measures of toxic	<u>ity</u>					
Acute toxicity estimates						
Route	ATE value					
Oral	312536.5 mg/kg					

# Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure	
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours	

#### Persistence and degradability

Not available.

### **Bioaccumulative potential**

Not available.

### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Product name PM ARCH SG PMK CALIM BG MPN6345

# Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

### 14. Transport information

	DOT	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

### Additional information

- DOT : None identified. IMDG : None identified.
- IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Product name PM ARCH SG P	MK CALIM B	G MPN634	5		
Section 15. Regulato	ry informa	ation			
United States					
United States inventory (TSCA 8b	) : All compone	ents are listed	or exempted		
United States - TSCA 5(e) - Sub partially fluorinated alcohol, react		nt order:		Listed	
United States - TSCA 5(a)2 - Pr partially fluorinated alcohol, react		cant new use	rules:	Listed	
<u>SARA 302/304</u>					
SARA 304 RQ : N	ot applicable.				
Composition/information on ing	gredients				
No products were found.					
<u>SARA 311/312</u>					
Classification : D	elayed (chronic)	health hazar	d		
Composition/information on ing	gredients				
Name	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard

No.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

No.

No.

No.

### **Section 16. Other information**

#### Hazardous Material Information System (U.S.A.)

Health	:	1	*	Flammability	:	0	Physical hazards	:	0
(*) 06		 4-							

#### (\*) - Chronic effects

titanium dioxide

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

#### The customer is responsible for determining the PPE code for this material.

National Fire Protection Ass	ociation (U.S.A.)
Health : 1 Flamma	ibility : 0 Instability : 0
Date of previous issue	: 5/20/2015
Organization that prepared the MSDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

Product code 00414556

Date of issue 1 July 2015

Version 4

United States Page: 11/12

Yes.

### Product name PM ARCH SG PMK CALIM BG MPN6345

### Section 16. Other information

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

### Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.