# **SAFETY DATA SHEET**



Date of issue/Date of revision14 September 2016Version 1

Section 1. Identification		
Product name	: 1250-1270G PPG PAINTS MULTI-PRO MAINTENANCE INTERIOR LATEX FLAT - NAVAJO WHITE	
Product code	: 00385717	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of Product use	<ul> <li>the substance or mixture and uses advised against</li> <li>Industrial applications, Used by spraying.</li> </ul>	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272	
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)	
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)	

### Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: CARCINOGENICITY - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 19.9%
GHS label elements Hazard pictograms	
Signal word	: Warning
Hazard statements <u>Precautionary statements</u>	: Suspected of causing cancer.

**United States** 

Page: 1/12

Date of issue 14 September 2016Version 1

## Product name 1250-1270G PPG PAINTS MULTI-PRO MAINTENANCE INTERIOR LATEX FLAT - NAVAJO WHITE

### Section 2. Hazards identification

Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing.
Response	: IF exposed or concerned: Get medical attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Emits toxic fumes when heated.
Hazards not otherwise classified	: None known.

### Section 3. Composition/information on ingredients

Substance/mixture	1	Mixture
Product name	:	1250-1270G PPG PAINTS MULTI-PRO MAINTENANCE INTERIOR LATEX FLAT - NAVAJO WHITE

Ingredient name	%	CAS number
	≥1.0 - ≤5.0 ≥1.0 - ≤5.0 <1.0	13463-67-7 Not available. 4080-31-3

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

#### Description of necessary first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Date of issue 14 September 2016Version 1

## Product name 1250-1270G PPG PAINTS MULTI-PRO MAINTENANCE INTERIOR LATEX FLAT - NAVAJO WHITE

### Section 4. First aid measures

	s/effects, acute and delayed
Potential acute health et	ffects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs/sy</u>	<u>mptoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
ndication of immediate r	nedical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist imm

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### See toxicological information (Section 11)

### Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

United States Page: 3/12

Date of issue 14 September 2016Version 1

Product name 1250-1270G PPG PAINTS MULTI-PRO MAINTENANCE INTERIOR LATEX FLAT - NAVAJO WHITE

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see

### Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be
Special precautions	<ul> <li>hazardous. Do not reuse container.</li> <li>If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.</li> </ul>

Section 1 for emergency contact information and Section 13 for waste disposal.

Date of issue 14 September 2016Version 1

## Product name 1250-1270G PPG PAINTS MULTI-PRO MAINTENANCE INTERIOR LATEX FLAT - NAVAJO WHITE

### Section 7. Handling and storage

Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
titanium dioxide	OSHA PEL (United States, 2/2013).
	TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust
	ACGIH TLV (United States, 3/2015).
	TWA: 10 mg/m <sup>3</sup> 8 hours.
proprietary thickener, thixotropic agents	None.
methenamine 3-chloroallylochloride	None.

#### Key to abbreviations = Acceptable Maximum Peak А S = Potential skin absorption ACGIH = American Conference of Governmental Industrial Hygienists. SR = Respiratory sensitization С = Ceiling Limit SS = Skin sensitization F STEL = Short term Exposure limit values = Fume IPEL = Internal Permissible Exposure Limit TD = Total dust OSHA = Occupational Safety and Health Administration. TLV = Threshold Limit Value = Respirable TWA = Time Weighted Average R

Z = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

#### Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Date of issue 14 September 2016Version 1

Product name 1250-1270G PPG PAINTS MULTI-PRO MAINTENANCE INTERIOR LATEX FLAT - NAVAJO WHITE

### Section 8. Exposure controls/personal protection

### Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	: Safety glasses with side shields.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

### Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Not available.
Odor	: Characteristic.
Odor threshold	: Not available.
рН	: Not available.
Melting point	: Not available.
Boiling point	: >37.78°C (>100°F)
Flash point	: Closed cup: Not applicable. [Product does not sustain combustion.]
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Upper: 0%
Evaporation rate	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.

Date of issue 14 September 2016Version 1

## Product name 1250-1270G PPG PAINTS MULTI-PRO MAINTENANCE INTERIOR LATEX FLAT - NAVAJO WHITE

### **Section 9. Physical and chemical properties**

Relative density	: 1.17
Density(lbs / gal)	: 9.76
Solubility	: Soluble in the following materials: cold water.
Partition coefficient: n- octanol/water	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >0.21 cm <sup>2</sup> /s (>21 cSt)
Volatility	: 86% (v/v), 73.832% (w/w)
% Solid. (w/w)	: 26.168

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
titanium dioxide methenamine 3-chloroallylochloride	LD50 Oral LD50 Dermal	Rat Rabbit	>11 g/kg 565 mg/kg	-
o onioroanyloonionae	LD50 Oral	Rat	500 mg/kg	-
Conclusion/Summary	: There are no data available on t	he mixture itself.		
Irritation/Corrosion				
Conclusion/Summary				
Skin	: There are no data available on t	he mixture itself.		
Eyes	: There are no data available on t	he mixture itself.		
Respiratory	: There are no data available on t	he mixture itself.		
Sensitization				

Date of issue 14 September 2016Version 1

## Product name 1250-1270G PPG PAINTS MULTI-PRO MAINTENANCE INTERIOR LATEX FLAT - NAVAJO WHITE

### Section 11. Toxicological information

Dreduct/in an elient neme	00114		NTD
<b>Classification</b>			
<b>Conclusion/Summary</b>	: There ar	re no data av	vailable on the mixture itself.
Carcinogenicity			
<b>Conclusion/Summary</b>	: There ar	e no data a	vailable on the mixture itself.
<u>Mutagenicity</u>			
Respiratory	: There ar	re no data av	vailable on the mixture itself.
Skin	: There ar	re no data av	vailable on the mixture itself.
Conclusion/Summary			

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

#### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Specific target organ toxicity (single exposure)

Name	Category
proprietary thickener, thixotropic agents	Category 3

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Target organs

: Contains material which may cause damage to the following organs: upper respiratory tract, skin, eyes.

#### Aspiration hazard

Not available.

#### Information on the likely routes of exposure

### Potential acute health effects

Eye contact :	No known significant effects or critical hazards.
Inhalation	No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion :	No known significant effects or critical hazards.
Over-exposure signs/sympton	<u>ms</u>
Eye contact :	No specific data.
Inhalation	No specific data.
Skin contact :	No specific data.

#### Ingestion : No specific data.

Date of issue 14 September 2016Version 1

## Product name 1250-1270G PPG PAINTS MULTI-PRO MAINTENANCE INTERIOR LATEX FLAT - NAVAJO WHITE

### Section 11. Toxicological information

<u>Delayed and immediate effec</u>	<u>ts and also chronic effects from short and long term exposure</u>
Conclusion/Summary	: There are no data available on the mixture itself. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
<u>Short term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
<u>Long term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health effe	<u>cts</u>
General	: No known significant effects or critical hazards.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Not available.	

## Section 12. Ecological information

т	oxi	С	itv
-			

Product/ingredient name	Result	Species	Exposure
titanium dioxide methenamine 3-chloroallylochloride	Acute LC50 >100 mg/l Fresh water Acute EC50 27 to 30 ppm Fresh water	Daphnia - Daphnia magna Daphnia - Daphnia magna	48 hours 48 hours
	Acute LC50 20.5 to 23 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
methenamine 3-chloroallylochloride	-0.1	-	low

### Mobility in soil

		United States	Page: 9/12
--	--	---------------	------------

Date of issue 14 September 2016Version 1

Product name 1250-1270G PPG PAINTS MULTI-PRO MAINTENANCE INTERIOR LATEX FLAT -**NAVAJO WHITE** 

### Section 12. Ecological information

Soil/water partition coefficient (Koc)

: Not available.

### Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### Additional information

- DOT : None identified. **IMDG** : None identified.
- : None identified.

ΙΑΤΑ

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Date of issue 14 September 2016Version 1

Product name 1250-1270G PPG PAINTS MULTI-PRO MAINTENANCE INTERIOR LATEX FLAT - NAVAJO WHITE

### Section 15. Regulatory information

#### United States

United States inventory (TSCA 8b) : All components are listed or exempted.

#### SARA 302/304

SARA 304 RQ : Not applicable.

**Composition/information on ingredients** 

No products were found.

#### SARA 311/312

Classification : Delayed (chronic) health hazard

**Composition/information on ingredients** 

Name	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
titanium dioxide proprietary thickener, thixotropic agents	No. Yes.	No. No.	No. No.	No. Yes.	Yes. No.
methenamine 3-chloroallylochloride	Yes.	No.	No.	Yes.	No.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 2 \* Flammability : 0 Physical hazards : 0

(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health : 2 Flamma	ibility : 0 Instability : 0
Date of previous issue	: No previous validation
Organization that prepared the MSDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

United States Page: 11/12

Date of issue 14 September 2016Version 1

## Product name 1250-1270G PPG PAINTS MULTI-PRO MAINTENANCE INTERIOR LATEX FLAT - NAVAJO WHITE

### Section 16. Other information

as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

#### Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.