

**MSDS for: RR-808****Revised: 24-May-2005****SECTION 1:**

PRODUCT IDENTIFIER: RR-808 WET OR DRY PLASTIC ROOF CEMENT  
DATE OF PREPARATION: JULY 22, 2004  
PRODUCT USE: ROOFING SEALANT

MANUFACTURED BY: MACCO ADHESIVES  
15885 SPRAGUE RD.  
STRONGSVILLE, OHIO 44136, U.S.A.

ICI PAINTS (CANADA)  
8200 KEELE STREET  
CONCORD, ONTARIO L4K 2A5, CANADA

EMERGENCY AND MSDS TELEPHONE NUMBER: 1-800-545-2643

MSDS PREPARED BY: PRODUCT SAFETY AND TOXICOLOGY DEPARTMENT  
ICI PAINTS NORTH AMERICA

**SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

| <b>INGREDIENT</b>   | <b>WT.%</b> |
|---|-------------|
| CHEMICAL NAME: AMIDOAMINE<br>COMMON NAME: AMIDOAMINE<br>CAS NUMBER: CONFIDENTIAL  | 1-5         |
| CHEMICAL NAME: HYDRATED MAGNESIUM ALUMINUM SILICATE<br>COMMON NAME: THICKENER<br>CAS NUMBER: 12174-11-7                                 | 10-20       |
| CHEMICAL NAME: LIMESTONE<br>COMMON NAME: LIMESTONE<br>CAS NUMBER: 1317-65-3   | 30-40       |
| CHEMICAL NAME: SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC<br>COMMON NAME: MEDIUM ALIPHATIC SOLVENT NAPHTHA<br>CAS NUMBER: 64742-88-7 | 10-20       |
| CHEMICAL NAME: ASPHALT<br>COMMON NAME: ASPHALT<br>CAS NUMBER: 8052-42-4   | 30-40       |
| CHEMICAL NAME: CELLULOSE<br>COMMON NAME: CELLULOSE<br>CAS NUMBER: 9004-34-6   | 5-10        |

**SECTION 3: HAZARDS IDENTIFICATION**

PRIMARY ROUTE(S) OF EXPOSURE: INHALATION, SKIN CONTACT, EYE CONTACT,  
INGESTION

## EFFECTS OF OVEREXPOSURE

- INHALATION:** IRRITATION OF RESPIRATORY TRACT. PROLONGED INHALATION MAY LEAD TO LOSS OF APPETITE, MUCOUS MEMBRANE IRRITATION, DROWSINESS, HEADACHE, NAUSEA, CENTRAL NERVOUS SYSTEM DEPRESSION, INTOXICATION, SEVERE LUNG IRRITATION OR DAMAGE, CONVULSIONS, LOSS OF CONSCIOUSNESS, ASPHYXIATION.
- SKIN CONTACT:** IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE DERMATITIS, DEFATTING, SEVERE SKIN IRRITATION. SKIN CONTACT MAY RESULT IN DERMAL ABSORPTION OF COMPONENT(S) OF THIS PRODUCT WHICH MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION.
- EYE CONTACT:** IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE CONJUNCTIVITIS, TEARING OF EYES, REDNESS OF EYES, SEVERE EYE IRRITATION.
- INGESTION:** INGESTION MAY CAUSE LUNG INFLAMMATION AND DAMAGE DUE TO ASPIRATION OF MATERIAL INTO LUNGS, MUCOUS MEMBRANE IRRITATION, NAUSEA, GASTRO-INTESTINAL DISTURBANCES, ABDOMINAL PAIN, CENTRAL NERVOUS SYSTEM DEPRESSION.

## MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

EYE, SKIN, RESPIRATORY DISORDERS, ASTHMA-LIKE CONDITIONS

## **SECTION 4: FIRST-AID MEASURES**

- INHALATION:** REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED BREATHING. GET EMERGENCY MEDICAL ATTENTION. HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL HELP FOR ANY BREATHING DIFFICULTY.
- SKIN CONTACT:** WASH THOROUGHLY WITH SOAP AND WATER. IF ANY PRODUCT REMAINS, GENTLY RUB PETROLEUM JELLY, VEGETABLE OR MINERAL/BABY OIL ONTO SKIN. REPEATED APPLICATIONS MAY BE NEEDED. REMOVE CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING BEFORE RE-USE.
- EYE CONTACT:** FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.
- INGESTION:** IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

## **SECTION 5: FIRE-FIGHTING MEASURES**

FLASH POINT (SETA): 115 F/ 46 C. LOWER EXPLOSIVE LIMIT: NOT AVAILABLE  
UPPER EXPLOSIVE LIMIT: NOT AVAILABLE

FIRE EXTINGUISHING MEDIA: DRY CHEMICAL OR FOAM, WATER FOG, CARBON DIOXIDE

## UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE. VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED TEMPERATURES. CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE. MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT AND/OR TOXIC GASES. IN CLOSED TANKS, WATER OR FOAM MAY CAUSE FROTHING OR ERUPTION.

## FIRE FIGHTING PROCEDURES

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS. FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.

## HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS

CARBON MONOXIDE, CARBON DIOXIDE, HYDROGEN SULFIDE,  
TOXIC GASES, OXIDES OF CALCIUM

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS. ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. PLACE COLLECTED MATERIAL IN PROPER CONTAINER.

LARGE SPILLS: SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGEABLE MATERIAL AND RINSE WATER OUT OF SEWERS AND WATER COURSES.

SMALL SPILLS: USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE OF PROPERLY.

## **SECTION 7: HANDLING AND STORAGE**

### HANDLING AND STORAGE

STORE BELOW 100F (38C). KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.

### OTHER PRECAUTIONS

USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING. KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

COMMON NAME: LIMESTONE

CAS NUMBER: 1317-65-3

ACGIH(TWA): 10 MG/M3

OSHA(TWA): 5 MG/M3

COMMON NAME: MEDIUM ALIPHATIC SOLVENT NAPHTHA  
CAS NUMBER: 64742-88-7  
OSHA(TWA): 500 X PPM

COMMON NAME: ASPHALT  
CAS NUMBER: 8052-42-4  
ACGIH(TWA): 0.5 MG/M3

COMMON NAME: CELLULOSE  
CAS NUMBER: 9004-34-6  
ACGIH(TWA): 10 MG/M3 OSHA(TWA): 5 MG/M3

X AS PETROLEUM DISTILLATES

#### RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC SEALING-SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS. DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT 29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

#### VENTILATION

PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.

#### PERSONAL PROTECTIVE EQUIPMENT

EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES,  
IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

|                      |                |                      |                  |
|----------------------|----------------|----------------------|------------------|
| VAPOR PRESSURE:      | NOT AVAILABLE  | SPECIFIC GRAVITY:    | 1.327            |
| BOILING RANGE (F/C): | NOT AVAILABLE  | WEIGHT PER GALLON:   | 11.05/ 13.27 IMP |
| APPEARANCE:          | BLACK          | %VOLATILE BY VOLUME: | NOT DETERMINED   |
| PHYSICAL STATE:      | LIQUID         | SOLUBLE IN WATER:    | N                |
| PH:                  | NOT APPLICABLE |                      |                  |

### **SECTION 10: STABILITY AND REACTIVITY**

UNDER NORMAL CONDITIONS: STABLE (SEE SECTION 5 FIRE FIGHTING MEASURES)

MATERIALS TO AVOID: OXIDIZERS, ACIDS

CONDITIONS TO AVOID: ELEVATED TEMPERATURES, SPARKS, OPEN FLAME,  
IGNITION SOURCES

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

## SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME: AMIDOAMINE  
CAS NUMBER: CONFIDENTIAL  
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME: THICKENER  
CAS NUMBER: 12174-11-7  
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME: LIMESTONE  
CAS NUMBER: 1317-65-3  
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO  
LD50: 6450.00 MG/KG ORL RAT

COMMON NAME: MEDIUM ALIPHATIC SOLVENT NAPHTHA  
CAS NUMBER: 64742-88-7  
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO  
LD50: 28.00 GM/KG SKN RBT  
LD50: 28.00 GM/KG ORL RAT

COMMON NAME: ASPHALT  
CAS NUMBER: 8052-42-4  
CARCINOGENICITY LISTED BY: NTP NO IARC YES 2B OSHA NO ACGIH YES A4

COMMON NAME: CELLULOSE  
CAS NUMBER: 9004-34-6  
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO  
LD50: > 5.00 GM/KG ORL RAT  
LD50: > 2.00 GM/KG SKN RBT  
LC50: > 5800.00 GM/KG IHL RAT

### SUPPLEMENTAL HEALTH INFORMATION

NOTICE: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. OTHER EFFECTS OF OVEREXPOSURE MAY INCLUDE TOXICITY TO LUNGS.

CARCINOGENICITY: NO CARCINOGENIC EFFECTS ARE ANTICIPATED

REPRODUCTIVE EFFECTS: NO REPRODUCTIVE EFFECTS ARE ANTICIPATED

MUTAGENICITY: NO MUTAGENIC EFFECTS ARE ANTICIPATED

TERATOGENICITY: NO TERATOGENIC EFFECTS ARE ANTICIPATED

## SECTION 12: ECOLOGICAL INFORMATION

NO ECOLOGICAL TESTING HAS BEEN DONE BY ICI PAINTS ON THIS PRODUCT AS A WHOLE.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL: DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.  
AVOID DISCHARGE TO NATURAL WATERS.

### **SECTION 14: TRANSPORT INFORMATION**

DOT: ADHESIVE, COMBUSTIBLE LIQUID, UN1133, PGIII, ERG 128  
IMDG: ADHESIVES, CLASS 3, UN1133, PGIII, LIMITED QUANTITY  
IATA: CONSUMER COMMODITY, 9, ID8000  
TDG: NOT AVAILABLE

### **SECTION 15: REGULATORY INFORMATION**

|      |      |        |           |        |
|------|------|--------|-----------|--------|
| SARA | SARA | CERCLA | HAZ AIR   | MARINE |
| 302  | 313  | 302.4  | POLLUTANT | POLTNT |

THIS PRODUCT CONTAINS NO SARA 302, CERCLA 302.4 OR HAZARDOUS AIR POLLUTANT CHEMICALS. IT ALSO CONTAINS NO CHEMICALS WHICH ARE SUBJECT TO THE REPORTING REQUIREMENTS UNDER SARA 313. AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

### **SECTION 16: OTHER INFORMATION**

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH ICI PAINTS BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA. ICI PAINTS SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS MATERIAL. COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.