



GE22780 12C-Crtrg(0.695LBS-0.315KG) CAULKING

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By: Daytona Plant
703 South Street
New Smyrna Beach FL 32168

Revised: 03/08/2008
Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use: Sealant
Formula: Mixture

HMIS

Flammability: 0 Reactivity: 0 Health: 1

NFPA

Flammability: 0 Reactivity: 0 Health: 1

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING! Irritating to eyes, respiratory system and skin. Harmful by inhalation, in contact with skin and if swallowed. May cause allergic skin reaction. May cause central nervous system depression.

Form: Liquid Color: Clear Odor: acrylic

POTENTIAL HEALTH EFFECTS

INGESTION

May be harmful if swallowed. Irritation of the mouth, throat, and stomach. May cause kidney damage. May cause headache, dizziness, nausea, vomiting, gastrointestinal irritation and central nervous system depression.

SKIN

May be absorbed through skin and produce effects as listed under "Ingestion". Can cause irritation and reddening of the skin.

INHALATION

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Can irritate mucous membranes and respiratory tract with coughing and shortness of breath. Avoid inhalation of vapour or mist.

EYES

Contact can cause severe irritation and conjunctivitis (redness and swelling).

MEDICAL CONDITIONS AGGRAVATED

Central nervous system disorders. Pre-existing skin or respiratory diseases. Kidney disorders

GE22780 12C-Crtrg(0.695LBS-0.315KG) CAULKING

SUBCHRONIC (TARGET ORGAN)

Respiratory system; Kidney; Central nervous system; This product contains a component which is considered a teratogen or embryotoxin under the Canadian WHMIS act.

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

Inhalation; Dermal; Eyes

3. COMPOSITION / INFORMATION ON INGREDIENTS

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<u>A. HAZARDOUS</u>		
1,2-Ethenediol	107-21-1	< 1 %
2-(2-Methoxyethoxy)ethanol,	111-77-3	1 - 5 %
<u>B. NON-HAZARDOUS</u>		
Vendor Trade secret-Acrylic Polymer	-	30 - 60 %
Water	7732-18-5	30 - 60 %
White Mineral Oil	8042-47-5	1 - 5 %
Silica	112945-52-5	1 - 5 %

4. FIRST AID MEASURES

INGESTION

Do NOT induce vomiting. If victim is conscious, give 2-4 glasses of water. If symptoms persist, call a physician.

SKIN

Wash off with soap and water. Remove and wash contaminated clothing before re-use. Get medical attention if irritation or symptoms from Section 3 develop. Flush skin with large amounts of water for at least 15 minutes until no evidence of chemical remains.

INHALATION

Get medical attention if irritation or symptoms from Section 3 develop. If not breathing, begin artificial respiration using a barrier device. Because of chemical properties, do not use mouth-to-mouth contact. Remove to fresh air.

**GE22780 12C-Crtrg(0.695LBS-0.315KG)
CAULKING**

EYES

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

NOTE TO PHYSICIAN

Treatment is symptomatic and supportive.

5. FIRE-FIGHTING MEASURES

FLASH POINT: > 93.3 °C; 200 °F. Aqueous system
METHOD: estimated
IGNITION TEMPERATURE: Not applicable
FLAMMABLE LIMITS IN AIR - LOWER (%): Not applicable
FLAMMABLE LIMITS IN AIR - UPPER (%): Not applicable

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected., Follow normal Industrial Hygiene practices when handling

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section. Keep out of water supplies and sewers.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Avoid contact with skin and eyes. Remove and wash contaminated clothing before re-use. Keep away from children. Keep container tightly closed. Keep container dry. Do not inhale vapors. Avoid accidental ingestion of this material. Wash hands and face before eating, drinking, smoking, using toilet facilities, or applying cosmetics. Store between 40 F and 120 F. Product releases formaldehyde

**GE22780 12C-Crtrg(0.695LBS-0.315KG)
CAULKING**

during curing.

STORAGE

Keep tightly closed in a dry, cool and well-ventilated place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

Eyewash stations; Showers; Exhaust ventilation

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

PROTECTIVE GLOVES

Impermeable or chemical resistant gloves.

EYE AND FACE PROTECTION

Safety glasses with side-shields

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

Component	CAS RN	Source	Value
------------------	---------------	---------------	--------------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F:	100.00 °C; 212 °F
VAPOR PRESSURE (20 C) (MM HG):	Unknown
VAPOR DENSITY (AIR=1):	No data available
FREEZING POINT:	Unknown
MELTING POINT:	Unknown
PHYSICAL STATE:	Liquid
ODOR:	acrylic
COLOR:	Clear
EVAPORATION RATE (BUTYL ACETATE=1):	No data available

**GE22780 12C-Crtrg(0.695LBS-0.315KG)
CAULKING**

SPECIFIC GRAVITY (WATER=1):	1.05
DENSITY:	ca. 1.058 g/cm ³
ACID / ALKALINITY (MEQ/G):	Unknown
pH:	7.7 - 8.1
VOLATILE ORGANIC CONTENT (VOL):	1.3 %(m)
SOLUBILITY IN WATER (20 C):	Unknown
SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):	Unknown
VOC EXCL. H₂O & EXEMPTS (G/L):	45

10. STABILITY AND REACTIVITY

STABILITY

Stable

HAZARDOUS POLYMERIZATION

Will not occur

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide (CO₂); Formaldehyde; Carbon monoxide; Oxides of nitrogen.; Acrylic monomers

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL

Remarks: NONE FOUND

ACUTE DERMAL

Remarks: NONE FOUND

ACUTE INHALATION

Remarks: NONE FOUND

OTHER

Contains ethylene glycol which causes birth defects in laboratory animals., Repeated inhalation of ethylene glycol mist may produce signs of central nervous system involvement, particularly dizziness and nystagmus., Ethylene glycol has been shown to produce dose-related teratogenic effects in rats and mice when given by gavage or in drinking water at high concentrations or doses. The no-effect doses for developmental toxicity for ethylene glycol given by gavage over the period of organogenesis has been shown to be 150 mg/kg/day for the mouse and 500 mg/kg/day for the rat. Also, in a preliminary study to assess the effects of exposure of pregnant rats and mice to aerosols at

**GE22780 12C-Crtrg(0.695LBS-0.315KG)
CAULKING**

concentrations of 150, 1000 and 2500 mg/m³ for 6 hours a day throughout the period of organogenesis, teratogenic effects were produced at the highest concentration, but only in mice. The conditions of these latter experiments did not allow a conclusion as to whether the developmental toxicity was mediated by inhalation of aerosol, percutaneous absorption of ethylene glycol from contaminated skin, or swallowing of ethylene glycol as a result of grooming the wetted coat. In a further study, comparing effects from high aerosol concentration by whole-body or nose-only exposure, it was shown that nose-only exposure resulted in maternal toxicity (1000 and 2500 mg/m³) and developmental toxicity with minimal evidence of teratogenicity (2500 mg/m³). The no-effects concentration (based on maternal toxicity) was 500 mg/m³. In a further study in mice, no teratogenic effects could be produced when ethylene glycol was applied to skin of pregnant mice over the period of organogenesis. The above observations suggest that ethylene glycol is to be regarded as an animal teratogen. There is currently no available information to suggest that ethylene glycol has caused birth defects in humans. Cutaneous application of ethylene glycol is ineffective in producing developmental toxicity. Exposure to high aerosol concentrations is only minimally effective in producing developmental toxicity. The major route for producing developmental toxicity is perorally. Two chronic feeding studies, using rats and mice, have not produced any evidence that ethylene glycol causes dose-related increases in tumor incidence, or a different pattern of tumors compared with untreated controls. The absence of a carcinogenic potential for ethylene glycol has been supported by numerous in vitro genotoxicity studies showing that it does not produce mutagenic or clastogenic effects.

SENSITIZATION

No data available

SKIN IRRITATION

No data available

EYE IRRITATION

No data available

MUTAGENICITY

Unknown

12. ECOLOGICAL INFORMATION

ECOTOXICITY

No data available

DISTRIBUTION

No data available

CHEMICAL FATE

No data available

**GE22780 12C-Crtrg(0.695LBS-0.315KG)
CAULKING**

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

Further Information:

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION

Inventories

TSCA list	y (Positive listing)
Canada DSL Inventory	y (Positive listing)
Canada NDSL Inventory	n (Negative listing)
Japan Inventory of Existing & New Chemical Substances (ENCS)	n (Negative listing)
Australia Inventory of Chemical Substances (AICS)	n (Negative listing)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	n (Negative listing)
Korea Existing Chemicals Inventory (KECI)	n (Negative listing)
China Inventory of Existing Chemical Substances	n (Negative listing)

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

US Regulatory Information

SARA (311,312) HAZARD CLASS
Acute Health Hazard

SARA (313) CHEMICALS
50-00-0, Formaldehyde

CALIFORNIA PROPOSITION 65

WARNING! This product contains a chemical known in the State of California to cause cancer. 50-00-0, Formaldehyde. 140-88-5, Ethyl Acrylate. 108-88-3, Toluene. 872-50-4, N-METHYL PYRROLIDINONE.



**GE22780 12C-Crtrg(0.695LBS-0.315KG)
CAULKING**

Canadian Regulatory Information

WHMIS HAZARD CLASS

D2A VERY TOXIC MATERIALS, D2B TOXIC MATERIALS

Other

SCHDLE B/HTSUS: 3809.91 Water Repellent Agents

16. OTHER INFORMATION

OTHER

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate., C = ceiling limit NEGL = negligible EST = estimated NF = none found
NA = not applicable UNKN = unknown NE = none established REC = recommended ND = none determined V = recommended by vendor SKN = skin TS = trade secret R = recommended MST = mist NT = not tested STEL = short term exposure limit ppm = parts per million ppb = parts per billion By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).