Material Safety Data Sheet



SOLID STAINAWAY

Section 1. Chemical product and company identification

Trade name

: SOLID STAINAWAY

Product use

: Laundry product

Supplier

; Ecolab Inc. Institutional Division

370 N. Wabasha Street St. Paul. MN 55102 1-800-352-5326

Code

: 904524

Date of issue

: 03-May-2006

EMERGENCY HEALTH INFORMATION: 1-800-328-0026 Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, information on ingredients

	CAS number	% by weight
Name triphosphoric acid, pentasodium salt	7758-29-4	2
troclosene sodium, dihydrate	51580-86-0	>50
1-octanesulfonic acid, sodium salt	5324-84-5	1 - 5

Section 3. Hazards identification

Physical state

; Solid (Cast Solid)

Emergency overview

: WARNING!

CAUSES SEVERE EYE AND SKIN IRRITATION. Untreated contact may cause severe

irritation or chemical burns. HARMFUL IF SWALLOWED.

Do not ingest. Do not get in eyes, on skin or on clothing. Avoid breathing dust. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Potential acute health effects

Eyes

; Severely irritating to eyes. Untreated contact may cause chemical burns.

Skin.

: Severely irritating to the skin. Untreated contact may cause severe irritation or chemical

burns.

Inhalation

: No known significant effects or critical hazards.

ingestion

: Harmful if swallowed. Causes burns to mouth, throat and stomach.

See toxicological information (section 11)

Section 4. First aid measures

Eye contact

: In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention

Skin contact

immediately. : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes

thoroughly before reuse. Get medical attention immediately.

Inhalation

: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult,

give oxygen. Get medical attention immediately.

Ingestion

: Rinse mouth; then drink one or two large glasses of water. Do not induce vomiting. Never give

anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire fighting measures

Flash point

: > 100°C

Product does not support combustion.

Products of combustion Fire-fighting media and instructions

These products are halogenated compounds, hydrogen chloride.

Use an extinguishing agent suitable for the surrounding fire.

Dike liquid for later disposal.

No specific hazard.

for fire-fighters

Special protective equipment: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

Section 6. Accidental release measures

Personal precautions : Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Do not allow to enter drains or watercourses.

Environmental precautions Methods for

cleaning up

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

: If emergency personnel are unavailable, vacuum or carefully scoop up spilled material and place in an appropriate container for disposal by incineration. Avoid creating dusty conditions and prevent wind dispersal.

Section 7. Handling and storage

Handling

: Do not ingest. Do not get in eyes or on skin or clothing. Do not breathe dust. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Storage

Keep out of the reach of children. Keep container tightly closed. Keep container in a cool, wellventilated area.

Do not store above 50°C

Section 8. Exposure controls, personal protection

Engineering

: Good general ventilation should be sufficient to control airborne levels.

controls

Personal protection

Eyes

: Due to the form and packaging of the product, no protective equipment is needed under normal

use conditions.

Hands

: Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.

Skin

Due to the form and packaging of the product, no protective equipment is needed under normal

use conditions.

Respiratory

: A respirator is not needed under normal and intended conditions of product use.

Name chlorine Exposure limits ACGIH TLV (United States, 1/2005).

STEL: 2.9 mg/m3 15 minute/minutes. Form: All forms STEL: 1 ppm 15 minute/minutes. Form: All forms TWA: 1.5 mg/m3 8 hour(s). Form: All forms TWA: 0.5 ppm 8 hour(s). Form: All forms OSHA PEL (United States, 8/1997). CEIL: 3 mg/m3 Form: All forms

CEIL: 1 ppm Form: All forms

SOLID STAINAWAY Page: 3/4

Section 9. Physical and chemical properties

Physical state

Solid. (Cast Solid)

Color

White.

Odor Нα

: chlorine : 9.1 (1%)

Solubility

: Partially soluble in cold water, hot water.

Section 10. Stability and reactivity

Stability

: The product is stable.

Reactivity

: Highly reactive with acids.

Reactive with reducing agents, combustible materials, organic materials.

Mixing this product with acid or ammonia releases chloring gas.

Do not allow water to enter container. Wet material may generate halogenated gas

that may pressurize sealed containers.

Hazardous decomposition: These products are halogenated compounds, hydrogen chloride, chlorine.

products

Hazardous polymerization: Will not occur.

Section 11. Toxicological information

Potential acute health effects

Eyes

: Severely irritating to eyes. Untreated contact may cause chemical burns.

Skin

Severely irritating to the skin. Untreated contact may cause severe irritation or chemical

Inhalation

. No known significant effects or critical hazards.

Ingestion

: Harmful if swallowed. Causes burns to mouth, throat and stomach.

Potential chronic health effects

Section 12. Ecological information

Products of degradation

; These products are carbon oxides (CO, CO₂) and water, nitrogen oxides (NO, NO₂ etc.), sulfur oxides (SO₃, SO₃ etc.), halogenated compounds, phosphates. Some metallic oxides.

Section 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport information

Regulatory Information	UN number	Proper shipping name	Class	Packing group	Additional information
DOT	Not	-	-	-	-
Classification	regulated.		<u> </u>	<u> </u>	<u> </u>

APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

SOLID STAINAWAY

Page: 4/4

Section 15. Regulatory information

HCS Classification

U.S. Federal regulations

: Corrosive material

: SARA 302/304/311/312 extremely hazardous substances: No products were

found.

SARA 302/304 emergency planning and notification: No products were found.

TSCA 8(b) inventory California Prop. 65

: All materials are listed or exempt.

: WARNING: This product contains a chemical known to the State of California to

cause cancer.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Fire hazard 0

Reactivity 1

Personal protection

Date of issue

Responsible name
Date of previous issue

03-May-2006.

: Regulatory Affairs : No previous validation.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.