



MATERIAL SAFETY DATA SHEET

PO Box 1090 • Menomonee Falls, WI 53052-1090
N92 W14701 Anthony Ave • Menomonee Falls, WI 53051-1630
800-966-7580 • 262-255-9500 • Fax 262-255-0684

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT CODE . . . : 08552 048905 604
PRODUCT NAME . . . : 11200 EBI-WHITE 0
PRODUCT CLASS . . . : Aerosol Product

MSDS PREPARATION DATE : 03/08/2000

MANUFACTURER IDENTIFICATION:

RAABE CORPORATION
PO BOX 1090

CUSTOMER IDENTIFICATION:

EBI Ltd.
1751 Robinhood Road

MENOMONEE FALLS WI 53052 Vista, CA 92084

EMERGENCY TELEPHONE NUMBERS:

24 HOURS A DAY - CALL CHEMTREC : 800-424-9300
INTERNATIONAL CALLS TO CHEMTREC : 703-527-3887
8 AM TO 4:30 PM CENTRAL TIME : 262-255-9500

SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

1 2-PENTANONE

CAS# 107-87-9

2-PENTANONE

PCT BY WT: 8.0000 LEL 1.50

EXPOSURE LIMIT:

ACGIH TLV-TWA 200 ppm
ACGIH TLV-STEL 250 ppm
OSHA PEL-TWA 200 ppm
COMPANY N.E.

2 N-BUTANE

CAS# 106-97-8

N-BUTANE

PCT BY WT: 14.0000 VAPOR PRESSURE: 879.100 MMHG @ 68F LEL 1.80

EXPOSURE LIMIT:

ACGIH TLV-TWA 800 ppm
ACGIH TLV-STEL NO INFO
OSHA PEL-TWA 800 ppm
COMPANY N.E.

3 PROPANE

CAS# 74-98-6

PROPANE

PCT BY WT: 15.0000 VAPOR PRESSURE: 5585.200 MMHG @ 68F LEL 2.20

EXPOSURE LIMIT:

ACGIH TLV-TWA 1000 ppm
ACGIH TLV-STEL NO INFORMATION

RAABE CORPORATION
MATERIAL SAFETY DATA SHEET
01

08552 048905 604

4 TITANIUM DIOXIDE

CAS# 13463-67-7

TITANIUM DIOXIDE

PCT BY WT: 4.0000

EXPOSURE LIMIT:

ACGIH TLV-TWA 10 mg/m3

ACGIH TLV-STEL NO INFO

OSHA PEL-TWA 10 mg/m3

COMPANY N.E.

5 XYLENE

CAS# 1330-20-7

XYLENE

PCT BY WT: 2.0000

LEL 1.00

EXPOSURE LIMIT:

ACGIH TLV-TWA 100 ppm

ACGIH TLV-STEL 150 ppm

OSHA PEL-TWA 100 ppm

COMPANY N.E.

6 ACRYLIC POLYMER

ACRYLIC POLYMER

PCT BY WT: 3.0000

EXPOSURE LIMIT:

ACGIH TLV-TWA N.E.

ACGIH TLV-STEL N.E.

OSHA PEL-TWA N.E.

COMPANY N.E.

7 BUTYL BENZYL PHTHALATE

CAS# 85-68-7

BUTYL BENZYL PHTHALATE

PCT BY WT: 1.0000

LEL .30

EXPOSURE LIMIT:

ACGIH TLV-TWA 5 mg/m3

ACGIH TLV-STEL N.E.

OSHA PEL-TWA 5 mg/m3

8 ACETONE

CAS# 67-64-1

ACETONE

PCT BY WT: 41.0000 VAPOR PRESSURE: 185.000 MMHG @ 68F LEL 2.60

EXPOSURE LIMIT:

ACGIH TLV-TWA 750 ppm

ACGIH TLV-STEL 1000 ppm

OSHA PEL-TWA 750 ppm

OSHA PEL-STEL 1000 ppm

COMPANY N.E.

RAABE CORPORATION
 MATERIAL SAFETY DATA SHEET
 01

08552 048905 604

9 ETHYLENE GLYCOL MONOPROPYL ETH
 CAS# 2807-30-9
 ETHYLENE GLYCOL MONOPROPYL ETHER
 PCT BY WT: 1.0000 VAPOR PRESSURE: 1.200 MMHG @ 68F LEL 1.30
 EXPOSURE LIMIT:
 ACGIH TLV-TWA NO INFO
 ACGIH TLV-STEL NO INFO

10 ETHYL 3-ETHOXYPROPIONATE
 CAS# 763-69-9
 ETHYL 3-ETHOXYPROPIONATE
 PCT BY WT: 3.0000 VAPOR PRESSURE: 1.110 MMHG @ 68F LEL 1.10
 EXPOSURE LIMIT:
 ACGIH TLV-TWA 50 ppm
 ACGIH TLV-STEL NONE EST.
 OSHA PEL-TWA 50 ppm
 COMPANY N.E.

11 PROPYLENE GLYCOL METHYL ETHER
 CAS# 108-65-6
 PROPYLENE GLYCOL METHYL ETHER ACETATE
 PCT BY WT: 1.0000 VAPOR PRESSURE: 3.700 MMHG @ 68F LEL 1.30
 EXPOSURE LIMIT:
 ACGIH TLV-TWA NOT ESTABLISHED
 ACGIH TLV-STEL NOT ESTABLISHED

 This product contains no reported carcinogens or suspected
 carcinogens.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Harmful if swallowed.
 Harmful if inhaled.
 Causes eye irritation.
 Causes skin irritation.
 Vapors irritating to eyes and respiratory tract.
 Extremely flammable liquid and vapor.
 Vapors may cause flash fire or explosion.
 Extremely flammable aerosol.
 Contents under pressure.

POTENTIAL HEALTH EFFECTS:

EYE:

May cause severe eye irritation.

SKIN:

May cause skin irritation.

Prolonged or repeated contact may cause drying, cracking, or irritation

RAABE CORPORATION
MATERIAL SAFETY DATA SHEET
01

08552 048905 604

of the skin.

Product contains a component which can be absorbed through the skin. Excessive exposure may cause hemolysis (red blood cell damage) which can impair the blood's ability to transport oxygen.

INHALATION:

Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation.

Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.

Liquid or vapor may be irritating to skin, eyes, throat or lungs.

Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.

INGESTION:

Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis.

Aspiration of material into the lungs if swallowed or if vomiting occurs can cause chemical pneumonitis which can be fatal.

CHRONIC EFFECTS:

Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals:

- Kidney damage
- Eye damage
- Liver damage
- Anemia

Chronic overexposure to a component or components in this product has been suggested as a cause of the following effects in humans:

- Cardiac abnormalities

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Contains butyl benzyl phthalate which has been shown to cause cancer in at least one study in laboratory animals. Butyl benzyl phthalate is not listed by OSHA, IARC or NTP as a carcinogen.

Rats exposed to titanium dioxide dust at 250 mg/m³ developed lung cancer, however, such exposure levels are not attainable in the workplace with this material.

SECTION 4 - FIRST AID MEASURES**EYE CONTACT:**

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

Flush with large quantities of water for 15 minutes.

SKIN CONTACT:

Wash thoroughly with soap and water and seek medical attention. Remove contaminated clothing. Launder contaminated clothing before reuse.

INHALATION:

For inhalation overexposure move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention.

INGESTION:

Since this product may contain materials which can cause lung damage if

RAABE CORPORATION
MATERIAL SAFETY DATA SHEET
01

08552 048905 604

aspirated into the lungs, the decision whether to induce vomiting or not must be made by a physician after careful consideration of all materials ingested.

NOTE TO PHYSICIAN:

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE PRODUCT:

| | |
|-------------------------------|--------------------|
| Flashpoint | : Less Than -25 °F |
| Explosion Level | : Low - .3 |
| | High - 100.0 |
| Flammability Limits | : Lower - -N/A |
| | Higher - -N/A |

EXTINGUISHING MEDIA:

Use Dry Chemical, Carbon Dioxide or Chemical Foam.

FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Keep containers tightly closed. Isolate from heat, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Contents under pressure. Do not use or store near sources of heat, sparks or open flame. Keep away from any source of heat such as sunlight, heaters or stoves that could cause the container to burst. Do not puncture or incinerate. Do not crush or place in a garbage compactor. Do not store above 120 degrees F. Aerosol containers may explode when exposed to extreme heat.

Product vapors are heavier than air and may travel a long distance to a source of ignition and flash back.

Full protective equipment including self-contained breathing apparatus to avoid inhalation of vapors should be used.

Water spray should not be used except to keep down vapors or cool closed containers to prevent build-up of pressure. If water is used, fog nozzles are preferred.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CLEAN-UP AND CONTAINMENT:

Remove all sources of ignition. Avoid heat, sparks, flames and anything which could cause fire.

Ventilate area of spill and adjacent low lying areas. Avoid breathing solvent vapors. Remove with inert absorbant materials and non-sparking tools.

SECTION 7 - HANDLING AND STORAGE

HANDLING:

Wash hands thoroughly after handling.

STORAGE:

Store in a cool dry area with ventilation suitable for storing materials shown in section 2.

Keep away from heat, sparks and flame.

RAABE CORPORATION
 MATERIAL SAFETY DATA SHEET
 01

08552 048905 604

Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120 degrees F.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

ENGINEERING CONTROLS:

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

RESPIRATORY PROTECTION:

If workplace exposure limits are exceeded for any component (see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

SKIN PROTECTION:

Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.

EYE PROTECTION:

Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.

OTHER PROTECTIVE EQUIPMENT:

Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.

HYGIENIC PRACTICES:

Wash hands before eating or smoking. Smoke in designated areas only.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|--------------------------------------|---|-------------------|-----------------------|
| Vapor Pressure | : | 5585.20 | mm Hg @ 20 C |
| Vapor Density | : | -N/A | |
| Boiling Range | : | Lower - 1.0 °F | |
| | | Higher - 999.0 °F | |
| Specific Gravity | : | .744 | |
| Formula Weight per Volume | : | 6.1958 | LB/GL |
| VOC (Calculated, LB/GAL) | : | 4.410 | |
| VOC (Calculated, GM/L) | : | 528.45 | |
| Percent Volatile by Weight | : | 86.6037 | |
| Evaporation Rate | : | 7.700 | (n-Butyl Acetate = 1) |
| Viscosity | : | -N/A | |

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID:

Avoid contact with heat, sparks, and open flame.

Product may explode if heated. Keep cool, avoid exposure to heat.

INCOMPATIBILITIES:

Strong oxidizing agents.

DECOMPOSITION:

Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.

POLYMERIZATION:

08552 048905 604

RAABE CORPORATION
MATERIAL SAFETY DATA SHEET
01

No hazardous polymerization will occur under normal conditions.

STABILITY:

The product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

No specific information is available. Please refer to Section 3 for available information on potential health effects.

SECTION 12 - ECOLOGICAL INFORMATION

No specific ecological information is available for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

Domestic ground shipment of Paint Aerosols and all liquid paint products in Containers of 1 Quart or less: CONSUMER COMMODITY, ORM-D

Domestic air shipment of Paint Aerosols and all liquid paint in containers of 1 quart or less: CONSUMER COMMODITY, CLASS 9, ID 8000, MISCELLANEOUS LABEL

International Air Shipments of Paint Aerosols: AEROSOLS, FLAMMABLE, N.O.S. CLASS 2.1, UN 1950, FLAMMABLE GAS LABEL

International Air Shipment of liquid paint in containers of 1 quart or less: PAINT, CLASS 3, UN 1263, FLAMMABLE LIQUID LABEL

All shipments of Liquid Paint in containers of more than 1 quart: PAINT, CLASS 3, UN 1263, PACKING GROUP II, FLAMMABLE LIQUID LABEL

See 49 CFR 172.101, Hazardous Materials Table 1 for more information on shipping hazardous materials on land.

See IATA Dangerous Goods Regulations for more details on shipping hazardous materials by air.

SECTION 15 - REGULATORY INFORMATION

SARA 313 INFORMATION:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

RAABE CORPORATION
MATERIAL SAFETY DATA SHEET
01

08552 048905 604

XYLENE

CAS# 1330-20-7 PCT BY WT: 1.8970

ETHYLENE GLYCOL MONOPROPYL ETHER

CAS# 2807-30-9 PCT BY WT: 1.3560

FEDERAL REGULATIONS:

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 inventory.

STATE REGULATIONS:

NEW JERSEY RIGHT-TO-KNOW

No non-hazardous ingredients are among the top five ingredients

PENNSYLVANIA RIGHT-TO-KNOW

No non-hazardous ingredients are present greater than 3%

INTERNATIONAL REGULATIONS:

CANADA: The chemical substances in this product are listed on the Canadian Domestic Substances List.

SECTION 16 - OTHER INFORMATION

HMS RATINGS:

HEALTH: 2* FLAMMABILITY: 4 REACTIVITY: 0 PERSONAL PROTECTION: G