

Material Safety Data Sheet

May be used to comply with OSHA's
Hazardous Communication Standard, 29 CFR 1910.1200

IDENTITY (As used on LABELS and LIST)

Namco

White Lightning Tile & Grout Cleaner

NOH 600

NPCA Hazardous Materials Identification System

Specific Hazard	Personal Protection
4-Severe	X-Ask a supervisor
3-Serious	A-Safety Glasses
2-Moderate	B-Goggles, Gloves
1-Slight	C-Goggles, Gloves, Apron
0-Minimal	D-Goggles, Gloves, Apron, & Faceshield

Health (4)

Flammability (0)

Reactivity (3)

Personal Protection (D)

SECTION I

MFGR'S NAME AND ADDRESS

SUNLINE L.L.C.

1300 ALDEN ROAD - ORLANDO, - FL 32803-1895

EMERGENCY TELEPHONE NUMBER
NIGHTS / WEEKENDS

407- 896-2129
(407) 415-8751

DATE PREPARED:
1-23-09

SECTION II-HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Hazardous Components	OSHA	PEL	ACGIH	Other Limits Recommended	%Optional
Specific Component(s) Specific Chemical Identity Common Name(s)					
Hydrogen Chloride CAS #7647-01-0	5ppm		5ppm-ceiling		15.0

SECTION III-PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT (F)	Over 212°F	SPECIFIC GRAVITY (H ₂ O=1)	1.0824
VAPOR PRESSURE (mmHg)	N/A	MELTING POINT	N/A
VAPOR DENSITY (air=1)	N/A	EVAPORATION POINT	Less than 1 (Butyl Acetate=1)
SOLUBILITY IN WATER	Complete		
APPEARANCE AND ODOR:	Milky, white, liquid with a mint wintergreen scent.		

SECTION IV-FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED)	FLAMMABLE LIMITS	LEL	UEL
Closed Cup- Over 350°F	N/A	N/A	

EXTINGUISHING MEDIA: Water Fog, Carbon Dioxide or Dry Chemical

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode and protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Acid reacts with most metals to release hydrogen gas which can form explosive mixtures with the air.

