# Accumetric, Inc. 350 Ring Road Elizabethtown, KY 42701 (800) 928-2677

# PRODUCT IDENTIFICATION

TEMENICAL NAME:

RTV SILICONE ADHESIVE

SEALANT

CUSTOMER NAME:

MARS Silicone

PERCENT BY WEIGHT: 2.00%

PERCENT BY WEIGHT: 2.00%

PERCENT BY WEIGHT: 10.00%

Sealant

CHEMICAL FAMILY:

SILICONE

FORMULA: MIXTURE

HAZARD CLASS:

U.M. NUMBER:

PACKING GROUP:

HAZARDOUS INDREDIENTS

NAME: METHYLTRIACETOXYSILANE

CAS NUMBER: 004153343

ACGIH TLV: NONE ESTABLISHED

OSHA PEL: NONE ESTABLISHED

OSHA STEL: NONE ESTABLISHED

NAME: ETHYLTRIACETOXYSILANE

CAS NUMBER: 017689779

ACGIH TLV: NONE ESTABLISHED NONE ESTABLISHED

OSHA STEL: NONE ESTABLISHED

NAME: SILICA

CAS NUMBER: 007631869

ACGIH TLV: 10 MG/M3

OSHA PEL: NONE ESTABLISHED

OSHA STEL: NONE ESTABLISHED

NON-HAZARDOUS INGREDIENT: POLYDIMETHYSILOXANE

PHYSICAL PROPERTIES

BOILING POINT: N/A

VAPOR PRESSURE (MM HG): <5 MM VAPOR DENSITY (AIR-1): N/A SOLUBILITY IN WATER: <0.1%

APPEARANCE AND ODOR: ACETIC ACID-LIKE PASTE

SPECIFIC GRAVITY (H20=1): 1.04

MELTING POINT: N/A

EVAPORATION RATE (ETHER 1); <1

Accumetric, Inc. 350 Ring Road Elizabethtown, KY 42701 (800) 928-2677

# PRODUCT IDENTIFICATION

CHEMICAL NAME:

CUSTOMER NAME:

RTV SILICONE ADHESIVE

MARS Silicone

SEALANT

Sealant

CHEMICAL FAMILY:

SILICONE

FORMULA:

MIXTURE

HAZARD CLASS:

U.N. NUMBER:

PACKING GROUP:

## HAZARDOUS INDREDIENTS

NAME: METHYLTRIACETOXYSILANE

CAS NUMBER: 004153343

PERCENT BY WEIGHT: 2.00%

ACGIH TLV: NONE ESTABLISHED OSHA PEL: NONE ESTABLISHED OSHA STEL: NONE ESTABLISHED

NAME: ETHYLTRIACETOXYSILANE

PERCENT BY WEIGHT: 2.00%

CAS NUMBER: 017689779
ACGIH TLV: NONE ESTABLISHED
OSHA PEL: NONE ESTABLISHED
OSHA STEL: NONE ESTABLISHED

NAME: SILICA

CAS NUMBER: 007631869 ACGIH TLV: 10 MG/M3

FERCENT BY WEIGHT: 10.00%

OSHA PEL: NONE ESTABLISHED

OSHA STEL: NONE ESTABLISHED

NON-HAZARDOUS INGREDIENT: POLYDIMETHYSILOXANE

## PHYSICAL PROPERTIES

BOILING POINT: N/A

VAPOR PRESSURE (MM HG): <5 MM VAPOR DENSITY (AIR=1): N/A SOLUBILITY IN WATER: <0.1%

APPEARANCE AND ODOR: ACETIC ACID-LIKE PASTE

SPECIFIC GRAVITY (H20-1): 1.04

MELTING POINT: N/A

EVAPORATION RATE (ETHER 1): <1

## FIRE AND EXPLOSION HAZARD DATA

FLASH POINT & METHOD: 212 DEG F/100 DEG C OPEN CUP-

FLAMMABLE LIMITS: NOT DETERMINED

LEL%: N/D UEL%: N/

EXTINGUISHING MEDIA: WATER, WATER FOG, CO2, DRY CHEMICAL, FOAM

SPECIAL FIRE FIGHTING PROCEDURES:

SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD

BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE KNOWN.

## REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID: AIR OR MOISTURE CAUSES POLYMERIZATION AND

ACETIC ACID VAPORS ARE FORMED.

INCOMPATIBILITY: OXIDIZING MATERIAL CAN CAUSE A REACTION.

HAZARDOUS DECOMPOSTION OR BYPRODUCTS:

SILICONE DIOXIDE, CARBON DIOXIDE, AND TRACES OF INCOMPLETELY

BURNED CARBON PRODUCTS.

HAZARD POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: NONE

### HEALTH HAZARD DATA

ROUTES OF ENTRY:

INHALATION: YES SKIN: YES INGESTION: YES

HEALTH HAZARDS: NONE KNOWN

CARCINOGENICITY: NTP: NO IARC MONOGRAPHS: NO

OSHA REGULATED: NO

SIGNS AND SYMPTOMS OF EXPOSURE:

INGESTION: MAY CAUSE STOMACH DISCOMFORT

SKIN CONTACT: UNCURED PRODUCT MAY IRRITATE LIPS, GUMS, TONGUE,

AND SKIN.

EYE CONTACT: UNCURED PRODUCT CONTACT IRRITATE EYES.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN

EMERGENCY AND FIRST AID PROCEDURES:

EYES: FLUSH WITH WATER FOR 15 MINUTES. OBTAIN MEDICAL ATTENTION

SKIN: WIPE OFF AND FLUSH WITH WATER

INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION

ORAL: OBTAIN MEDICAL ATTENTION

Comments:

When heated to temperatures above 150°C (300°F) in the presence of air, product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate eyes, nose and throat. Safe handling conditions may be maintained by keeping vapor concentrations within the OSHA permissible exposure limit for formaldehyds.

### PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE PRODUCT AND USE ABSORBENT MATERIAL TO TAKE CARE OF ANY OIL-LIKE RESIDUES.

WASTE DISPOSAL METHOD:

REVIEW ALL LOCAL, STATE, AND FEDERAL REGULATIONS CONCERNING HEALTH AND POLLUTION TO DETERMINE APPROVED DISPOSAL METHOD. PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE BELOW 90 DEG. F. USE REASONABLE CARE AND CAUTION. OTHER PRECAUTIONS:

NONE KNOWN

#### CONTROL MEASURES

RESPIRATORY PROTECTION:

ACID GAS/ORGANIC VAPOR TYPE

VENTILATION:

LOCAL EXHAUST: NONE ESTABLISHED

MECHANICAL: NONE

SPECIAL: N/A

OTHER: N/A

PROTECTIVE GLOVES: USE CHEMICAL WORKERS GLOVES.

EYE PROTECTION: USE PROPER EYE PROTECTION, SAFETY GLASSES AS

MINIMUM.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

NONE

WORK PRACTICES:

GROSS AMOUNTS OF MATERIAL SHOULD BE REMOVED FROM THE SKIN AS SOON AS PRACTICAL, ESPECIALLY BEFORE EATING OR SMOKING.

DATE PREPARED: May 5, 1999