

MATERIAL SAFETY DATA SHEET
PRO STOCK Acrylic Adhesive Sealant
CENTURY PART# 458210

Sealant Technology
Emergency Phone Numbers
Day (713)691 6500
Night (800) 938 3232
PO Box 16950.

Houston. Texas 77222
919 Crosstimbers. Houston, TX 77022

HAZARD RATING: FIRE - INSIGNIFICANT
REACTIVITY - INSIGNIFICANT
TOXICITY - SLIGHT
SPECIAL - NONE

Product Name.: Pro Stock COLORS Acrylic Adhesive Sealant
Tube Code; 26011, 27011 29011 & 30011
DOT Hazard Class: Nonregulated
Material Description: Generic Aqueous Caulk Formulation
Dot. Issued: July 1, 1995 OSHA Hazardous WHMIS Controlled

I - COMPOSITIONAL INFORMATION

	Approx Wt %	TLV
Bulyl BenzyI Phthalate	7% Max	NE
Mineral Spirits	3% Max	100 ppm
Ethylene Glycol	2% Max	50 ppm Ceiling

II - PHYSICAL PROPERTY INFORMATION

Appearance: Milky White Paste Odor: Acrylic Resin Odor Viscosity: Variable
Melting and Freezing Point: Variable Boiling Point: Variable
Vapor Pressure (mmHg): Greater Than 1
Vapor Density (Air=1): Less than 1 Solubility in water: Dilutable
Percent Volatile by Weight: 25%Max
Specific Gravity (Water = 1): Greater Than 1
Evaporation Rate (Butyl Acetate = 1): Less Than 1

III - FIRE AND EXPLOSION HAZARD INFORMATION

Flash Point: Non-Combustible Auto Ignition Temperature: Not Applicable
Lower Explosion Limit: Not Applicable Upper Explosion Limit: Not Applicable
Extinguishing Media: Not Applicable
Special Fire Fighting Procedures: None
Unusual Fire and Explosion Hazards: Material can splatter above 100C/212F. Polymer film can burn.

IV - HEALTH HAZARD INFORMATION

This product is not a carcinogen under NTP, TARC and OSHA
Effects Of Overexposure:
INHALATION: Vapor can irritate nose, throat and lungs in high concentrations.
EYE CONTACT: Moderately Irritating to the eyes.
SKIN CONTACT: May cause drying and cracking of the skin with repeated contact.

Emergency and First Aid Procedures:

INHALATION: Move subject to fresh air.
EYE AND SKIN CONTACT: Flush eyes with a large amount of water for at least 15 minutes. See a physician if irritation persists. Wash affected skin areas with soap and water.
INGESTION: If swallowed, dilute by giving 2 glasses of water to drink. See a physician. Never give anything by mouth to an unconscious person.

NOTE TO PHYSICIAN: Petroleum hydrocarbons can cause CNS effects. If swallowed, careful evacuation of the stomach is advised.

V - REACTIVITY INFORMATION

Stability: Stable Conditions to Avoid: Decomposition is dependent on time and temperature. Onset of polymer decomposition is at 117C/350F.
Hazardous Decomposition Products: Not Applicable
Hazardous Polymerization: Will not occur Conditions to Avoid; Not Applicable
Incompatibility: (Materials to Avoid): Not Applicable

VI- SPILL OR LEAK PROCEDURE INFORMATION

Steps to be taken in case material is released or spilled:
Keep spectators away. The sealant may cause the floor to be slippery. Use care to avoid falling. Scoop or shovel solid material into a suitable container for recovery or disposal. Keep spills and cleaning runoff out of municipal sewers and open bodies of water.
Waste Disposal Methods:
Waste product should be incinerated or disposed of in an approved commercial landfill in accordance with local, state and federal regulations.

VII- SPECIAL PROTECTION INFORMATION

Ventilation Type: Mechanical local exhaust ventilation in areas of confined usage.
Respiratory Protection: Where exposure limits are exceeded, wear a suitable respirator (MSHA/NIOSH approved or equivalent).
Protective Gloves: When use gives continuous exposure to the product gloves are recommended. Eye Protection: Protective Goggles

VIII- STORAGE AND HANDLING INFORMATION

Storage Temperature; Maximum - 60C/140F Minimum - 1C/34F
PRECAUTIONARY LABELING: PROTECT FROM FREEZING

IX - SPECIAL PRECAUTIONS

PRECAUTIONARY WARNINGS: DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.

X - MISCELLANEOUS INFORMATION

NE - Not Established
TLV - OSHA and ACGIH Threshold Limit Value
The effects of overexposure shown in Section IV are based on information about similar materials and on toxicity profiles for the solvents in this product.

The information contained in this Material Safety Data Sheet is based on data considered to be accurate. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Sealant Technology Inc. assumes no responsibility for personal injury or property damage to distributor, users or third parties caused by the product. Distributors and users of the product assume all risk associated with the use of the product.