



HAZARDS IDENTIFICATION (ANSI Section 3)

Primary route(s) of exposure : Inhalation, skin contact, eye contact, ingestion.

Effects of overexposure :

Inhalation : Irritation of respiratory tract, lungs. Prolonged inhalation may lead to mucous membrane irritation, drowsiness, dizziness and/or lightheadedness, headache, nausea, coughing, central nervous system depression, difficulty of breathing, severe lung irritation or damage, kidney damage, pneumoconiosis.

Skin contact : Irritation of skin. Prolonged or repeated contact can cause dermatitis, defatting. Possible sensitization to skin.

Eye contact : Irritation of eyes. Prolonged or repeated contact can cause conjunctivitis, tearing of eyes, redness of eyes.

Ingestion : Ingestion may cause mouth and throat irritation, dizziness and/or lightheadedness, headache, nausea, vomiting, gastro-intestinal disturbances, severe abdominal pain, abdominal damage, pulmonary edema, loss of consciousness, acute poisoning, respiratory failure, cardiac failure, brain damage.

Medical conditions aggravated by exposure : Eye, skin, respiratory disorders, lung disorders, asthma-like conditions, kidney disorders, respiratory disorders.

FIRST-AID MEASURES

Inhalation : Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical help for any breathing difficulty.

Skin contact : Wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin. Repeated applications may be needed. Remove contaminated clothing. Wash contaminated clothing before re-use.

Eye contact : Flush immediately with large amounts of water, especially under lids for at least 15 minutes. If irritation or other effects persist, obtain medical treatment.

Ingestion : If swallowed, obtain medical treatment immediately.

FIRE-FIGHTING MEASURES

Fire extinguishing media : Dry chemical or foam water fog. Carbon dioxide. Closed containers may burst if exposed to extreme heat or fire. In closed tanks, water or foam may cause frothing or eruption.

Fire fighting procedures : Water may be used to cool and protect exposed containers. Firefighters should use full protective clothing, eye protection, and self-contained breathing apparatus.

Hazardous decomposition or combustion products : Carbon monoxide, carbon dioxide. Oxides of calcium.

ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled : Comply with all applicable health and environmental regulations. Eliminate all sources of ignition. Ventilate area. Spills may be collected with absorbent materials. Evacuate all unnecessary personnel. Place collected material in proper container. Small spills - use absorbent to pick up residue and dispose of properly.

HANDLING AND STORAGE

From freezing.

Handling and storage : Store below 100°F (38°C). Keep away from heat, sparks and open flame. Keep

Other precautions : Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes, and breathing of vapors. Wash hands thoroughly after handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. Avoid conditions which result in formation of inhalable particles such as spraying or abrading (sanding) painted surfaces. If such conditions cannot be avoided, use appropriate respiratory protection as directed under exposure controls/personal protection.

EXPOSURE CONTROLS/PERSONAL PROTECTION (ANSI Section 8)

Respiratory protection : Control environmental concentrations below applicable exposure standards when using this material. When respiratory protection is determined to be necessary, use a NIOSH/MSHA (Canadian 294.4) Approved elastomeric sealing- surface facepiece respirator outfitted with organic vapor cartridges and paint spray (dust/mist) prefilters. Determine the proper level of protection by conducting appropriate air monitoring. Consult 29CFR1910.134 For selection of respirators (Canadian 294.4).

Ventilation : Provide dilution ventilation or local exhaust to prevent build-up of vapors.

Personal protective equipment : Eye wash, safety shower, safety glasses or goggles. Impermeous gloves, impermeous clothing.

STABILITY AND REACTIVITY

Under normal conditions : Stable see section 5 fire fighting measures

Materials to avoid : Oxidizers, acids, ammonium salts, hydrogen fluoride. Styrene monomer.

Conditions to avoid : Elevated temperatures, contact with oxidizing agent, freezing, sparks, open flame.

Hazardous polymerization : Will not occur

TOXICOLOGICAL INFORMATION

Supplemental health information : No additional effects are anticipated

Carcinogenicity : Contains crystalline silica which is considered a hazard by inhalation. IARC has classified crystalline silica as carcinogenic to humans (group 1). Crystalline silica is also a known cause of silicosis, a noncancerous lung disease. The national toxicology program (NTP) has classified crystalline silica as a known human carcinogen. In a lifetime inhalation study, exposure to 250 mg/m³ titanium dioxide resulted in the development of lung tumors in rats.

The mechanisms and were different from common human lung tumors in both type and location. The relevance of these findings to humans is unknown but questionable. The international agency for research on cancer (IARC) has classified titanium dioxide as possibly carcinogenic to humans (group 2b) based on inadequate evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

Reproductive effects : No reproductive effects are anticipated

Mutagenicity : No mutagenic effects are anticipated

Teratogenicity : Some laboratory test results have shown ethylene glycol to be an animal teratogen. However, an expert panel convened by the national toxicology program's center for the evaluation of risks to human reproduction (cehr) conducted a review of the scientific literature and concluded that ethylene glycol does not present a significant concern with respect to developmental and reproductive toxicity in humans.

ECOLOGICAL INFORMATION

No ecological testing has been done by ICI paints on this product as a whole.

The information contained herein is based on data available at the time of preparation of this data sheet which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and the users of this material. Complies with OSHA hazard communication standard 29CFR1910.1200.

DISPOSAL CONSIDERATIONS (ANSI Section 13)

Waste disposal : Dispose in accordance with all applicable regulations. Avoid discharges to natural waters.

REGULATORY INFORMATION

As of the date of this MSDS, all of the components in this product are listed (or are otherwise exempt) from listing on the TSCA Inventory. This product has been classified in accordance with the hazard criteria of the CFR (controlled products regulations) and the MSDS contains all the information required by the CFR.

(ANSI Section 15)

Physical Data

(ANSI Sections 1, 9, and 14)

Product Code	Description	Wt / Gal.	VOC gr. / litr.	% Volatile by Volume	Flash Point	Boiling Range	HMS	DOT, proper shipping name
1412-0100	ultra-hide interior latex eggshell wall & trim enamel, white	10.04	135.90	69.17	none	212-400	*310	paint ** protect from freezing **
1412-0110	ultra-hide interior latex eggshell wall & trim enamel - white tint base	10.06	135.71	69.03	none	212-400	*310	paint ** protect from freezing **
1412-0120	ultra-hide interior latex eggshell pure brilliant white	10.06	135.71	69.03	none	212-400	*310	paint ** protect from freezing **
1412-0300	ultra-hide interior latex eggshell wall & trim enamel - intermediate tint	10.26	70.76	67.34	none	212-501	310	paint ** protect from freezing **
1412-0400	ultra-hide interior latex eggshell wall & trim enamel - deep tint base	9.61	75.10	69.33	none	212-501	310	paint ** protect from freezing **
1412-0500	ultra-hide interior latex eggshell wall & trim enamel - accent tint base	9.73	63.99	66.72	none	212-501	210	paint ** protect from freezing **
1412-1000	ultra-hide interior latex eggshell wall & trim enamel - white-high hiding	10.08	135.53	68.97	none	212-400	*310	paint ** protect from freezing **
1412-1010	ultra-hide latex eggshell interior wall & trim enamel, swiss coffee	10.08	135.31	68.96	none	212-400	*310	paint ** protect from freezing **
1412-1020	ultra-hide interior latex eggshell wall & trim enamel - antique white	10.08	135.53	68.97	none	212-400	*310	paint ** protect from freezing **
1412-1070	ultra-hide latex eggshell interior wall & trim enamel - soft off white	10.18	138.89	68.13	none	212-400	*210	paint ** protect from freezing **
1412-1100	ultra-hide latex eggshell interior wall & trim enamel - white whisper	10.08	135.41	68.96	none	212-400	*310	paint ** protect from freezing **
1412-1130	ultra-hide interior latex eggshell wall & trim enamel - bone white	10.08	135.53	68.97	none	212-400	*310	paint ** protect from freezing **

Ingredients

Product Codes with % by Weight (ANSI Section 2)

Chemical Name	Common Name	CAS. No.	1412-0100	1412-0110	1412-0120	1412-0300	1412-0400	1412-0500	1412-1000	1412-1010	1412-1020	1412-1070	1412-1100	1412-1130
1,2-ethanediol	ethylene glycol	107-21-1	1-5	1-5	1-5	1-5	5-10	1-5	1-5	1-5	1-5	1-5	1-5	1-5
limestone	limestone	1317-65-3												
kaolin	clay	1332-58-7	1-5	1-5	1-5	1-5		1-5	1-5	1-5	1-5	1-5	1-5	1-5
titanium oxide	titanium dioxide	13463-67-7	10-20	10-20	10-20	10-20	1-5	10-20	10-20	10-20	10-20	10-20	10-20	10-20
quartz	quartz	14808-60-7					10-20							
2-propenoic acid, butyl ester, polymer with ethenyl acetate	vinyl acrylic latex	25067-01-0	10-20	10-20	10-20	10-20		10-20	10-20	10-20	10-20	10-20	10-20	10-20
propanoic acid, 2-methyl-, monoester with 2,4-trimethyl-1,3-pentanediol	hexanol	25265-77-4	1-5	1-5	1-5	1-5	1-5	1-5	1-5	1-5	1-5	1-5	1-5	1-5
2-propenoic acid, 2-methyl-, methyl acrylic polymer	acrylic polymer	25852-37-3					20-30							
nepheline syenite	feldspar-type minerals	37244-96-5				10-20								
diatomaceous earth, uncalcined	diatomaceous earth, uncalcined	61790-53-2	1-5	1-5	1-5									1-5
water	water	7732-18-5												50-60

Chemical Hazard Data

(ANSI Sections 2, 8, 11, and 15)

Common Name	CAS. No.	8-hour TWA		STEL		C		S		8-hour TWA		STEL		C		S	
		OSHA-PEL	S	C	OSHA-PEL	S	C	OSHA-PEL	S	C	OSHA-PEL	S	C	OSHA-PEL	S	C	
ethylene glycol	107-21-1	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.
limestone	1317-65-3	10 mg/m3	not est.	not est.	not est.	5 mg/m3	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.
clay	1332-58-7	2 mg/m3	not est.	not est.	not est.	5 mg/m3	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.
titanium dioxide	13463-67-7	10 mg/m3	not est.	not est.	not est.	10 mg/m3	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.
quartz	14808-60-7	0.25 mg/m3	not est.	not est.	not est.	0.1 mg/m3	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.
vinyl acrylic latex	25067-01-0	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.

Footnotes:

C=Ceiling - Concentration that should not be exceeded, even instantaneously.
 S=Skin - Additional exposure, cover and above airborne exposure, may result from skin absorption.
 n/a=not applicable
 not est.=not established
 CC=CERCLA Chemical
 ppm=parts per million
 ng/m3=milligrams per cubic meter
 Sup Conf=Supplier Confidential
 S2=Sara Section 302 EHS
 S3=Sara Section 313 Chemical
 S R Std=Supplier Recommended Standard
 H=Hazardous Air Pollutant, M=Marine Pollutant
 P=pollutant, S=Severe Pollutant
 Carcinogenicity Listed By:
 N=NTP, I=ARC, O=SHA, Y=yes, n=no

Chemical Hazard Data (Continued) (ANSI Sections 2, 8, 11, and 15)

Common Name	CAS. No.	8-Hour TWA	STEL	C	S	8-Hour TWA	STEL	C	S	OSHA-PEL									
										S.R. Std.	S2	S3	CC	H	M	N	I	O	
hexanol	25265-77-4	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n	n
feldspar-type minerals	37244-96-5	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n	n
diatomaceous earth, uncalcined	61790-53-2	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n	n

Footnotes:

C=Ceiling - Concentration that should not be exceeded, even instantaneously.

S=Skin - Additional exposure, over and above airborne exposure, may result from skin absorption.

n/a=not applicable
not est=not established
CC=CERCLA Chemical

ppm=parts per million
mg/m3=milligrams per cubic meter
Sup Conf=Supplier Confidential

S2=Sara Section 302 EHS
S3=Sara Section 313 Chemical
S.R. Std.=Supplier Recommended Standard

H=Hazardous Air Pollutant, M=Marine Pollutant
P=Pollutant, S=Severe Pollutant
Carcinogenicity Listed By:
N=NTP, I=ARC, O=OSHA, y=yes, n=no