



MATERIAL SAFETY DATA SHEET

prepared 07/13/07

HAZARDS IDENTIFICATION (ANSI Section 3)

Primary route(s) of exposure : Inhalation, skin contact, eye contact, ingestion.

Effects of overexposure :

Inhalation : Irritation of respiratory tract, lungs. Prolonged inhalation may lead to mucous membrane irritation, headache, nausea, coughing, difficulty of breathing, severe lung irritation or damage, pneumoconiosis.

Skin contact : Irritation of skin.

Eye contact : Irritation of eyes. Prolonged or repeated contact can cause tearing of eyes, redness of eyes.

Ingestion : Ingestion may cause mouth and throat irritation, nausea, vomiting, diarrhea, gastrointestinal disturbances, abdominal pain, abnormal blood pressure.

Medical conditions aggravated by exposure : Eye, skin, respiratory disorders, lung disorders, asthma-like conditions.

FIRST-AID MEASURES (ANSI Section 4)

Inhalation : Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical help for any breathing difficulty. Remove to fresh air if inhalation causes eye watering, headaches, dizziness, or other discomfort. Get medical attention if discomfort or irritation persists.

Skin contact : Wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin. Repeated applications may be needed. Remove contaminated clothing. Wash contaminated clothing before re-use. If irritation occurs, consult a physician.

Eye contact : Flush immediately with large amounts of water, especially under lids for at least 15 minutes. If irritation or other effects persist, obtain medical treatment.

Ingestion : If swallowed, obtain medical treatment immediately.

FIRE-FIGHTING MEASURES (ANSI Section 5)

Fire extinguishing media : Dry chemical or foam water fog. Carbon dioxide. Closed containers may burst if exposed to extreme heat or fire. May decompose under fire conditions emitting irritant and/or toxic gases. In closed tanks, water or foam may cause frothing or eruption.

Fire fighting procedures : Water may be used to cool and protect exposed containers. Firefighters should use full protective clothing, eye protection, and self-contained breathing apparatus.

Hazardous decomposition or combustion products : Carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen chloride, toxic gases. Vinyl acetate monomer acrylic monomers. Sodium oxide, acetaldehyde, oxides of calcium.

ACCIDENTAL RELEASE MEASURES (ANSI Section 6)

Steps to be taken in case material is released or spilled : Comply with all applicable health and environmental regulations. Eliminate all sources of ignition. Ventilate area. Ventilate area with explosion-proof equipment. Evacuate all unnecessary personnel. Place collected material in proper container. Spilled material is extremely slippery. Complete personal protective equipment must be used during cleanup. Large spills - shut off leak if safe to do so. Dike and contain spill. Pump to storage or salvage vessels. Use absorbent to pick up excess residue. Keep salvageable material and rinse water out of sewers and water courses. Small spills - use absorbent to pick up residue and dispose of properly.

HANDLING AND STORAGE (ANSI Section 7)

Handling and storage : Store below 100f (38c). Keep away from heat, sparks and open flame. Keep from freezing.

Other precautions : Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes, and breathing of vapors. Wash hands thoroughly after handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. Avoid conditions which result in formation of inhalable particles such as spraying or abrading (sanding) painted surfaces. If such conditions cannot be avoided, use appropriate respiratory protection as directed under exposure controls/personal protection. Ground equipment when transferring to prevent accumulation of static charge.

EXPOSURE CONTROLS/PERSONAL PROTECTION (ANSI Section 8)

Respiratory protection : Where respiratory protection is required, use only NIOSH/MSHA approved respirators in accordance with OSHA standard 29 CFR 1910.134.

Ventilation : Provide dilution ventilation or local exhaust to prevent build-up of vapors. Use explosion-proof equipment.

Personal protective equipment : Eye wash, safety shower, safety glasses or goggles. Impervious gloves, impervious clothing.

STABILITY AND REACTIVITY (ANSI Section 10)

Under normal conditions : Stable see section 5 fire fighting measures

Materials to avoid : Oxidizers, acids, reducing agents, bases, halogens, ammonium salts, organic materials, combustible materials. Styrene monomer.

Conditions to avoid : Elevated temperatures, contact with oxidizing agent, freezing, sparks, open flame, ignition sources.

Hazardous polymerization : Will not occur

TOXICOLOGICAL INFORMATION (ANSI Section 11)

Supplemental health information : Contains iron oxide, repeated or prolonged exposure to iron oxide dust may cause siderosis, a benign pneumoconiosis.

Carcinogenicity : Treatment related nasal tumors were observed in rats and mice exposed to vinyl acetate via inhalation at 600 ppm for 2 years. In a lifetime inhalation study, exposure to 250 mg/m³ titanium dioxide resulted in the development of lung tumors in rats. These tumors occurred only at dust levels that overwhelmed the animals' lung clearance mechanisms and were different from common human lung tumors in both type and location. The relevance of these findings to humans is unknown but questionable. The international agency for research on cancer (IARC) has classified titanium dioxide as possibly carcinogenic to humans (group 2b) based on inadequate evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

Reproductive effects : No reproductive effects are anticipated

Mutagenicity : No mutagenic effects are anticipated

Teratogenicity : No teratogenic effects are anticipated

ECOLOGICAL INFORMATION (ANSI Section 12)

No ecological testing has been done by ICI paints on this product as a whole.

The information contained herein is based on data available at the time of preparation of this data sheet which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and the users of this material. Complies with OSHA hazard communication standard 29CFR1910.1200.

ICI Paints North America

15885 Sprague Road - Strongsville, Ohio 44136

EMERGENCY TELEPHONE: NO. (800) 545-2643

GLIDDEN COLOR INT LATEX EGGSHELL

CL12XX

DISPOSAL CONSIDERATIONS

(ANSI Section 13)

Waste disposal: Dispose in accordance with all applicable regulations. Avoid discharge to natural waters.

REGULATORY INFORMATION

(ANSI Section 15)

As of the date of this MSDS, all of the components in this product are listed (or are otherwise exempt from listing) on the TSCA inventory. This product has been classified in accordance with the hazard criteria of the CPR (controlled products regulations) and the MSDS contains all the information required by the CPR.

Physical Data

(ANSI Sections 1, 9, and 14)

| Product Code | Description | Wt. / Gal. | VOC gr. / ltr. | % Volatile by Volume | Flash Point | Boiling Range | HMIS | DOT, proper shipping name |
|--------------|---|------------|----------------|----------------------|-------------|---------------|------|-----------------------------------|
| CL 1230 | glidden color interior latex eggshell ready mix - atmosphere | 10.52 | 38.93 | 66.65 | none | 212-212 | 310 | paint ** protect from freezing ** |
| CL 1231 | glidden color interior latex eggshell ready mix - classic antique white | 10.52 | 38.87 | 66.65 | none | 212-212 | 310 | paint ** protect from freezing ** |
| CL 1232 | glidden color interior latex eggshell ready mix - pure neutral | 10.57 | 38.34 | 66.59 | none | 212-212 | 310 | paint ** protect from freezing ** |
| CL 1233 | glidden color interior latex eggshell ready mix - beautiful beige | 10.58 | 38.49 | 66.58 | none | 212-212 | 310 | paint ** protect from freezing ** |
| CL 1234 | glidden color interior latex eggshell ready mix - sand castle | 10.55 | 38.52 | 66.60 | none | 212-212 | 310 | paint ** protect from freezing ** |
| CL 1235 | glidden color interior latex eggshell ready mix - transitional gold | 10.62 | 37.90 | 66.49 | none | 212-212 | 310 | paint ** protect from freezing ** |
| CL 1236 | glidden color interior latex eggshell ready mix - essence of yellow | 10.54 | 38.73 | 66.62 | none | 212-212 | 310 | paint ** protect from freezing ** |
| CL 1237 | glidden color interior latex eggshell ready mix - quiet sage | 10.55 | 39.59 | 66.58 | none | 212-212 | 310 | paint ** protect from freezing ** |
| CL 1238 | glidden color interior latex eggshell ready mix - botanical garden | 10.51 | 41.12 | 66.62 | none | 212-212 | 310 | paint ** protect from freezing ** |
| CL 1239 | glidden color interior latex eggshell ready mix - tranquility | 10.52 | 39.33 | 66.64 | none | 212-212 | 310 | paint ** protect from freezing ** |
| CL 1240 | glidden color interior latex eggshell ready mix - infinite blue | 10.52 | 38.94 | 66.65 | none | 212-212 | 310 | paint ** protect from freezing ** |
| CL 1241 | glidden color interior latex eggshell ready mix - captivating red | 9.69 | 51.02 | 64.72 | none | 149-501 | 310 | paint ** protect from freezing ** |

Ingredients

Product Codes with % by Weight (ANSI Section 2)

| Chemical Name | Common Name | CAS. No. | CL 1230 | CL 1231 | CL 1232 | CL 1233 | CL 1234 | CL 1235 | CL 1236 | CL 1237 | CL 1238 | CL 1239 | CL 1240 | CL 1241 |
|--|---------------------------------|------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| limestone | limestone | 1317-65-3 | | | | | | | | | | | | 1-5 |
| kaolin | clay | 1332-58-7 | 5-10 | 5-10 | 5-10 | 5-10 | 5-10 | 5-10 | 5-10 | 5-10 | 5-10 | 5-10 | 5-10 | |
| silicic acid, aluminum sodium salt | sodium aluminosilicate | 1344-00-9 | 1-5 | 1-5 | 1-5 | 1-5 | 1-5 | 1-5 | 1-5 | 1-5 | 1-5 | 1-5 | 1-5 | |
| titanium oxide | titanium dioxide | 13463-67-7 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | |
| propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentandiol | texanol | 25265-77-4 | | | | | | | | | | | | 1-5 |
| nepheline syenite | feldspar-type minerals | 37244-96-5 | | | | | | | | | | | | 10-20 |
| c.i. pigment yellow 42 | yellow iron oxide | 51274-00-1 | | | | 1-5 | | | 1-5 | | | | | |
| 2-naphthalenecarboximide, 3-hydroxy-n-(2-methylphenyl)-4-((2,4,5-trichlorophenyl)azo)- | arylide red | 6535-46-2 | | | | | | | | | | | | 1-5 |
| water | water | 7732-18-5 | 50-60 | 50-60 | 50-60 | 50-60 | 50-60 | 50-60 | 50-60 | 50-60 | 50-60 | 50-60 | 50-60 | 50-60 |
| quino(2,3-b)acridine-7,14-dione, 5,12-dihydro-2,9- dimethyl- | quinacridone red | 980-26-7 | | | | | | | | | | | | 1-5 |
| vinyl acetate/acrylic copolymer | vinyl acetate/acrylic copolymer | Sup. Conf. | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | |
| acrylic resin | acrylic resin | Sup. Conf. | | | | | | | | | | | | 20-30 |

Chemical Hazard Data

(ANSI Sections 2, 8, 11, and 15)

| Common Name | CAS. No. | ACGIH-TLV | | | | OSHA-PEL | | | S.R. Std. | S2 | S3 | CC | H | M | N | I | O |
|------------------------|------------|------------|----------|----------|----------|------------|----------|----------|-----------|----------|----|----|---|---|---|---|---|
| | | 8-Hour TWA | STEL | C | S | 8-Hour TWA | STEL | C | | | | | | | | | |
| limestone | 1317-65-3 | 10 mg/m3 | not est. | not est. | not est. | 5 mg/m3 | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n |
| clay | 1332-58-7 | 2 mg/m3 | not est. | not est. | not est. | 5 mg/m3 | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n |
| sodium aluminosilicate | 1344-00-9 | 10 mg/m3 | not est. | not est. | not est. | 5 mg/m3 | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n |
| titanium dioxide | 13463-67-7 | 10 mg/m3 | not est. | not est. | not est. | 10 mg/m3 | not est. | not est. | not est. | not est. | n | n | n | n | y | y | n |
| texanol | 25265-77-4 | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n |
| feldspar-type minerals | 37244-96-5 | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n |

Footnotes:
 C=Ceiling - Concentration that should not be exceeded, even instantaneously.
 S=Skin - Additional exposure, over and above airborne exposure, may result from skin absorption.
 n/a=not applicable
 not est.=not established
 CC=CERCLA Chemical
 ppm=parts per million
 mg/m3=milligrams per cubic meter
 Sup Conf=Supplier Confidential
 S2=Sara Section 302 EHS
 S3=Sara Section 313 Chemical
 S.R.Std.=Supplier Recommended Standard
 H=Hazardous Air Pollutant, M=Marine Pollutant
 P=Pollutant, S=Severe Pollutant
 Carcinogenicity Listed By:
 N=NTP, I=IARC, O=OSHA, y=yes, n=no

Chemical Hazard Data (Continued) (ANSI Sections 2, 8, 11, and 15)

| Common Name | CAS. No. | ACGIH-TLV | | | | OSHA-PEL | | | | S.R. Std. | S2 | S3 | CC | H | M | N | I | O |
|---------------------------------|------------|------------|----------|----------|----------|------------|----------|----------|----------|-----------|----|----|----|---|---|---|---|---|
| | | 8-Hour TWA | STEL | C | S | 8-Hour TWA | STEL | C | S | | | | | | | | | |
| yellow iron oxide | 51274-00-1 | 5 mg/m3 | not est. | not est. | not est. | 10 mg/m3 | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| arylide red | 6535-46-2 | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| quinacridone red | 980-26-7 | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| vinyl acetate/acrylic copolymer | Sup. Conf. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |

Footnotes:

C=Ceiling - Concentration that should not be exceeded, even instantaneously.

S=Skin - Additional exposure, over and above airborne exposure, may result from skin absorption.

n/a=not applicable
not est.=not established
CC=CERCLA Chemical

ppm=parts per million
mg/m3=milligrams per cubic meter
Sup Conf=Supplier Confidential

S2=Sara Section 302 EHS
S3=Sara Section 313 Chemical
S.R.Std.=Supplier Recommended Standard

H=Hazardous Air Pollutant, M=Marine Pollutant
P=Pollutant, S=Severe Pollutant
Carcinogenicity Listed By:
N=NTP, I=IARC, O=OSHA, y=yes, n=no