

MATERIAL SAFETY DATA SHEET

MSDS Name: PL(R) Polyurethane CONCRETE & MASONRY SEALANT gray
MSDS Number: P73263125
Version Number 2
Revision Date: OCT-13-2005
Page Number: 1

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: PL(R) Polyurethane CONCRETE & MASONRY SEALANT gray
HMIS Hazard Rating: Health: 1 Fire: 1 Reactivity: 0 PPE: G

Company Identification: HENKEL CONSUMER ADHESIVES
7405 PRODUCTION DRIVE
MENTOR OH 44060

Contact (24 hour): Customer Affairs (800)321-0253
Information phone/Fax: (440) 255-8900 / (440) 974-8358
CHEMTREC Emergency (24 hour): (703) 527-3887 (International)
(800) 424-9300
in Canada CANUTEC 613-996-6666

Product Class URETHANE SEALANT
Trade Name PL-BRANDS
Product Code See NO. above

SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredient Name	CAS Number	Percent	TSCA
Titanium Dioxide **	13463-67-7	< 5.0	Y
STODDARD SOLVENT	8052-41-3	< 5.0	Y
SILICA, QUARTZ	14808-60-7	TRACE	Y

Ingredient Notes:

Remaining ingredients are not considered OSHA hazardous.
**The main hazard for Titanium Dioxide is dust inhalation. Because of its incorporation into the caulk, exposure by inhalation is unlikely.

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: Non sag caulk.
Appearance/Color: Various
Odor: Mild,oily
Solubility (in water): insol.
pH Value, +/- .3: Not Applicable
Boiling Range: 250.°F - 484.°F (121.11°C - 251.11°C)
Vapor Pressure (mmHg): less than 4.@ 68.°F (20.°C)

MATERIAL SAFETY DATA SHEET

MSDS Name: PL(R) Polyurethane CONCRETE & MASONRY SEALANT gray
MSDS Number: P73263125
Version Number 2
Revision Date: OCT-13-2005
Page Number: 2

Evaporation Rate: 0.1 times Slower than n-Butyl Acetate

Vapor Density: Heavier than air

% Volatile, Weight under 5.%
% Volatile, Volume Not Available
Specific Gravity: 1.1805
VOC (less H2O or exempt) < 44 Gr/L, 3%

NOTE:

*BOIL RANGE, EVAP RATE, VAPOR PRESSURE AND DENSITY FOR SOLVENT ONLY!

SECTION IV - FIRE FIGHTING MEASURES (Flash,UEL,LEL for solvent only)

Flammability Class IIIB
Flash Range: 200.°F (93.33°C)
Pensky-Martens Closed Cup ASTM D 93
Explosive Range (LEL/UEL): Not Available

EXTINGUISHING MEDIA:

Carbon Dioxide---Dry Chemical---Foam
Use water to cool material in vicinity of fire.

SPECIAL FIRE-FIGHTING PROCEDURES:

Use self-contained breathing apparatus with full facepiece
operated in pressure demand or other positive pressure mode.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Water may be unsuitable except as a cooling agent.
Use fog nozzle. Any closed container may rupture when
exposed to extreme heat.

SECTION V - HEALTH HAZARD DATA

ROUTES OF ENTRY:

ENTRY THROUGH...

Inhalation? Yes | Skin? Yes | Ingestion? Yes

TARGET ORGANS...

Overexposure -- Toluene Diisocyanate (<0.1%): Skin, Eyes
A known skin sensitizer

CARCINOGENICITY...

NTP? N/E | IARC Monographs? noted | OSHA? NO
Normal use of this product does not produce dust. Sanding dried
material could generate trace amounts of Silica (quartz) which
is a suspect human carcinogen by IARC.

EFFECTS OF OVEREXPOSURE

Eyes: Can cause irritation, redness, tearing and blurred vision.
Skin: Repeated contact can cause moderate irritation, dermatitis

MATERIAL SAFETY DATA SHEET

MSDS Name: PL(R) Polyurethane CONCRETE & MASONRY SEALANT gray
MSDS Number: P73263125
Version Number 2
Revision Date: OCT-13-2005
Page Number: 3

and possible sensitivity. Allergic reactions are possible.
Inhalation: Headaches, dizziness, nausea, decreased blood pressure,
irritation, coughing, chest discomfort. See Chronic below.
Ingestion: Can cause gastrointestinal irritation, nausea.

FIRST AID MEASURES

Eyes: Flush with large amounts of water for at least 15 minutes
lifting eyelids occasionally; get prompt medical attention
Skin: Wash thoroughly with soap and water; apply a mild skin
cream. Remove contaminated clothing. Rubbing alcohol may help
to remove uncured adhesive.
Inhalation: Remove affected person to fresh air.
Ingestion: Get medical attention if ill effects develop.

CHRONIC HAZARDS

CHRONIC HAZARDS: Preexisting respiratory or skin conditions may be
aggravated by exposure. This product contains an isocyanate. Skin and
respiratory sensitization can result from repeated exposures to
isocyanates. For most individuals these effects are reversible.
Persons previously sensitized to isocyanates may experience an
allergic respiratory reaction: signs/symptoms can include difficulty
breathing, wheezing, tightness of chest, and respiratory failure.
SILICA: Normal use of this product does not produce dust. Sanding dried
material could generate trace amounts of Silica (quartz) which
is a suspect human carcinogen (IARC group 1).
Repeated and prolonged occupational overexposure to Crystalline
Silica may cause silicosis, a progressively disabling lung disease.
NOTICE: Reports have associated repeated and prolonged
occupational overexposure to solvents with permanent brain,
nervous system, liver or kidney damage or may cause cardiac
arrhythmia. INTENTIONAL misuse of this product by
deliberately inhaling its vapors may be harmful or fatal.

SECTION VI - STABILITY AND REACTIVITY

Stability: This product is stable
Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATABILITY:

Keep away from strong oxidizing agents, alkalies, acids,
and water contamination.

CONDITIONS TO AVOID:

Keep away from heat, spark, and open flame.
Product cures in contact with water.

HAZARDOUS DECOMPOSITION PRODUCTS:

Will produce fumes and smoke containing carbon monoxide and
dioxide and nitrogen oxides under fire conditions.

SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:

MATERIAL SAFETY DATA SHEET

MSDS Name: PL(R) Polyurethane CONCRETE & MASONRY SEALANT gray
MSDS Number: P73263125
Version Number 2
Revision Date: OCT-13-2005
Page Number: 4

STEPS TO BE TAKEN IN CASE OF SPILL:

Eliminate all ignition sources.
Ventilate confined areas. (Open windows and doors)
Cover with absorbent, scoop into sealable safety container.
Wear protective clothing.

WASTE DISPOSAL METHOD:

Dispose of following local, state, and federal regulations.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Table with 5 columns: Substance, ACGIH TLV, ACGIH TLV-C, ACGIH STEL, OSHA STEL, OSHA PEL. Rows include Titanium Dioxide, STODDARD SOLVENT, and SILICA, QUARTZ.

Note: The TLV for Silica is for the respirable fraction of dust only.

RESPIRATORY PROTECTION:

If TLV of the product is exceeded, wear NIOSH/MSHA jointly approved respiratory protection in the absence of proper ventilation. Follow applicable OSHA regulations.

VENTILATION:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV. Ventilate during application and curing of this product.

PROTECTIVE CLOTHING:

Rubber gloves should be worn.
Cover arms and legs to minimize exposure.

EYE PROTECTION:

Eye protection should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep away from sunlight, heat and flame
Keep container tightly closed when not in use
Wear protective clothing, Wash skin thoroughly after use.
Avoid contact with eyes, skin or clothing.
KEEP OUT OF REACH OF CHILDREN

MATERIAL SAFETY DATA SHEET

MSDS Name: PL(R) Polyurethane CONCRETE & MASONRY SEALANT gray
MSDS Number: P73263125
Version Number 2
Revision Date: OCT-13-2005
Page Number: 5

SECTION IX - TRANSPORT INFORMATION: (not all sizes available)

GROUND TRANSPORT (DOT) - DOMESTIC
Caulking compound, Non Regulated

AIR TRANSPORT (DOT) - DOMESTIC
Caulking compound, Non Regulated

AIR TRANSPORT (IATA) - INTERNATIONAL
Caulking compound, Non Regulated

MARINE - OCEAN TRANSPORT (IMDG)
Caulking compound, Non Regulated

SECTION X - REGULATORY INFORMATION:

-PROP 65 (CARCINOGEN)

WARNING: This product contains a chemical known to the state of California to cause cancer.

Ingredient Name	CAS Number	Percent
SILICA, QUARTZ	14808-60-7	TRACE

The material fits the EPA Hazard Category definition of Immediate (Acute) and Delayed (Chronic) health hazards under SARA Sections 311, 312.

DISCLAIMER:

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of the environment, and the health & safety of the users of this material.