



Material Safety Data Sheet

Section 1. Chemical Product and Company Identification

Product name **Fast 505 - Industrial Cleaner & Degreaser**

Product code **ZU505**

Date of issue **03/24/08** **Supersedes**

Emergency Telephone Numbers

For MSDS Information:
 Compliance Services 404-352-1680

For Medical Emergency
 INFOTRAC: (877) 541-2016 Toll Free - All Calls Recorded

For Transportation Emergency
 CHEMTREC: (800) 424-9300 - All Calls Recorded
 In the District of Columbia (202) 483-7616

Prepared By
 Compliance Services
 1420 Seaboard Industrial Blvd.
 Atlanta, GA 30318

Section 2. Hazards Identification

Emergency overview

CAUTION

CAUSES EYE AND SKIN IRRITATION.
 HARMFUL IF ABSORBED THROUGH SKIN.
 HARMFUL IF SWALLOWED.

*Hazard Determination System (HDS): Health, Flammability, Reactivity



NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects

Routes of Entry

Eye contact. Absorbed through skin. Inhalation. Ingestion.

Eyes Causes eye irritation. Liquid in eye may cause irritation with possible damage if not rinsed immediately.

Skin May cause skin irritation. Harmful if absorbed through the skin. Skin inflammation is characterized by itching, scaling, reddening or, occasionally, blistering.

Inhalation Inhalation of the spray or mist may produce severe irritation of respiratory tract, characterized by coughing, choking or shortness of breath. Inhalation of high concentrations of vapor may affect the central nervous system.

Ingestion May be harmful if swallowed. Ingestion may cause gastrointestinal irritation and diarrhea.

Chronic effects

Overexposure of this product by inhalation or absorption can produce central nervous system depression resulting in headache, nausea and/or dizziness. Repeated or prolonged exposure to the substance can produce damage to blood, kidneys, liver, upper respiratory tract.

Carcinogenicity Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

Name of Hazardous Ingredients	CAS number	% by Weight
SODIUM METASILICATE; silicic acid (H2-Si-O3) disodium salt; water glass	6834-92-0	1 - 5
ETHYLENE GLYCOL MONOBUTYL ETHER; 2-butoxyethanol; butyl cellosolve	111-76-2	1 - 5

Section 4. First Aid Measures

Eye Contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.

Skin Contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Get medical attention.

Inhalation Move exposed person to fresh air. If irritation persists, get medical attention.

Ingestion Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)



Flash Point	None.
Flammable Limits	Not applicable.
Flammability	Non-combustible.
Fire hazard	No specific hazard.
Fire-Fighting Procedures	Use an extinguishing agent suitable for the surrounding fire. Fire-fighters should wear appropriate protective equipment.

Section 6. Accidental Release Measures

Spill Clean up Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and Storage

Handling Put on appropriate personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Avoid breathing vapors, spray or mists. Use only with adequate ventilation. Do not ingest. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection**Product name**

SODIUM METASILICATE; silicic acid (H₂-Si-O₃) disodium salt; water glass
ETHYLENE GLYCOL MONOBUTYL ETHER; 2-butoxyethanol; butyl cellosolve

Exposure limits

Supplier Suggested (United States).
CEIL: 2 mg/m³ Form:
ACGIH TLV (United States).
TWA: 20 ppm 8 hour(s). Form:
OSHA PEL (United States), Skin
TWA: 50 ppm 8 hour(s). Form:

Personal Protective Equipment (PPE)

Eyes Safety glasses.

Body Wear appropriate protective clothing to prevent skin contact. Chemical-resistant gloves.

Respiratory Use with adequate ventilation. A respirator is not needed under normal and intended conditions of product use.

**Section 9. Physical and Chemical Properties**

Physical State	Liquid.	Color	Colorless to light yellow.
pH	12.75 - 13.25	Odor	Lemon-like. [Slight]
Boiling Point	100°C (212°F)	Vapor Pressure	Not determined.
Specific Gravity	1.032	Vapor Density	Not determined.
Solubility	Soluble in water in any proportion.	Evaporation Rate	Not determined.
		VOC (Consumer)	36 (g/l). 0.30 lbs/gal 3.5%

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.

Incompatibility Reactive or incompatible with the following materials: oxidizing materials and acids.

Hazardous Polymerization Will not occur.

Hazardous Decomposition Products carbon oxides (CO, CO₂)

Section 11. Toxicological Information**Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Sodium Metasilicate	LD50 Oral	Rat	1153 mg/kg	-
	LD50 Oral	Mouse	770 mg/kg	-
Ethylene Glycol Monobutyl Ether	LD50 Dermal	Rabbit	680 mg/kg	-
	LD50 Oral	Rat	1746 mg/kg	-
	LC50 Inhalation Vapor	Rat	450 ppm	4 hours

Section 12. Ecological Information**Environmental Effects** No applicable toxicity data**Aquatic Ecotoxicity**

Not available.

Section 13. Disposal Considerations**Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Code: D002
Classification: - (Hazardous waste.)
Origin: - (RCRA waste.)**Section 14. Transport Information**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification	Not regulated.	- None.	Not a DOT controlled material (United States).		
TDG Classification	Not regulated.	- None.	Not a TDG-controlled material.	-	
IMDG Class	Not available.	Not available.	Not available.	-	

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG* : Packing group

Section 15. Regulatory Information**U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

Product name

Ethylene Glycol Monobutyl Ether (Glycol Ethers)

Clean Water Act (CWA) 307: No products were found.**Clean Water Act (CWA) 311:** No products were found.**Clean Air Act (CAA) 112 regulated toxic substances:** No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

State Regulations**California Prop 65** No products were found.**Canada****WHMIS (Canada)** Class D-2B: Material causing other toxic effects (Toxic).**Section 16. Other Information**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.