



## Material Safety Data Sheet

Revision Date: 11-Jul-2011

Revision Number: 1

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** INSL-GUARD EPOXY POOL COATING - COMPONENT A  
**Product Code** IG4000-SERIES  
**Product List** IG40010, IG40100, IG40190, IG40240, IG40420  
**Product Class** SOLVENT THINNED PAINT  
**Color** All

**Manufacturer** Complementary Coatings Corp.  
 dba Insl-X  
 101 Paragon Drive  
 Montvale, NJ 07645  
 Phone: (800)-225-5554  
 www.insl-x.com

**Emergency Telephone Number(s)**  
 CHEMTREC (US): 800-424-9300  
 CHEMTREC (outside US): (703)-527-3887

### 2. COMPOSITION INFORMATION ON COMPONENTS

#### Hazardous Components

| Chemical Name                              | CAS-No     | Weight % (max) |
|--|------------|----------------|
| Titanium dioxide                           | 13463-67-7 | 40             |
| Proprietary polyamine                      |            | 30             |
| Kaolin                                     | 1332-58-7  | 20             |
| Xylene                                     | 1330-20-7  | 15             |
| Solvent naphtha, petroleum, light aromatic | 64742-95-6 | 10             |
| Propylene glycol monomethyl ether          | 107-98-2   | 10             |
| 1,2,4-Trimethylbenzene                     | 95-63-6    | 5              |
| Ethyl benzene                              | 100-41-4   | 5              |
| Propylene glycol monomethyl ether acetate  | 108-65-6   | 5              |
| Triethylenetetramine                       | 112-24-3   | 5              |
| Silica, amorphous                          | 7631-86-9  | 5              |
| Copper chlorophthalocyanine                | 12239-87-1 | 5              |
| 2-Butoxyethanol                            | 111-76-2   | 0.5            |

### 3. HAZARDS IDENTIFICATION

### 3. HAZARDS IDENTIFICATION

#### Emergency Overview

#### **DANGER**

Vapors may be irritating to eyes, nose, throat, and lungs. May cause skin irritation and/or dermatitis. May cause sensitization by skin contact. Flammable.

IMPORTANT: Designed to be mixed with other components. Mixture will have hazards of all components.

**Appearance** liquid

**Odor** solvent

#### **OSHA Regulatory Status**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

#### Potential Health Effects

#### **Principal Routes of Exposure**

Eye contact, skin contact and inhalation.

#### **Acute Effects**

##### **Eyes**

Contact with eyes may cause irritation.

##### **Skin**

May cause skin irritation and/or dermatitis. May cause skin sensitization.

##### **Inhalation**

High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects.

##### **Ingestion**

Ingestion may cause irritation to mucous membranes. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

#### **Chronic Effects**

Avoid repeated exposure. Repeated contact may cause allergic reactions in very susceptible persons. Prolonged exposure may cause chronic effects.

See Section 11 for additional Toxicological information.

**Aggravated Medical Conditions** None known

**HMIS**            **Health:** 2\*            **Flammability:** 3            **Reactivity:** 0            **PPE:** -

#### **HMIS Legend**

0 - Minimal Hazard

1 - Slight Hazard

2 - Moderate Hazard

3 - Serious Hazard

4 - Severe Hazard

\* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

*Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.*

*Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.*

## 4. FIRST AID MEASURES

|                                   |   |
|-----------------------------------|---|
| <b>General Advice</b>             | If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.   |
| <b>Eye Contact</b>                | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician. |
| <b>Skin Contact</b>               | Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.  |
| <b>Inhalation</b>                 | Move to fresh air. If symptoms persist, call a physician.<br>If not breathing, give artificial respiration. Call a physician immediately  |
| <b>Ingestion</b>                  | Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.                           |
| <b>Notes To Physician</b>         | Treat symptomatically   |
| <b>Protection Of First-Aiders</b> | Use personal protective equipment   |

## 5. FIRE-FIGHTING MEASURES

|  |   |
|--|---|
| <b>Suitable Extinguishing Media</b>                          | Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  |
| <b>Protective Equipment And Precautions For Firefighters</b> | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.  |
| <b>Specific Hazards Arising From The Chemical</b>            | Flammable. Closed containers may rupture if exposed to fire or extreme heat. Keep product and empty container away from heat and sources of ignition. Thermal decomposition can lead to release of irritating gases and vapors. |
| <b>Sensitivity To Mechanical Impact</b>                      | No  |
| <b>Sensitivity To Static Discharge</b>                       | Yes   |
| <b>Flash Point Data</b>                                      |   |
| Flash Point (°F)   | 80  |
| Flash Point (°C)   | 27  |
| Flash Point Method   | PMCC  |
| <b>Flammability Limits In Air</b>                            |   |
| Lower Explosion Limit  | Not available   |
| Upper Explosion Limit  | Not available   |

**NFPA**      **Health:** 2      **Flammability:** 3      **Instability:** 0      **Special:** Not Applicable

**NFPA Legend**

- 0 - Not Hazardous
- 1 - Slightly
- 2 - Moderate
- 3 - High
- 4 - Severe

*The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.*

*Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at [www.nfpa.org](http://www.nfpa.org).*

## 6. ACCIDENTAL RELEASE MEASURES

- Personal Precautions**                      Use personal protective equipment. Remove all sources of ignition.
- Environmental Precautions**            Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.
- Methods For Clean-Up**                    Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.
- Other Information**                        None known

## 7. HANDLING AND STORAGE

- Handling**                                    Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.
- Storage**                                      Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep in properly labeled containers.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Limits**

**Hazardous Components**

| Chemical Name                              | ACGIH                           | OSHA  |
|--|---------------------------------|---|
| Titanium dioxide                           | 10 mg/m <sup>3</sup> - TWA      | 15 mg/m <sup>3</sup> - TWA total                              |
| Proprietary polyamine                      | N/E                             | N/E   |
| Kaolin                                     | 2 mg/m <sup>3</sup> - TWA       | 15 mg/m <sup>3</sup> - TWA total<br>5 mg/m <sup>3</sup> - TWA |
| Xylene                                     | 100 ppm - TWA<br>150 ppm - STEL | 100 ppm - TWA<br>435 mg/m <sup>3</sup> - TWA                  |
| Solvent naphtha, petroleum, light aromatic | N/E                             | N/E   |

|   |                                 |  |
|---|---------------------------------|--|
| Propylene glycol monomethyl ether         | 100 ppm - TWA<br>150 ppm - STEL | N/E  |
| 1,2,4-Trimethylbenzene                    | N/E                             | N/E  |
| Ethyl benzene                             | 100 ppm - TWA<br>125 ppm - STEL | 100 ppm - TWA<br>435 mg/m <sup>3</sup> - TWA                                     |
| Propylene glycol monomethyl ether acetate | N/E                             | N/E  |
| Triethylenetetramine                      | N/E                             | N/E  |
| Silica, amorphous                         | N/E                             | - (80)/(%) SiO <sub>2</sub> mg/m <sup>3</sup> TWA<br>20 mppcf - TWA              |
| Copper chlorophthalocyanine               | N/E                             | N/E  |
| 2-Butoxyethanol                           | 20 ppm - TWA                    | 240 mg/m <sup>3</sup> - TWA<br>50 ppm - TWA<br>prevent or reduce skin absorption |

**Legend**

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits  
 OSHA - Occupational Safety & Health Administration Exposure Limits  
 N/E - Not Established

**Engineering Measures**

Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment**

**Eye/Face Protection**

Safety glasses with side-shields.

**Skin Protection**

Long sleeved clothing. Protective gloves.

**Respiratory Protection**

In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

**Hygiene Measures**

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. When using do not eat, drink or smoke.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

|                                   |               |
|-----------------------------------|---------------|
| <b>Appearance</b>                 | liquid        |
| <b>Odor</b>                       | solvent       |
| <b>Density (lbs/gal)</b>          | 9.1 - 12.5    |
| <b>Specific Gravity</b>           | 1.05 - 1.55   |
| <b>pH</b>                         | Not available |
| <b>Viscosity (centistokes)</b>    | Not available |
| <b>Evaporation Rate</b>           | Not available |
| <b>Vapor Pressure</b>             | Not available |
| <b>Vapor Density</b>              | Not available |
| <b>Wt. % Solids</b>               | 70 - 80       |
| <b>Vol. % Solids</b>              | 60 - 70       |
| <b>Wt. % Volatiles</b>            | 20 - 30       |
| <b>Vol. % Volatiles</b>           | 30 - 40       |
| <b>VOC Regulatory Limit (g/L)</b> | < 340         |
| <b>Boiling Point (°F)</b>         | 248           |
| <b>Boiling Point (°C)</b>         | 120           |
| <b>Freezing Point (°F)</b>        | Not available |
| <b>Freezing Point (°C)</b>        | Not available |

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                       |               |
|-----------------------|---------------|
| Flash Point (°F)      | 80            |
| Flash Point (°C)      | 27            |
| Flash Point Method    | PMCC          |
| Upper Explosion Limit | Not available |
| Lower Explosion Limit | Not available |

## 10. STABILITY AND REACTIVITY

|   |   |
|---|---|
| <b>Chemical Stability</b>                 | Stable under normal conditions. Hazardous polymerisation does not occur.              |
| <b>Conditions To Avoid</b>                | Keep away from open flames, hot surfaces, static electricity and sources of ignition. |
| <b>Incompatible Materials</b>             | Incompatible with strong acids and bases and strong oxidizing agents.                 |
| <b>Hazardous Decomposition Products</b>   | Thermal decomposition can lead to release of irritating gases and vapors.             |
| <b>Possibility Of Hazardous Reactions</b> | None under normal conditions of use.  |

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

#### **Product**

Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

#### **Component**

##### Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat)

LD50 Dermal: > 10000 mg/m<sup>3</sup> (Rabbit)

LC50 Inhalation (Dust): > 6.82 mg/L (Rat, 4 hr.)

##### Kaolin

LD50 Oral: > 5000 mg/kg (Rat)

##### Xylene

LD50 Oral: 4300 mg/kg (Rat)

LD50 Dermal: > 1700 mg/kg (Rabbit)

LC50 Inhalation (Vapor): 5000 ppm (Rat, 4 hr.)

Sensitization: No sensitizing effects known.

Solvent naphtha, petroleum, light aromatic

LD50 Oral: 8400 mg/kg (Rat)

Propylene glycol monomethyl ether

LD50 Oral: 6,600 mg/kg (Rat)

LD50 Dermal: 13,000 mg/kg (Rabbit)

LC50 Inhalation (Vapor): 10,000 ppm (Rat)

1,2,4-Trimethylbenzene

LD50 Oral: 5000 mg/kg (Rat)

LC50 Inhalation (Vapor): 18000 mg/m<sup>3</sup> (Rat, 4 hr.)

Ethyl benzene

LD50 Oral: 3500 mg/kg (Rat)

LD50 Dermal: > 5000 mg/kg (Rabbit)

LC50 Inhalation (Vapor): 55000 mg/m<sup>3</sup> (Rat, 2 hr.)

Sensitization: No sensitizing effects known.

Propylene glycol monomethyl ether acetate

LD50 Oral: 8532 mg/kg (Rat)

LD50 Dermal: > 5000 mg/kg (Rabbit)

LC50 Inhalation (Vapor): > 4345 ppm

Triethylenetetramine

LD50 Oral: 2500 mg/kg (Rat)

LD50 Dermal: 805 mg/kg (Rabbit)

Silica, amorphous

LD50 Oral: > 5000 mg/kg (Rat)

LD50 Dermal: 2,000 mg/kg (Rabbit)

LC50 Inhalation (Dust): > 2 mg/L

2-Butoxyethanol

LD50 Oral: 470 mg/kg (Rat)

LD50 Dermal: 220 mg/kg (Rabbit)

LC50 Inhalation (Vapor): 2.2 mg/L (Rat, 4 hr.)

Sensitization: No sensitizing effects known.

**Chronic Toxicity**

**Carcinogenicity**

The information below indicates whether each agency has listed any ingredient as a carcinogen:

| <b>Chemical Name</b> | <b>ACGIH</b> | <b>IARC</b>                          | <b>NTP</b> | <b>OSHA<br/>Carcinogen<br/>Listed</b> |
|----------------------|--------------|--------------------------------------|------------|---------------------------------------|
| Titanium dioxide     |              | 2B - Possible<br>Human<br>Carcinogen |            | Listed                                |

| Chemical Name   | ACGIH   | IARC                           | NTP | OSHA Carcinogen Listed |
|-----------------|---|--------------------------------|-----|------------------------|
| Ethyl benzene   | A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans | 2B - Possible Human Carcinogen |     |                        |
| 2-Butoxyethanol | A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans |                                |     |                        |

- Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

**Legend**

ACGIH - American Conference of Governmental Industrial Hygienists  
 IARC - International Agency for Research on Cancer  
 NTP - National Toxicity Program  
 OSHA - Occupational Safety & Health Administration

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity Effects**

**Product**

**Acute Toxicity to Fish**

No information available

**Acute Toxicity to Aquatic Invertebrates**

No information available

**Acute Toxicity to Aquatic Plants**

No information available

**Component**

**Acute Toxicity to Fish**

Titanium dioxide

LC50: >1000 mg/L (Fathead Minnow - 96 hr.)

Xylene

LC50: 13.5 mg/L (Rainbow Trout - 96 hr.)

Ethyl benzene



## 12. ECOLOGICAL INFORMATION

LC50: 12.1 mg/L (Fathead Minnow - 96 hr.)

2-Butoxyethanol

LC50: 1490 mg/L (Bluegill sunfish - 96 hr.)

### Acute Toxicity to Aquatic Invertebrates

Ethyl benzene

EC50: 1.8 mg/L (Daphnia magna - 48 hr.)

### Acute Toxicity to Aquatic Plants

Ethyl benzene

EC50: 4.6 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

## 13. DISPOSAL CONSIDERATIONS

### **Waste Disposal Method**

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

## 14. TRANSPORT INFORMATION

### **DOT**

|                             |                 |
|-----------------------------|-----------------|
| <b>Proper Shipping Name</b> | Paint (Mixture) |
| <b>Hazard Class</b>         | 3               |
| <b>UN-No</b>                | UN1263          |
| <b>Packing Group</b>        | III             |

### **ICAO / IATA**

Contact the preparer for further information.

### **IMDG / IMO**

Contact the preparer for further information.

## 15. REGULATORY INFORMATION

### International Inventories

**United States TSCA**

Yes - All components are listed or exempt.

**Canada DSL**

Yes - All components are listed or exempt.

### Federal Regulations

**SARA 311/312 hazardous categorization**

Acute Health Hazard

Yes

|                                   |     |
|-----------------------------------|-----|
| Chronic Health Hazard             | Yes |
| Fire Hazard                       | Yes |
| Sudden Release of Pressure Hazard | No  |
| Reactive Hazard                   | No  |

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

| <u>Chemical Name</u>        | <u>CAS-No</u> | <u>Weight % (max)</u> |
|-----------------------------|---------------|-----------------------|
| Xylene                      | 1330-20-7     | 15                    |
| 1,2,4-Trimethylbenzene      | 95-63-6       | 5                     |
| Ethyl benzene               | 100-41-4      | 5                     |
| Copper chlorophthalocyanine | 12239-87-1    | 5                     |
| 2-Butoxyethanol             | 111-76-2      | 0.5                   |

*This product may contain trace amounts of (other) SARA reportable chemicals. Contact the preparer for further information.*

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following HAPs:

| <u>Chemical Name</u> | <u>CAS-No</u> | <u>Weight % (max)</u> |
|----------------------|---------------|-----------------------|
| Xylene               | 1330-20-7     | 15                    |
| Ethyl benzene        | 100-41-4      | 5                     |
| 2-Butoxyethanol      | 111-76-2      | 0.5                   |

*This product may contain trace amounts of (other) HAPs chemicals. Contact the preparer for further information.*

**State Regulations**

**California Proposition 65**

*This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.*

**State Right-to-Know**

| <u>Chemical Name</u>              | <u>Massachusetts</u> | <u>New Jersey</u> | <u>Pennsylvania</u> | <u>Louisiana</u> | <u>Rhode Island</u> |
|-----------------------------------|----------------------|-------------------|---------------------|------------------|---------------------|
| Titanium dioxide                  | X                    | X                 | X                   |                  | X                   |
| Kaolin                            | X                    | X                 | X                   |                  | X                   |
| Xylene                            | X                    | X                 | X                   |                  | X                   |
| Propylene glycol monomethyl ether | X                    | X                 | X                   |                  | X                   |
| 1,2,4-Trimethylbenzene            | X                    | X                 | X                   |                  |                     |
| Ethyl benzene                     | X                    | X                 | X                   |                  | X                   |
| Triethylenetetramine              | X                    | X                 | X                   |                  |                     |
| Silica, amorphous                 | X                    | X                 | X                   |                  |                     |
| Copper chlorophthalocyanine       |                      | X                 | X                   |                  |                     |
| 2-Butoxyethanol                   | X                    | X                 | X                   |                  | X                   |

**Legend**

X - Listed

## 16. OTHER INFORMATION

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**Prepared By** Product Stewardship Department  
Complementary Coatings Corp.  
dba Insl-X  
101 Paragon Drive  
Montvale, NJ 07645  
Phone: 1-800-225-5554

**Revision Date:** 11-Jul-2011  
**Revision Summary** Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of MSDS**