

Material Safety Data Sheet

RV & Marine AntiFreeze -50F Burst Proof

1. General / Company Information

Revised: 07\09

Chemical Name & Synonyms: Antifreeze - Propylene Glycol based
Chemical Family: Polyalcohol
Proper DOT Shipping Name: Anti-Freeze
Trade Name & Synonyms: MSDS APPLIES TO ALL RV & Marine Antifreeze
-50F REGARDLESS OF TRADE NAME

DOT Hazard Classification: Non-hazardous, Not Regulated

Blended By: *South/Win, Ltd.*
606 Walters Street
Reidsville, NC 27320
(336) 348-4808

CHEMTREC: *(800) 424-9300*

2. Composition

Principal Components	CAS #	Percent	Threshold Limit Value/Units
Propylene Glycol	57-55-6	≤ 20	None established
Glycerol		≤ 10	
Water		≥ 68	
DiPotassium Phosphate	7758-11-4	≤ 2	None established
Dye, FG	Varies		

3. Physical Data

Boiling Point @ 760 mm Hg: 216 °F
Freezing Point: 8 °F
Vapor Pressure (mm Hg.): N/A
Vapor Density (Air=1): N/A
Solubility in Water @ 20°C: 100%
Appearance & Odor: Clear or dyed liquid. Characteristic odor.

Specific Gravity (@60°F/60°F): 1.023 to 1.046
Refractive Index @25°C: 1.362 to 1.400
Percent Volatile By Volume: 25-35%
pH: 8.5 to 11

Material Safety Data Sheet

RV & Marine AntiFreeze -50F Burst Proof

4. Fire & Explosion Data

Flash Point (Test Method):	228°F PMCC (Estimated Minimum)
Flammable Limits:	
LEL:	2.8 (Maximum)
UEL:	12.5 (Maximum)
Autoignition Temperature:	700°F (Estimated Minimum)
Extinguishing Media:	Alcohol type foam, CO ₂ , Dry chemical.
Special Fire Fighting Procedures:	Wear a NIOSH/MSHA approved positive pressure self-contained breathing apparatus when any material is involved in a fire.
Unusual Fire & Explosion Hazards:	None.

5. Health Hazard Data

OSHA Permissible Exposure Limits:	None established.
ACGIH Threshold Limit Value:	1
Carcinogen - NTP Program:	N/A
Carcinogen - IARC Program:	N/A
Symptoms of Exposure:	Practically non-toxic; mild skin irritant. May cause diarrhea by oral ingestion. Medical Conditions
Aggravated By Exposure:	May be a skin sensitizer to some individuals.
Primary Route(s) of Entry:	Skin, eyes, ingestion and inhalation.
Emergency First Aid:	Flush with water. If irritation develops call a physician.
	Eyes: Flush with water, if irritation develops call a physician.
	Ingestion: Drink water to dilute.
	Inhalation: Remove victim to fresh air.

6. Reactivity Data

Stability:	Stable.
Conditions To Avoid:	Extreme heat.
Incompatibility/Materials To Avoid:	Strong oxidizers.
Hazardous Polymerization:	Will not occur.
Hazardous Decomposition Products:	Carbon monoxide, carbon dioxide.

Material Safety Data Sheet

RV & Marine AntiFreeze -50F Burst Proof

7. Environmental Protection Procedures

Spill Response: Wear goggles, coveralls, impervious gloves and boots. Add dry absorbent shovel or sweep up. Place in appropriate container and seal.. Wash contaminated clothing before reuse. Large Spill: Call the Emergency Number on page one of MSDS.

Waste Disposal Method: Dispose of contaminated product, empty containers and materials used in cleanup of spills or leaks in manner approved for material. Consult appropriate Federal, State and Local regulatory agencies to ascertain proper disposal procedures.

8. Special Protection Information

Eye Protection: Wear goggles to prevent splashing into eyes.
Skin Protection: Wear chemically resistant clothing to minimize contact.
Respiratory Protection (Specific Type): NIOSH approved respirator to prevent over exposure.
Ventilation Recommended: N/A
Other Protection: N/A

9. Special Precautions

Hygienic Practices In Handling & Storage: None.
Precautions For Repair & Maintenance Of Contaminated Equipment: None. Other
Precautions: Wash with soap and water before eating or drinking. Launder contaminated clothing before reuse.

*****End Of MSDS*****

Key: N/A Not Applicable
ND Not Determined

The information contained herein is based on the data available to us and is believed to be correct. However, South/Win Ltd. and/or the prepare makes no warranty, expressed or implied, regarding the accuracy of this information or the results to be obtained from the use thereof. South/Win Ltd. assumes no responsibility for injury from the use of the product.