Armstrong

MATERIAL SAFETY DATA SHEET

Armstrong World Industries, Inc. Environment, Health and Safety

2500 Columbia Avenue, P.O. Box 3001

Lancaster, PA 17604

Telephone 1-877-276-7876, Option 3 for Techline

Issued By: Corporate Environment

Health and Safety

HMIS (0 = minimal hazard, 4 = severe hazard)

 $\begin{aligned} & \text{Health} & = 1 \\ & \text{Flammability} & = 0 \end{aligned}$

Reactivity = 0

Division: Building Products

Date: 5/16/08 (Replaces 1/23/01)

N/A = Not Applicable or Not Available N/K = None Known or Not Known

Department of Transportation Information

Shipping name: Not Classified

Hazard Class: N/A ID#: N/A

Emergency Only Contact: CHEM-TEL 800-255-3924

I. Product Information

A. Product Name: Armstrong Supercoat Ceiling Touch Up Paint - MSDS # 15

B. Chemical Name and Synonyms: Latex Based Paint

C. Chemical or Product Family: N/A

II. Ingredient Information

A. Hazardous Components

(Chemical Identity; Common Name)

None

N/A

N/A

N/A

OSHA PEL

ACGIH TLV

ACGIH TLV

This product formulation does not contain asbestos.

III. Physical Data

- A. Appearance and Color: White liquid
- B. Boiling Point (degrees F): N/K
- C. Vapor pressure (mm Hg @ 20 degrees C): N/K
- D. Vapor density (Air = 1): N/K
- E. Solubility in Water: Soluble
- F. Specific Gravity ($H_2O = 1$): 1.85
- G. VOC Content: 2.5%
- H. Evaporation Rate (Butyl Acetate = 1): Slower than ether
- I. pH: 7-8

IV. Fire and Explosion Data

- A. Flash point: None
- $B. \ \ Flammable \ Range: \ \ LEL = N/A; \ \ UEL = N/A$
- C. Extinguishing Media: Carbon dioxide, dry chemical, water spray.
- D. Special Fire Fighting Procedures: Protect fire fighters from toxic products of combustion by wearing self contained breathing apparatus.
- E. Unusual Fire and Explosion Hazards: Closed containers in a fire may rupture due to pressure build-up; use water to cool containers to prevent this.

Continued: Armstrong White Ceiling Touch-up Paint - MSDS # 15 Date: 5/16/08 (Replaces 1/23/01)

V. Health Data

A. Primary Route (s) of Entry: Direct dermal exposure

B. Target Organs: Skin and eyes

Effects of Overexposure:

<u>Skin and Eyes:</u> Excessive or prolonged skin contact may cause irritation and result in dermatitis. Eye contact may be irritating.

<u>Inhalation:</u> Dust exposure is not expected since the raw materials are tied up in the product and do not present a dust hazard.

- C. Carcinogenicity: NTP: No IARC Monographs: No OSHA Regulated: No
- D. Medical Conditions Generally Aggravated by Exposure: None
- E. First Aid Procedures:

Skin and Eyes: Flush any skin or eye contact with plenty of water. Additionally with skin contact, wash with soap and water. Refer to physician if irritation or symptoms persist.

Inhalation: None

VI. Reactivity Data

- A. Stability: Stable
- B. Incompatibility: Oxidizing agents.
- C. Hazardous Decomposition Products: Normal products of combustion.
- D. Hazardous Polymerization: Will not occur.

VII. Spill or Leak Procedures

- A. Steps to be taken if material is released or spilled: Contain spill, preventing it from entering sewer line or waterways. Use absorbent to pick up residue and dispose of properly.
- B. Waste Disposal Method: Dispose of container and any unused contents in accordance with Federal, State, and Local Waste Disposal Regulations. Do not reuse container.

VIII. Special Protection Information

- A. Ventilation: Normal, ambient air circulation or ventilation should be adequate.
- B. Respiratory Protection: Should not be required under typical conditions of use.
- C. Skin and Eye Protection: It is always a good safety practice to avoid contact with eyes and prolonged contact with skin. Use spectacle-type glasses and latex or rubber gloves to avoid contact.

IX. Special Precautions

- A. Precautions to be taken in handling and storage: Store below 100 degrees F. Keep from freezing.
- B. Other Precautions: None

.....

The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.