MATERIAL SAFETY DATA SHEET

FOR COATINGS, RESINS AND RELATED MATERIALS

Date Issued 08/13/2009

SECTION I

<u>MANUFACTURER'S NAME</u>
GARDNER-GIBSON CORPORATION
STREET ADDRESS
4161 E. 7TH AVENUE
EMERGENCY TELEPHONE NUMBER
1-800-424-9300 CHEMTREC
PRODUCT CLASS
ASPAHLT ROOF PRIMER
Spray Grade
TRADE NAME
GARDNER SPRAY PRIMER

CITY, STATE, AND ZIP CODE TAMPA, FL 33605 PRODUCT INFORMATION 1-813-248-2101 MANUFACTURER'S CODE IDENTIFICATION 0148-GA

SECTION II- HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV	TLV
		PPM	Mg/M3
PETROLEUM ASPHALT	<60%	NA	0.5
CAS # - 8052-42-4			Fume
MINERAL SPIRITS	<60%	100	NA
CAS #- 8052-41-3			

ADDITIONAL INFORMATION- NA NOT APPLICABLE

Hazardous Materials Identification System (HMIS)

Health 1 Flammability 2

Reactivity 0 Personal Protection B

SECTION III - PHYSICAL DATA

BOILING RANGE: >300 °F

VAPOR DENSITY 🔀 HEAVIER

EVAPORATION RATE

SLOWER THAN ETHER

PERCENT VOTILE BY VOLUME 50 % WEIGHT PER GALLON BY VOLUME 7.5LBS

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY - NOT REGULATED

FLASH POINT- 105°F Minimum

EXTINGUISHING MEDIA- CO2, FOAM, & DRY CHEMICAL

UNUSUAL FIRE AND EXPLOSION HAZARDS- CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. PRODUCTS OF COMBUSTION MAY BE TOXIC

SPECIAL FIRE FIGHTING PROCEDURES- **WEAR SELF CONTAINED BREATHING APPARATUS. WATER MAY BE USED TO COOL CLOSED CONTAINERS. HIGH PRESSURE STREAM WILL SPREAD FIRE.**

SECTION V – REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID: HEAT, FLAMES, OXIDIZERS

INCOMPATIBILTY (MATERIALS TO AVOID): OXIDIZING AGENTS

Page 1 of 3

0148-GA

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON DIOXIDE, CARBON MONOXIDE

HAZARDOUS POLYMERIZATION: X WILL NOT OCCUR

CONDITIONS TO AVOID: NONE

SECTION VI-HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE- ACUTE: **SKIN**: PROLONGED / REPEATED CONTACT MAY CAUSE IRRITATION. **EYES**: MAY CAUSE SLIGHT IRRITATION. **INHALATION**: EXCESSIVE BREATHING OF HIGH VAPOR CONCENTRATION MAY CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS, NAUSEA, POSSIBLE UNCONSCIOUSNESS AND EVEN ASPHYXIATION, ASPIRATION OF MATERIAL INTO LUMGS CAN CUASE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. **INGESTION**: CAN CAUSE GASTROINTESTINAL IRRITATION NAUSEA, VOMITING AND DIARRHEA. **CARCINOGENICITY**: IARC HAS DETERMINED THAT THERE IS INADEQUATE EVIDENCE THAT UNREFINED ASPHALT IS CARCINOGENIC TO ANIMALS. ADDITIONALLY, IARC HAS CONCLUDED THAT THERE IS INADEQUATE EVIDENCE THAT ASPHALTS ALONE ARE CARCINOGENIC TO HUMANS. IN SOLUTION, SOLVENT EXTRACTS OF ASPHALTS CAN PRODUCE SKIN CANCER IN EXPERIMENTAL ANIMALS FOLLOWING PROLONGED AND REPEATED CONTACT. IARC HAS CONCLUDED THAT THERE IS SUFFICIENT EVIDENCE FOR THE CARCINOGENICITY OF ASPHALT EXTRACTS; THEREFORE CUTBACKS LIKE THIS PRODUCT MAY ALSO BE IMPLICATED AS POTENTIALLY CARCINOGENIC. PLEASE FOLLOW MSDS PRECAUTIONARY MEASURES.

EMERGENCY FIRST AID PROCEDURE- EYES: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING/SHOES. WASH AFFECTED AREAS WITH MILD SOAP AND WATER. IF IRRITATION DEVELOPS AND PERSISTS, SEEK MEDICAL ATTENTION. DO NOT REUSE CLOTHING/SHOES UNTIL THOROUGHLY LAUNDERED. **INHALATION**: REMOVE FROM EXPOSURE. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED, ADMINISTER ARTIFICIAL RESPIRATION. KEEP PERSON WARM AND QUIET. SEEK MEDICAL ATTENTION IMMEDIATELY. **INGESTION**: DO NOT INDUCE VOMITING – TRANSPORT TO HOSPITAL IMMEDIATELY.

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: EVACUATE ALL UNNECESSARY PERSONNEL. DO NOT RE-ENTER AFFECTED AREA WITHOUT PROPER PROTECTIVE EQUIPMENT. VENTILATE AREA. COLLECT IN MOST SAFE MANNER FOR DISPOSAL OR RECLAMATION IN SEALED CONTAINERS.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: USE NIOSH/MSHA APPROVED RESPIRATOR WHEN TLV IS EXCEEDED.

VENTILATION: USE WITH ADEQUATE VENTILATION.

PROTECTIVE GLOVES: NITRILE RUBBER SHOULD BE USED.

EYE PROTECTION: SAFETY GOGGLES SHOULD BE USED.

OTHER PROTECTIVE EQUIPMENT: CLOTHING AND GLOVES IMPERVIOUS TO ASPHALT.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN COOL PLACE

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN OR CLOTHING. DO NOT THIN!!.

DOT CATEGORY: NOT REGULATED

TSCA STATUS: ALL CHEMICAL SUBSTANCES IN THIS PRODUCT ARE INCLUDED ON OR EXEMPTED FROM LISTING ON THE TSCA INVENTORY OF CHEMICAL SUBSTANCES.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ).

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Read and follow label directions and information given on Material Safety Data Sheets and use care when handling or using all petroleum products.