

# **IDEAL Tuff-Rod™ Fishing Poles** Operations Manual

Tuff-Rod™ Regular Flex Fishing Poles are 1/4" diameter non-conductive white fiberglass. Their extra stiffness makes it easier to span longer distances, and gives you greater control when grabbing or pulling wires across suspended ceilings.

Tuff-Rod™ Extra Flex Glow Fishing Poles have all the advantages of Tuff-Rod™ Extra Flex Fishing Poles listed above, plus they are made from pale green luminescent fiberglass. Storage in normal ambient light keeps them charged for everyday use. They emit a soft glow in the dark, providing greater visibility when working in attics or other sites where lighting may be limited.

Available ends include:






### Warnings

Contact with electricity can cause serious injury or death. Shut off power at the circuit breaker or remove fuse before using this product.



#### Cautions

- Fiberglass is flexible but can break or shatter if handled improperly. Always use approved safety glasses and wear gloves when using this product.
- The rod connections and tips are metal and can conduct electricity. Do not use on energized circuits; make sure all power is off.
- Use this product in a safe work position to keep your balance; use extra caution when standing on ladders or lifts.
- Never jerk, yank, or pull rod strongly when it is in a 90 degree flexed position or it may break.
- Do not allow children to play with this product.
- Do not use pliers or other sharp tools to pull or handle Tuff-Rod™ Fishing Poles. Nicks may cause the poles to prematurely break. Use only your hands or a puller designed especially for this purpose, such as the IDEAL S-Class™ Fish Tape Puller, part # 31-170.
- If a rod breaks, either throw it away or cut away the damaged section and replace the connections with the appropriate repair kit.
- Tuff-Rod ™ sections screw together. Support the poles and keep them level while threading multiple rods together for easier connections. Tighten them securely; ends not tightened will allow some play at the joints causing stress on the threaded shaft and may cause it to break.









Proper care of Tuff-Rod™ fishing poles includes cleaning thoroughly and lightly oiling the threaded connections after each use and storing them in a dry, dirt free
area. The plastic tube your kit came in is good for continued storage. Be sure the rod is dry prior to storing in an enclosed container.

#### **Applications**


In walls, over suspended ceilings, in cable trays, or through studs Tuff-Rod™ Fishing Poles help you maneuver wires.




Pull through wall outlet with insulation



Over suspended ceiling



Raised floor wiring



Push wire through stud

## Tuff-Rod™ Fishing Pole Product List

Part #	Product Name	Product Description
31-611	Tuff-Rod Regular Flex Kit - 12ft	12 ft total, three 4 ft rods, 1/4" diameter white fiberglass, with one threaded J hook end
31-612	Tuff-Rod Regular Flex Kit - 24ft	24 ft total, four 6 ft rods, 1/4" diameter white fiberglass, with one threaded bullet nose end
31-631	Tuff-Rod Extra Flex <i>Glow</i> Kit - 12ft	12 ft total, three 4 ft rods, 3/16" diameter luminescent fiberglass, with one threaded J hook end
31-633	Tuff-Rod Extra Flex <i>Glow</i> Kit - 30ft	30 ft total, five 6 ft rods, 3/16" diameter luminescent fiberglass, with one threaded bullet nose end
31-651	Tuff-Rod Tip Accessory Kit 3/16"	For 3/16" Tuff-Rods, includes threaded bullet nose, J Hook, and Wisk
31-652	Tuff-Rod Tip Accessory Kit 1/4"	For 1/4" Tuff-Rods Regular Flex; includes threaded bullet nose, J Hook, and Wisk

Contact your local retailer or distributor for the full line of Tuff-Rod™ Fishing Poles as well as other fine products from IDEAL INDUSTRIES, INC. Visit us on the web at www.idealindustries.com

#### Warranty

Warranty limited solely to repair or replacement; no warranty of merchantability, fitness for a particular purpose or consequential damages.

## IDEAL INDUSTRIES, INC.

Sycamore, IL 60178 USA 800-435-0705 Customer Assistance www.idealind.com ND 3989-2