Disposable

UL Rated 1-A, 10-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Recreational unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough nylon valve assembly.



Includes bracket (896698R)

At a Glance

- Model FA110
- Multipurpose Dry Chemical
- UL listed
- UL rated 1-A,10-B:C
- U.S.C.G, DOT approved
- Supplied with retention strap
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 2.5 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved strap retention
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket



Pt # 21010207 UPC: 0-47871-10207-5 I2F - 10047871102072

For use on the following types of fire:









Product Specification

Froduct Specification					
Net agent weight (Average)	2.5 lb.				
Unit weight (Average)	3.9 lb.				
Diameter	3.25 inches				
Height	13.75 inches				
Discharge time	8-12 seconds				
Discharge range	6-8 feet				
Operating pressure	100 psi				
Cylinder	Seamless aluminum				
Valve, handle, lever	Nylon				
Strap Bracket	U.S.C.G approved				

Packaging Options



Packaging dimensions (inches)

ı				
1		Depth	Width	Height
	Carton	5.375	3.375	15.06
	Master Pack	16.5	16.5	11.5

