

SAFETY DATA SHEET

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

Product Identifier : **Henry® 345 Premixed Patch n' Level**
Product ID No. : 70012012
Trade Name/Synonyms : Henry 345
Material Use : Floor Patch and Smoothing Compound.

Manufacturer's name and address:

HENRY

The W.W. Henry Company
400 Ardex Park Drive
Aliquippa, PA 15001 USA

Information Telephone No. : (724) 203-8000
Website Address : <http://www.wwhenry.com>
24 Hr Emergency Telephone # : **CHEM-TEL: 1-800255-3924 OR 1-813-248-0585 (call collect)**

SECTION 2 – HAZARDS IDENTIFICATION

GHS Classification per 29CFR 1910 (OSHA Hazard Communication Standard)

Skin corrosion/irritation, Category 2 (Irritant)
Serious eye damage/eye irritation, Category 2B (Irritant).
Carcinogenicity, Category 2

WHMIS Classification

Class D2A (Materials Causing Other Toxic Effects, Very Toxic Material).

GHS Pictograms



Signal Word

Warning.

Hazard Statements

Suspected of causing cancer.
Causes skin irritation.
Causes eye irritation.

Precautionary Statements

Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection. Wash hands and exposed skin thoroughly after handling. Do not subject to grinding. Store locked up. Dispose of contents / container in accordance with federal, state, and local laws. Do not allow product to enter drains.

Hazards Not Otherwise Classified

None

% With Unknown Acute Toxicity : Up to 5% by weight of this product is comprised of ingredients with unknown acute toxicity.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS #	% (by weight)
Crystalline silica	14808-60-7	60. – 100.
2-Butoxyethanon	111-76-2	0.10 – 1.00

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets.

SECTION 4 – FIRST AID MEASURES

- General** : Call a Poison Center or doctor if you feel unwell.
- Inhalation** : If inhaled, move victim to fresh air and keep at rest in a position comfortable for breathing. If breathing difficulties persist, seek immediate medical attention/advice.
- Skin contact** : Remove/Take off immediately all contaminated clothing. Flush affected skin with gently flowing lukewarm water for at least 20 minutes. If rash or irritation persists, seek medical attention/advice.
- Eye contact** : Immediately flush eyes thoroughly with running water for at least 20 to 30 minutes. Seek immediate medical attention/advice.
- Ingestion** : Never give anything by mouth to an unconscious person. Rinse mouth with water. Do NOT induce vomiting. Seek immediate medical attention/advice.
- Notes for Physician** : Treat symptomatically.

Signs and symptoms of short-term (acute) exposure

- Inhalation* : May cause minor, temporary irritation to respiratory tract. Symptoms may include coughing and shortness of breath.
- Skin* : May cause skin irritation. Symptoms may include redness and itching.
- Eyes* : Causes irritation to eyes. Symptoms may include redness, itching, blurred vision or pain.
- Ingestion* : Symptoms such as gastric pain, nausea, vomiting, and diarrhea may occur.

Effects of long-term (chronic) exposure

- : Prolonged inhalation may cause adverse lung effects with symptoms including coughing and shortness of breath.

Indication of need for immediate medical attention or special treatment

- : Difficulty breathing persists after removing the person to fresh air.
Any exposure to the eye which causes irritation.
Ingestion.

SECTION 5 – FIRE FIGHTING MEASURES

- Suitable extinguishing media** : Carbon dioxide, dry chemical powder, appropriate foam or water fog.
- Unsuitable extinguishing media** : water jet
- Hazardous combustion products** : Carbon monoxide, carbon dioxide, and other toxic vapors and gases which are common to thermal degradation of organic compounds.
- Special fire-fighting procedures/equipment**
- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. After fires have been extinguished, carefully clean all equipment and surfaces exposed to fumes.
- Environmental precautions** : Do not allow material to enter drains or contaminate ground water system.
- Fire hazards/conditions of flammability**
- : Not flammable under normal conditions of use. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.1200, WHMIS)

: Not flammable

SECTION 6 – ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Restrict access to area until completion of clean-up. All persons dealing with clean-up should wear the appropriate chemically protective equipment.
- Protective equipment** : Refer to Section 8 on this Safety Data Sheet, EXPOSURE CONTROLS / PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.
- Emergency Procedures** : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).
US CERCLA Reportable quantity (RQ): None reported.

Methods and materials for containment and cleaning up

: Ventilate area of release. Stop spill or leak at source if safely possible. Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later disposal (see Section 13). Residual of product, while still wet, can be cleaned up with warm soapy water. Notify the appropriate authorities as required.

Prohibited materials

: Avoid strong oxidizing agents

Environmental precautions

: Do not allow product to enter drains or waterways. Do not allow material to contaminate ground water system.

Reference to other sections

: See Section 14 for disposal information.

SECTION 7 – HANDLING AND STORAGE

- Safe handling procedures** : Observe good hygiene standards. Use only with adequate ventilation. Do not eat, drink or smoke in the work area. Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Avoid repeated or prolonged skin contact. Avoid breathing vapors or mists of this product. Sanding and grinding dusts may be harmful if inhaled. When removing this product from existing flooring (i.e. during a renovation), wear safety goggles and respiratory protection from dust due to blasting, chipping, or mechanically pulverizing. Wear protective clothing to prevent skin contact. Promptly remove any clothing that becomes contaminated. Clean contaminated clothing before reuse. Keep container tightly closed.
- Storage requirements** : Store in a cool, dry, well-ventilated area. Store away from heat and open flame. Avoid storing in direct sunlight. Store in original container. Keep tightly closed when not in use. Do not reuse empty container without commercial cleaning or reconditioning.
- Incompatible materials** : See Section 10.
- Special packaging materials** : Always keep in containers made of the same materials as the supply container.

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

- Permissible Exposure Limits** : No exposure limits have been established for the product itself. Below are exposure limits for the components in the product.

Ingredients	CAS #	ACGIH TLV		OSHA PEL	
		TWA	STEL	PEL	STEL
Crystalline silica	14808-60-7	0.025 mg/m ³ (respirable fraction)	N/Av	0.1 mg/m ³ (respirable) (Final rule limit)	N/Av
2-Butoxyethanol	111-76-2	20 ppm	N/Av	50 ppm (skin)	N/Av

- Engineering Controls** : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Ventilation should effectively remove and prevent buildup of any vapor or mist generated from the handling of this product.

Personal Protection Equipment

- Eye / face protection** : Safety glasses must be worn when using this product. During operations where airborne dust is generated, wear chemical goggles.
- Skin protection** : Wear chemical resistant protective clothing and impervious gloves. Glove materials such as nitrile rubber or Viton (fluorocarbon rubber) are recommended. Consult with the glove manufacturer regarding breakthrough time for the components listed in Section 3.
- Body protection** : Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact.
- Respiratory protection** : Under normal conditions of use with adequate ventilation, respiratory protection should not be necessary. If work process generates excessive quantities of vapor or dust, or exposures in excess of any PEL, wear an appropriate organic vapor respirator or particulate respirator (dust mask) rated N-95 or higher, appropriate for the conditions.
- Site safety equipment** : An eyewash station and safety shower should be made available in the immediate working area.
- General hygiene considerations** : Avoid contact with eyes, skin and clothing. Avoid breathing vapors/dust. Do not eat, drink or smoke when using this product. Clean all equipment and clothing at end of each work shift.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Paste	Appearance	: off-white paste
Odor	: Mild	Odor threshold	: N/Av
pH	: 7.2 – 7.4	Specific gravity	: 1.53 – 1.64
Boiling point	: > 212°F (> 100°C)	Coefficient of water/oil distribution	: N/Av
Melting/Freezing point	: N/Av	Solubility in water	: Slightly soluble
Vapor pressure (mm Hg @ 20°C / 68°F)	: N/Av	Evaporation rate (n-Butyl acetate = 1)	: N/Av
Vapor density (Air = 1)	: N/Av	Volatiles (% by weight)	: 14 – 16
Volatile Organic Compounds (VOCs)	: 12.5 g/L SCAQMD Rule 1168		
Particle size	: N/Av	Flammability classification	: Not flammable
Flash point	: >212°F (100°C)	Lower flammable limit (% by vol)	: Not available
Flash point method	: Setaflash closed	Upper flammable limit (% by vol)	: Not available
Auto-ignition temperature	: N/Av	Decomposition temperature	: Not available
Viscosity	: Not available	Oxidizing properties	: Not available
Explosion data: Sensitivity to mechanical impact / static discharge	: Not expected to be sensitive to mechanical impact or static discharge.		

SECTION 10 – REACTIVITY AND STABILITY INFORMATION

- Reactivity** : Does not react.
- Stability** : Stable under the recommended storage and handling conditions prescribed.
- Hazardous reactions** : Hazardous polymerization does not occur.
- Conditions to avoid** : High temperatures.
- Materials to avoid and incompatibility** : Oxidizing agents.
- Hazardous decomposition products** : None known, refer to hazardous combustion products in Section 5.

SECTION 11 – TOXICOLOGICAL INFORMATION

- Routes of exposure** : *Inhalation*: YES *Skin Absorption*: NO *Skin and Eyes*: Yes *Ingestion*: YES
- Symptoms of exposure** : See Section 4.

Toxicological data : There are no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

Ingredients	LC50 (4 hr) Inhalation, rat	LD50	
		Oral, rat	Dermal, rabbit
2-Butoxyethanol	450 ppm	250 mg/kg	220 mg/kg
Crystalline silica, quartz	N/Av	N/Av	N/Av

Skin corrosion or irritation : May cause irritation to skin.

Serious eye damage / eye irritation : May cause irritation to eyes.

Respiratory or skin sensitization : None known.

Germ cell mutagenicity : None known.

Carcinogenic status : This product contains Crystalline silica - Quartz. Crystalline silica - Quartz is classified as carcinogenic by inhalation by IARC (Group 1), ACGIH (Group A2), NTP (Group 1) and OSHA (OSHA Select carcinogen). During normal usage of the product as recommended, airborne dusts will not be present. Do not sand/grind/ chip off excess material, following initial application, unless wearing proper respiratory and eye protection. (See Section 8.)

This product contains 2-Butoxyethanol. 2-Butoxyethanol is not listed as a carcinogen by NTP or OSHA, classified as Category 3 (not classifiable as to carcinogenicity) by IARC, classified by EPA as "Not likely to be carcinogenic to humans at environmental concentrations at or below the RfC [RfC = 1.6 mg/m³]", and classified by ACGIH as A3 – Animal Carcinogen (with unknown relevance to humans).

Reproductive toxicity : None known.

Specific Target Organ Toxicity, Single Exposure

: Not considered to be a hazard during normal usage of the product as recommended.

Specific Target Organ Toxicity, Repeated Exposure

: None known.

Aspiration hazard : None known.

Additional information : N/Av

SECTION 12 – ECOLOGICAL INFORMATION

Environmental effects : The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

Ecotoxicity : No data available.

Biodegradability : No data available.

Bioaccumulative potential : No data available.

Mobility in soil : No data available.

PBT and vPvB assessment : No data available.

Other adverse effects : No data available.

SECTION 13 – DISPOSAL CONSIDERATION

Handling for disposal : Handle waste according to recommendations in Section 7.

Methods of disposal : You must test your waste using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes. Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.

Packaging : Handle contaminated packaging in the same manner as the product.

RCRA : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14 – TRANSPORTATION INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	None	This product is not regulated according to Canadian TDG regulations.	None	None	None
TDG Additional Information	None				
49 CFR/DOT	None	This product is not regulated according to US DOT regulations.	None	None	None
49 CFR/DOT Additional Information	None				

SECTION 15 – REGULATORY INFORMATION

Canadian Information:

Canadian WHMIS Classification: This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Controlled Products Regulations (CPR). Refer to Section 2 for a WHMIS Classification for this product.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on either the Domestic Substances List (DSL) or the Non- Domestic Substances List (NDSL). It contains the following components above the *de minimus* level on the Canadian HPA Ingredient Disclosure List: Crystalline Silica (Quartz), 2-Butoxyethanol.

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.

U.S. State Right To Know Laws

California Proposition 65: Warning! This product contains a chemical known to the State of California to cause cancer.

Other State Right to Know Laws:

Ingredient on State RTK Law?	CAS #	CA	MA	MN	NJ	NY	PA	RI
Crystalline silica, quartz	14808-60-7	No	YES	YES	YES	No	YES	YES
2-Butoxyethanol	111-76-2	YES	YES	YES	YES	No	YES	YES

SECTION 16 – OTHER INFORMATION

HMIS Rating : * - Chronic Hazard 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe
Health: 1 Flammability 1 Reactivity 0 PPE: Gloves, safety glasses

Legend : ACGIH: American Conference of Governmental Industrial Hygienists
CAS: Chemical Abstract Services
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980

CFR: Code of Federal Regulations
DOT: Department of Transportation
DSL: Domestic Substances List
EPA: Environmental Protection Agency
GHS: Globally Harmonized System
IARC: International Agency for Research on Cancer
Inh: Inhalation
N/Av: Not Available
N/Ap: Not Applicable
NIOSH: National Institute of Occupational Safety and Health
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PEL: Permissible exposure limit
RCRA: Resource Conservation and Recovery Act
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

Disclaimer of Liability

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

No warranty of any kind is given or implied. The W.W. Henry Company will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein. This Safety Data Sheet is valid for three (3) years.

Prepared By:
The W.W. Henry Company
400 Ardex Park Drive
Aliquippa, PA, U.S.A.
15001

(724) 203-8000
Visit our Website: <http://www.wwhenry.com>

Revision date: : 13-Nov-2014

End of Document