

# I-95™

*It's Three Machines in One*

Here's a sectional cable machine that drives 7/8" and 5/8" sections – or even 5/16" cables for small drain work. You switch from 7/8" to 5/8" and back by repositioning the chuck cone. No adapter required. Attach a small drum to the back of the machine to drive smaller cables.

The I-95 gives you power and convenience. The motor is a 1/3 hp capacitor type, so it delivers plenty of torque to the cables. Yet, as soon as you lift the drive handle, the cable stops rotating, so there's no additional torque build up.

You also use the drive handle to carry the machine. And when it's in position on the job, its four point base gives it rock-solid stability. A cutter holder is attached to the back of the I-95, so your cutting heads are always with the machine. A Ground Fault Circuit Interrupter is standard equipment.



Clear 1-1/2" – 2" lines with 5/16" x 25' cable.



### **15R10-P Proflex® Cable.**

Optional 7/8" sectional cable (15R10-P) with Proflex inner core gives cable more strength for cutting through difficult stoppages.



Clear 2" – 3" lines up to 125 feet long with 5/8" x 7-1/2' sections or 4" lines up to 150 feet long with 7/8" x 15' sections.



### I-95 Accessories

Includes cable carriers, drums for small drain work, a rear guide hose, and a tool box – standard on 7/8" cable units.

### Transportable

Light weight I-95 is easy to carry up a ladder.

### Specifications:

#### Weight:

39 lbs. (18 kg).

#### Dimensions:

16" deep; 14" wide; 17" high (41 cm x 35 cm x 43 cm).

#### Motor:

1/3 hp capacitor type with forward-off-reverse switch, ten-foot power cord, and Ground Fault Circuit Interrupter. Rotates cables at 400 rpm.

#### Adjustable Chuck:

Has two sets of notches; one for 5/8" cables and one for 7/8" cables. Switch from one to the other in seconds. Pull down handle to engage, lift to stop. Brake stops spinning drums instantly. Chuck handle also acts as lifting handle.

#### Chuck Jaws:

Drive both 5/8" and 7/8" cables; also grip drum for smaller diameter cables.



#### Drum:

Drum holds 25 ft. x 5/16" cable for 1-1/2" to 2" lines, or 35 ft. x 3/8" cable for 2" to 3" lines.

#### Cables:

"T" slot couplings slide together to lock and uncouple with a pin key. 7.5R8 - 7-1/2 ft. x 5/8" (2.3 m x 15.6 mm) for 1-1/4" through 3" (31 mm – 75 mm) lines up to 125 ft long;

15R10 or 15R10P with Proflex inner core – 15 ft. x 7/8" (4.6 m x 22 mm) for 2" – 4" (50 mm – 100 mm) lines up to 150 ft. long.

#### Leather Gloves:

With double-reinforced palm, for hand protection when guiding cable.

#### Cutter Sets:

Cutter Set for 7/8" cables includes Spear Head, 2" U-Cutter, 3" U-Cutter, Hook Auger, and Retrieving Tool.

Cutter Set for 5/8" cables includes Arrow Head, Boring Gimlet, 1-1/2" U-Cutter, and Retrieving Tool.