

Product Name: RED RELIEF - PART A

Revision Date: 10/10/2013

SAFETY DATA SHEET

SECTION 1

MATERIAL AND MANUFACTURER IDENTIFICATION

PRODUCT

Product Identifier: RED RELIEF - PART A
Intended Product Use: Food dye stain remover
Manufacturer Identification Code: 3080 A

MANUFACTURER

Namco Mfg., Inc. 1651 Blalock Rd. Houston, TX 77080 1-800-634-5816 * 713-932-8293

24 hours Emergency Assistance Calls (USA): CHEMTREC (800) 424-9300 Please reference name and manufacturers identification number

SECTION 2

HAZARD(S) INDENTIFICATION

OSHA Hazard

Irritant

GHS CLASSIFICATION

Acute Toxicity, Oral (Category 5)
Acute Toxicity, Dermal (Category 5)
Serious Eye Damage/Eye Irritation (Category 2B)
Acute Toxicity, Inhalation (Category 5)

Routes of Exposure: Eye contact, skin contact, inhalation, and ingestion.

Inhalation: Inhalation of mist or vapor may cause severe irritation of the respiratory tract. Overexposure may result in coughing, choking or shortness of breath.

Eye Contact: Vapors/mist may irritate eyes. Irritation is characterized by redness, itching, or watering of eyes. Direct or prolonged contact with eyes will be painful and irritating; seek immediate medical attention for prolonged irritation.

Skin Contact: Repeated exposure may cause skin irritation, inflammation, drying, and/or chapping.

Ingestion: If swallowed may cause GI irritation with abdominal pain, nausea, vomiting, diarrhea, violent colic, and possible gastric hemorrhaging. Ingestion of sulfite compounds may cause severe allergic reactions in sensitive individuals and some asthmatics. Seek immediate medical attention.

Carcinogenic Potential: Not established

Acute Effects: This product is considered to be a potential irritant. This product should not be used for any other purpose than the intended use in section 1.

Chronic Effects: Not established.



Health hazard	2
Flammability hazard	0
Reactivity hazard	0
Other hazard	

Signal word: WARNING

Hazard statement(s): H303: May be harmful if swallowed;

H313: May be harmful in contact with skin;

H320: Causes eye irritation; H333: May be harmful if inhaled.

SDS Product: Red Relief - Part A

Page1 of 6



SECTION 3 COMPOSITON/INFORMATION ON INGREDIENTS

COMPONENTCAS #CONCENTRATIONS1. Ammonium Hydroxide1336-21-610-30%2. Sodium Metabisulfite7681-57-410-30%

This SDS contains confidential and propriety information of CTI and is protected by copyright, trade secret and other State and Federal laws. Its receipt or possession does not convey any rights to reproduce its contents, or to manufacture, use or anything it may describe. Reproduction, disclosure, or use without specific written authorization of CTI is strictly forbidden.

SECTION 4 FIRST-AID MEASURES

Inhalation: Remove from further exposure to fresh air. If respiratory irritation, dizziness, or nausea occurs seek immediate medical attention. If breathing stops, have trained person administer oxygen with a resuscitation mouth cover. Seek immediate medical attention.

Eye Contact: Flush eyes with a directed stream of water for 15 minutes, forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissue. Washing eyes immediately after exposure is essential to achieve maximum effectiveness and minimize potential irritation. If irritation persists, seek immediate medical attention.

Skin Contact: Wash contact areas with soap and water. Launder exposed clothing before reuse.

Ingestion: If swallowed, do not induce vomiting. Seek immediate medical attention.

SECTION 5 FIRE-FIGHTING MEASURES

FLAMMABILITY PROPERTIES

Flashpoint: Non-combustible/Non-flammable Flammable Limits: N/A
Auto ignition Temperature: N/A

FIREFIGHTING PROCEDURES

General Hazard: During a fire smoke may contain the original material in addition to toxic and or irritating compounds. Avoid heat sparks or open flame.

Firefighting Instructions: Evacuate all unnecessary personnel. Use dry chemical, CO₂, foam, or water spray. Use water or foam to cool surrounding containers. Direct water stream may spread the fire.

Firefighting Equipment: Firefighters should wear NICSH/MSHA approved self-contained, positive pressure breathing apparatus and full protective clothing.

Hazardous Combustion Products: Hazardous combustion products may include but limited to: CO, CO₂, Na₂O NH₄ and nitric oxides.

Unusual Fire and Explosion Hazards: No known unusual fire/explosion hazards.

SECTION 6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Persons performing the clean up should wear personal protective equipment sufficient to keep material away from skin. Avoid direct contact with material. See section 4 for First-Aid Advice. See section 5 for Firefighting Advice.

PROTECTIVE MEASURES

To minimize exposure to all chemicals, including this product, use good industrial hygiene and common sense. Use only in well ventilated area. If necessary, use exhaust ventilation to insure adequate ventilation. Insure that water is readily available and that you are prepared to properly wash out your eyes should the need arise. (See section 4 for more advice). Wear NIOSH/MSHA approved organic respirator when ventilation is not adequate or when the sufficiency of ventilation to maintain concentrations below exposure limits is in question. Wear chemical safety goggles to protect against splashes or contact with eyes. See OSHA 29 CFR 1910.33

SDS Product: Red Relief - Part A

Page 2 of 6



CLEAN-UP PROCEDURES

Small Spills: Wipe up or mop to dispose of spill in DOT approved waste container.

Large Spills: Contain by diking with soil or other non-combustible absorbent material, and dispose into DOT approved waste container. If possible complete clean up on a dry basis. Comply with all applicable governmental regulations on spill reporting, handling and disposal of waste. Contain all spills or leaks to prevent discharge into the environment. Responsibility of all spills or releases reported to the appropriate local, state and federal agencies falls upon the user.

SECTION 7 HANDLING AND STORAGE

HANDLING

This product is professional strength product to be used by professionals only. Avoid breathing vapors/mist of this product. Always keep container tightly closed and properly labels. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Impervious boots/shoes covering should be used if material is anticipated to contact feet. As with all chemicals, practice good industrial hygiene when handling this product. Always work in a well-ventilated area and avoid inhalation of product vapor or mist. Do not ingest.

The manufacturer and seller warrant that this product conforms to its standard specifications when used according to directions. As the conditions of method of its use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for use of this product. Information contained herein is believed to be true but all statements and suggestions are made without any warranty, expressed or implied, regarding accuracy of the information. The hazards connected with the use of this material and the results to be obtained from the use thereof.

STORAGE

Avoid excessive heat. Avoid storage with oxidizing or reducing agents and/or acids. Avoid storage with combustible organic materials. Employees should be trained to handle this product safely. Loosen closures cautiously. Store the product in a cool dry area away from ignition sources.

Storage temperature: Store in cool dry place

Storage pressure: Atmospheric

SECTION 8 | EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS

Exposure limits have not been established for this mixture. Avoid, as far as reasonably practicable, inhalation of vapor, mists or fumes generated. Limits for components are listed below:

	OSHA PEL	ACGIH TLV	NIOSH
COMPONENT #	TWA STEL	TWA STEL	TWA STEL
Ammonium Hydroxide	35ppm	25ppm	35 ppm
2. Sodium Metabisulfite	5 mg/m3	5 mg/m3	5 mg/m3

ENGINEERING CONTROLS

The level of protection and types of control will vary depending upon potential exposure conditions. If user operations generate dust, fume or mist, use adequate ventilation to keep exposure below exposure limit.

PERSONAL PROTECTION

Ventilation and engineering controls: Use only in well ventilated area. If necessary, use exhaust ventilation to insure adequate ventilation. Insure that water is readily available and that you are prepared to properly wash out your eyes should the need arise. (Refer to section 4).

Respiratory: Wear NIOSH/MSHA approved respirator when ventilation is not adequate. A NIOSH /MSHA –approved air purifying respirator with an organic vapor cartridge or canister may be advisable under certain circumstances where

SDS Product: Red Relief - Part A

Page 3 of 6



airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure, air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.

Eye Protection: Wear safety goggles to protect against eye contact. See OSHA 29 CFR 1910.33

Skin: Wear chemical impervious gloves. Gloves must be inspected before use. Dispose of gloves after use in accordance with applicable laws and good laboratory practices. Wear protective clothing to minimize skin contact. Wash skin after use. Wash contaminated clothing and dry before reuse.

Other: One should always use chemicals with an awareness of the potential hazard of the effect on the human system. To minimize employee exposure to all chemicals, including this product, use good industrial hygiene practices.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical State and Appearance: Liquid

Odor: Sulfur odor Vapor density: N/A Freezing point: N/A Solubility in water: soluble

Flammability: N/A Evaporation rate: N/A

Upper/lower flammability or explosive limits: N/A

Odor threshold: N/A Flash point: N/A Evaporation rate: N/A

Upper/lower flammability or explosive limits: not flammable

Vapor pressure: N/A

Auto-ignition temperature: N/A

Color: Clear pH: 4.5

Boiling point: 212F Melting point: N/A Density: N/A Particle size: N/A Viscosity: N/A Vapor pressure: N/A Vapor density: N/A

Relative density: N/A

Flammability (solid, gas): N/A Decomposition temperature: N/A

Vapor density: N/A

Partition coefficient: n-octanol/water: N/A

SECTION 10 | STABILITY AND REACTIVITY

Chemical Stability: Stable under ambient temperature and atmospheric pressure.

Conditions to avoid: Keep away from heat or excessive pressure. Keep away from heat or excessive pressure. Do not contaminate.

Incompatibility with other materials: Heavy metals, combustible organic materials, reducing agents.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Sulfur oxides.

Hazardous polymerization: Major components of this mixture show no hazardous polymerization.

Conditions to Avoid: Oxygen, which supports combustion.

SECTION 11 TOXICOLOGICAL INFORMATION

Toxicological information has not been established on this mixture. Toxicological information on components within this mixture is given by:

COMPONENT # TOXICITY

Ammonium Hydroxide
 Sodium Metabisulfite
 LD₅₀ Oral - rat -350 mg/kg
 LD₅₀ Oral - rat - 1,540 mg/kg
 LD₅₀ Dermal - rabbit - 2,000 mg/kg

SECTION 12 | ECOLOGICAL INFORMATION

SDS Product: Red Relief – Part A

Page 4 of 6



Ecological information has not been established for this product. Ecological information on components within this

mixture is given by:

COMPONENT # TOXICITY

1. Ammonium Hydroxide Freshwater fish-(rainbow trout) − LC₅₀ - 0.1ppm 24h

Freshwater fish-(fathead minnow) – 8.2mg/l 96h

2. Sodium Metabisulfite Freshwater fish-(rainbow trout) – 150-220 mg/l 96h

Green algae-(desmodomonas subspicatus) - LC₅₀ - 48 mg/l 96h

SECTION 13 DISPOSAL CONSIDERATIONS

Dispose of all waste, empty bottles and contaminated equipment in accordance with all applicable federal, state and local health and environmental regulations.

Do not dump into storm drains or any body of water. All disposal methods must be in compliance with all federal, State/ Province and local laws and regulations. Regulations may vary in different locations.

Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. The vendor has no control over the management practices or the processes by which the party who handles or uses this material. The information presented here pertains only to the product as shipped in its intended condition and recommended usage.

SECTION 14 TRANSPORT INFORMATION

Not a hazardous material as shipped per 49 CFR table 172.101. Consult 49 CFR to assure compliance with all applicable federal, state/provincial and local laws and regulations that may apply to you.

SECTION 15 | **REGULARTORY INFORMATION**

US Federal Regulations:

OSHA standards require that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, safety data sheet (SDS) sheets, training and access to written records. We request that you, as per your legal duty to, make all information in this SDS available to your employees and those who handle or consume the product. To aid our customers in complying with regulatory requirements regulatory information for components of this product are indicated below

This <u>mixture</u> has no established regulatory information all regulatory information given is based on individual components of the mixture by component number.

Regulatory information has not been established for this product. Regulatory information on components within this mixture is given by:

COMPONENT # Regulatory Information

1. Sodium Metabisulfite OSHA: Harmful by ingestion, irritant. SARA311/312: Acute Health Hazard

SECTION 16 OTHER INFORMATION

While the information is believed to be accurate, CTI makes no representations as to its accuracy or sufficiency. This SDS summarizes to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources of each individual component. Since

SDS Product: Red Relief - Part A

Page 5 of 6



CTI cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material. Users are responsible to verify this data under their own operating conditions to determine whether this product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance on information contained herein. This information relates only to the product-designated herein, and does not relate to its use in combination with any other material or in any other process.

SDS Product: Red Relief - Part A

Page 6 of 6



Product Name: RED RELIEF - PART B

Revision Date: 10/11/2013

SAFETY DATA SHEET

SECTION 1 | MATERIAL AND MANUFACTURER IDENTIFICATION

PRODUCT

Product Identifier: RED RELIEF - PART B
Intended Product Use: Food dye stain remover
Manufacturer Identification 3080 B - 3080 A

MANUFACTURER

Namco Mfg., Inc. 1651 Blalock Rd. Houston, TX 77080 1-800-634-5816 * 713-932-8293

24 hours Emergency Assistance Calls (USA): CHEMTREC (800) 424-9300 Please reference name and manufacturers identification number

SECTION 2

HAZARD(S) INDENTIFICATION

GHS Classification

Flammable Liquid (Category 3)
Acute Oral Toxicity (Category 5)
Acute Dermal Toxicity (Category 5)

Routes of Exposure: Eye contact, skin contact, inhalation, and ingestion.

Inhalation: Inhalation of mist or vapor may cause severe irritation of the respiratory tract that usually subsides after exposure ceases.

Eye Contact: Vapors may irritate eyes. Direct or prolonged contact with eyes will be painful and irritating may also cause possible permanent damage. Seek immediate medical attention for prolonged irritation.

Skin Contact: Repeated exposure may cause skin irritation, drying, chapping.

Ingestion: If swallowed will cause irritation/corrosion of the gastrointestinal tract. Seek immediate medical attention.

Carcinogenic Potential: Not established

Acute Effects: This product is considered to be a potential irritant. This product should not be used for any other

purpose than the intended use in section 1.

Chronic Effects: Not established.





Health hazard	2
Flammability hazard	2
Reactivity hazard	0
Other hazard	

Signal word: WARNING

Hazard statement(s): **H226: Flammable liquid;**

H303: May be harmful if swallowed;

H313: May be harmful in contact with skin.

1



SECTION 3 COMPOSITON/INFORMATION ON INGREDIENTS

 COMPONENT
 CAS #
 CONCENTRATIONS

 1. EDTA Sodium Salt
 13235-36-4
 1-10%

 2. Isopropyl Alcohol
 67-63-0
 15-30%

 3. Sodium dodecyl sulfate
 151-21-3
 1-10%

This SDS contains confidential and propriety information of CTI and is protected by copyright, trade secret and other State and Federal laws. Its receipt or possession does not convey any rights to reproduce its contents, or to manufacture, use or anything it may describe. Reproduction, disclosure, or use without specific written authorization of CTI is strictly forbidden.

SECTION 4 | **FIRST-AID MEASURES**

Inhalation: Remove from further exposure to fresh air. If respiratory irritation, dizziness, or nausea occurs seek immediate medical attention.

Eye Contact: Flush eyes with a directed stream of water for 15 minutes, forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissue. Washing eyes immediately after exposure is essential to achieve maximum effectiveness and minimize potential irritation. If irritation persists, seek immediate medical attention.

Skin Contact: Wash contact areas with soap and water. Launder exposed clothing before reuse.

Ingestion: If swallowed, do not induce vomiting. Seek immediate medical attention.

SECTION 5 | FIRE-FIGHTING MEASURES

FLAMMABILITY PROPERTIES

Flashpoint: Flammable; Flashpoint for mixture not established; some components have flashpoint >50F to warrant a flammable danger. Flash point 59F, 15C

Flammable Limits: N/A

Auto ignition Temperature: N/A

FIREFIGHTING PROCEDURES

General Hazard: During a fire smoke may contain the original material in addition to toxic and or irritating compounds. Avoid heat sparks or open flame. Decomposition releases oxygen, which can intensify the fire.

Firefighting Instructions: Evacuate all unnecessary personnel. Use dry chemical or CO₂. Direct water stream may spread the fire.

Firefighting Equipment: Firefighters should wear NICSH/MSHA approved self-contained, positive pressure breathing apparatus and full protective clothing.

Hazardous Combustion Products: During fire, smoke may contain the original material in addition to toxic and/or irritating compounds such as but not limited to: CO, CO₂.

Unusual Fire and Explosion Hazards: Not established



SECTION 6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Persons performing the clean up should wear personal protective equipment sufficient to keep material away from skin. Avoid direct contact with material. See section 4 for First-Aid Advice. See section 5 for Firefighting Advice.

PROTECTIVE MEASURES

To minimize exposure to all chemicals, including this product, use good industrial hygiene and common sense. Use only in well ventilated area. If necessary, use exhaust ventilation to insure adequate ventilation. Insure that water is readily available and that you are prepared to properly wash out your eyes should the need arise. (See section 4 for more advice). Wear NIOSH/MSHA approved organic respirator when ventilation is not adequate or when the sufficiency of ventilation to maintain concentrations below exposure limits is in question. Wear chemical safety goggles to protect against splashes or contact with eyes. See OSHA 29 CFR 1910.33

CLEAN-UP PROCEDURES

Small Spills: Wipe up or mop to dispose of spill in DOT approved waste container.

Large Spills: Contain by diking with soil or other non-combustible absorbent material, and dispose into DOT approved waste container. If possible complete clean up on a dry basis. Comply with all applicable governmental regulations on spill reporting, handling and disposal of waste. Contain all spills or leaks to prevent discharge into the environment. Responsibility of all spills or releases reported to the appropriate local, state and federal agencies falls upon the user.

SECTION 7 HANDLING AND STORAGE

HANDLING

This product is professional strength product to be used by professionals only. Avoid breathing vapors/mist of this product. Always keep container tightly closed and properly labels. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Impervious boots/shoes covering should be used if material is anticipated to contact feet. As with all chemicals, practice good industrial hygiene when handling this product. Always work in a well-ventilated area and avoid inhalation of product vapor or mist. Do not ingest.

The manufacturer and seller warrant that this product conforms to its standard specifications when used according to directions. As the conditions of method of its use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for use of this product. Information contained herein is believed to be true but all statements and suggestions are made without any warranty, expressed or implied, regarding accuracy of the information. The hazards connected with the use of this material and the results to be obtained from the use thereof.

STORAGE

Avoid excessive heat. Avoid storage with oxidizing or reducing agents and/or acids. Employees should be trained to handle this product safely. Store the product in a cool dry area away from ignition sources. Loosen closures cautiously. Avoid storage with combustible organic materials.

Storage temperature: Store in cool dry place

Storage pressure: Atmospheric



NIOSH

SECTION 8 | EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS

Exposure limits have not been established for this mixture. Avoid, as far as reasonably practicable, inhalation of vapor, mists or fumes generated. Limits for components are listed below:

ACGIH TI V

	OUITA I EE	ACCIII ILI	1110011
COMPONENT #	TWA STEL	TWA STEL	TWA STEL
1. EDTA Sodium Salt	not established	not established	not established
2. Isopropyl Alcohol	400ppm	200ppm	400ppm, 980mg/m3
3. Sodium dodecyl sulfate	not established	not established	not established

OSHA PEL

ENGINEERING CONTROLS

The level of protection and types of control will vary depending upon potential exposure conditions. If user operations generate dust, fume or mist, use adequate ventilation to keep exposure below exposure limit.

PERSONAL PROTECTION

Ventilation and engineering controls: Use only in well ventilated area. If necessary, use exhaust ventilation to insure adequate ventilation. Insure that water is readily available and that you are prepared to properly wash out your eyes should the need arise. (Refer to section 4).

Respiratory: Wear NIOSH/MSHA approved respirator when ventilation is not adequate. A NIOSH /MSHA –approved air purifying respirator with an organic vapor cartridge or canister may be advisable under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure, air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection. Eye Protection: Wear safety goggles to protect against eye contact. See OSHA 29 CFR 1910.33 Skin: Wear chemical impervious gloves. Wear protective clothing to minimize skin contact. Wash skin after use.

Wash contaminated clothing and dry before reuse.

Other: One should always use chemicals with an awareness of the potential hazard of the effect on the human system. To minimize employee exposure to all chemicals, including this product, use good industrial hygiene practices.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical State and Appearance: Liquid Odor: moderate astringent odor

Vapor density: N/A

Freezing point: N/A Solubility in water: soluble

Flammability: N/A Evaporation rate: N/A

Upper/lower flammability or explosive limits: N/A

Odor threshold: N/A Flash point: >59F Evaporation rate: N/A

Upper/lower flammability or explosive limits: not flammable

Vapor pressure: N/A

Auto-ignition temperature: N/A

Color: Clear pH: 11.0

Boiling point: >180F Melting point: N/A Density: N/A Particle size: N/A Viscosity: N/A Vapor pressure: N/A Vapor density: N/A Relative density: N/A

Flammability (solid, gas): N/A Decomposition temperature: N/A

Vapor density: N/A

Partition coefficient: n-octanol/water: N/A



SECTION 10 | STABILITY AND REACTIVITY

Chemical Stability: Unstable under ambient temperature and atmospheric pressure.

Conditions to avoid: Keep away from heat or excessive pressure. Keep away from heat or excessive pressure. Do not contaminate.

Incompatibility with other materials: Heavy metals, combustible organic materials, reducing agents.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Sulfur oxides.

Hazardous polymerization: Major components of this mixture show no hazardous polymerization.

Conditions to Avoid: Oxygen, which supports combustion.

SECTION 11 TOXICOLOGICAL INFORMATION

Toxicological information has not been established on this mixture. Toxicological information on components within this mixture is given by:

COMPONENT # TOXICITY

1. EDTA Sodium Salt LD_{50} Oral - rat - 630-1260 mg/kg 2. Isopropyl Alcohol LD_{50} Oral - rat - 5,045 mg/kg

LC₅₀ Inhalation - rat - 8 h- 18,000ppm

3. Sodium dodecyl sulfate LD₅₀ Oral - rat – 1288 mg/kg

LC₅₀ Inhalation - rat - 1h- >3,900mg/m3

LD₅₀ Dermal - rat - 580 mg/kg

SECTION 12 | ECOLOGICAL INFORMATION

Ecological information has not been established for this product. Ecological information on components within this mixture is given by:

COMPONENT # TOXICITY

1. EDTA Sodium Salt Not established

2. Isopropyl Alcohol LC₅₀ – Pimephales promelas(fat head minnow) – 9,640 mg/l-96.0h

ED₅₀ – Daphnia (other aquatic invertebrates) – 5.102 mg/l – 48 h

3. Sodium dodecyl sulfate Mortality NOEC – Oncorhynchus mykiss (rainbow trout) – 19.5 mg/l -96h

LC50 - Oncorhynchus mykiss (rainbow trout) – 2.68 mg/l – 6d

SECTION 13 DISPOSAL CONSIDERATIONS

Dispose of all waste, empty bottles and contaminated equipment in accordance with all applicable federal, state and local health and environmental regulations.

Do not dump into storm drains or any body of water. All disposal methods must be in compliance with all federal, State/ Province and local laws and regulations. Regulations may vary in different locations.

Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. The vendor has no control over the management practices or the processes by which the party who handles or uses this material. The information presented here pertains only to the product as shipped in its intended condition and recommended usage.



SECTION 14 TRANSPORT INFORMATION

Not a hazardous material as shipped per 49 CFR table 172.101 Consult 49 CFR to assure compliance with all applicable federal, state/provincial and local laws and regulations that may apply to you.

Shipping Instructions as shipped are: ORMD/LTD QTY Exemptions Used 173.120(B2), 173.121, 173.150(B&C) LTD QTY & ORM-D

DOT (US)

Proper Shipping Name Consumer commodity Hazard Class ORM-D Description Consumer commodity, ORM-D

SECTION 15 REGULARTORY INFORMATION

US Federal Regulations:

OSHA standards require that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, safety data sheet (SDS) sheets, training and access to written records. We request that you, as per your legal duty to, make all information in this SDS available to your employees and those who handle or consume the product To aid our customers in complying with regulatory requirements regulatory information for components of this product are indicated below

This <u>mixture</u> has no established regulatory information all regulatory information given is based on individual components of the mixture by component number

Regulatory information has not been established for this product. Regulatory information on components within this mixture is given by:

COMPONENT # Regulatory Information

1. EDTA Sodium Salt OSHA Hazards: Harmful by ingestion, Irritant

SARA 311/312 Hazards: Acute Health Hazard,

2. Isopropyl Alcohol OSHA Hazards: Flammable Liquid, Target Organ Effect, Irritant

SARA 311/312 Hazards: Fire Hazard, Acute Health Hazard, Chronic Health
3. Sodium dodecyl sulfate

OSHA Hazards: Flammable Solid, Target Organ Effect, Irritant, Toxic by skin

absorption

SARA 311/312 Hazards: Acute Health Hazard, Fire Hazard, Chronic Health

Hazard

SECTION 16 OTHER INFORMATION

While the information is believed to be accurate, CTI makes no representations as to its accuracy or sufficiency. This SDS summarizes to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources of each individual component. Since CTI cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material. Users are responsible to verify this data under their own operating conditions to determine whether this product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance on information contained herein. This information relates only to the product-designated herein, and does not relate to its use in combination with any other material or in any other process.

Page 6 of 6