



January 30, 2026

HD Supply  
3400 Cumberland Blvd SE  
Atlanta GA 30339

RE: Deflecto Item Number F0425, 4" x 25' Supurr-Flex® Duct

Please note Deflecto Item F0425, 4" x 25' Supurr-Flex® Duct is manufactured to meet, and or exceed, the requirements specified in the UL Standard 2158A for electric and gas dryer venting.

UL 2158A is the Underwriters Laboratories standard for **Clothes Dryer Transition Ducts**, which are the short, flexible ducts connecting your dryer to the wall vent, requiring them to be listed (labeled) for safety, typically made of aluminum/foil, and generally limited to 8 feet long and not concealed within walls, ensuring proper, safe ventilation; you can find official copies for purchase from UL or ANSI..

**What UL 2158A Specifies:**

- **Purpose:** Governs the flexible duct connecting a dryer's exhaust to the fixed duct in the building.
- **Material:** Focuses on flame resistance, often requiring all-metal (aluminum) or foil/plastic construction that resists crushing.
- **Installation Rules:**
  - Must be a single piece, no splicing allowed.
  - Maximum length of 8 feet.
  - Cannot be hidden inside walls, floors, or other concealed spaces.
  - Must have the UL 2158A mark/label.

Please feel free to contact me if you require additional information.

Sincerely,

**Scott Sorrells/Product Manager - Air Distribution**  
**Indianapolis, Indiana**  
**Office 317.849.9555 Ext. 4234/Mobile 317.554-9866**  
**Email [scott.sorrells@deflecto.com](mailto:scott.sorrells@deflecto.com)**