

DEHUMIDIFIERS

Models: SD22C1

SD35C1

SD50C1









Dehumidifier ENERGY STAR® Certified

Specifications

Voltage (Unit Specific) 115 Vac

Frequency 60 HZ

requeriey oo rii

Plug Rewired 5-15P

Control Panel | Digital Display & Interface

Timer Settings Up to 24 Hours

Fans Speeds High/Low

Regrigerant | Eco-Friendly R-410A

Filter Reusable

Mode Selection

Adjust, Continuous, and Comfort Mode

Check Filter Indicator

Light illuminates to notify when the filter needs to be cleaned or replaced.

Auto-Restart

If power loss occurs, the system will automatically resume operation based on previous settings.

Optimal Conditions for Cooling

Outdoor Temperature: 64-109°F Indoor Temperature: 62-90°F

Certifications

C-UL-US

ENERGY STAR® MOST EFFICIENT

CEC & DOE Listed

Warranty

2-Year Limited Warranty on Entire Unit5-Year Limited Warranty on Sealed System



DEHUMIDIFIERS

Models: SD22C1

SD35C1

SD50C1









	Model #	SD22C1	SD35C1	SD50C1
Dehumidifying Performance	Capacity (pints/day)	22	35.02	49.93
	Current (A)	2.2	3.25	4.8
	Input Power (W)	250	360	515
	Refrigerant Type	R410a	R410a	R410a
	Refrigerant Charge Amount(OZS)	5.29	7.05	6.88
Def	Design Pressure (High/Low)	540/300 PSIG	540/300 PSIG	540/300 PSIG
General Specifiations	Airflow CFM (H/L)	135/118	188/165	218/188
	Max. Indoor Sound Level	54dBA	54dBA	54dBA
	Bucket Capacity (L)	3L	6L	6L
	Net Weight	33 Lbs.	41 Lbs.	42 Lbs.
Electrical Specifications	Frequency	60Hz	60Hz	60Hz
	NEMA Plug Configuration	5-15P	5-15P	5-15P
	Power Cord Length	6 Ft.	6 Ft.	6 Ft.