



## THROUGH-THE-WALL AC & HEAT/COOL

Models:	ST08R1	ST08R1-H
	ST10R1	ST10R2
	ST10R2-H	ST12R1
	ST12R2	ST12R2-H
	ST14R2	ST14R2-H



Through The Wall

### Specifications

Voltage (Unit Specific)	115 or 230/208 Vac
Frequency	60 HZ
Plug Rewired	LCDI NEMA Type
Control Panel	Digital Display & Interface
Temperature Display	Fahrenheit or Celsius
Timer Settings	Up to 24 Hours
Fans Speeds	High/Medium/Low
Refrigerant	Eco-Friendly R-410a
Filter	Reusable
Directional Air Louvers	4-Way Manual Control
Wireless Remote	Included
Installation Hardware	Included

### Mode Selection

Choose between fan, cooling, dehumidifying & automatic operation.

### Sleep Feature

Slowly increases room temperature by 4°F when activated and returns to the original temperature setting after 7 hours.

### Energy Saver Feature

Optimally manages system operation to minimize power consumption.

### Follow-Me Feature

Automatically adjusts thermostatic performance based on location of the remote.

### Check Filter Indicator

Light illuminates to notify when the filter needs to be cleaned or replaced.

### Auto-Restart

If power loss occurs, the system will automatically resume operation based on previous settings.

### Optimal Conditions for Cooling

Outdoor Temperature: 64-109°F

Indoor Temperature: 62-90°F

### Certifications

C-UL-US

CEC & DOE Listed

### Warranty

2-Year Limited Warranty on Entire Unit

5-Year Limited Warranty on Sealed System

For additional information, contact 1-800-431-3000

Seasons is a registered trademark of HD Supply Facilities Maintenance, Ltd.

Dimensions and specifications are subject to change without notice. Rev 8/20/2021



# THROUGH-THE-WALL AC & HEAT/COOL

Models:	ST08R1	ST08R1-H
	ST10R1	ST10R2
	ST10R2-H	ST12R1
	ST12R2	ST12R2-H
	ST14R2	ST14R2-H



NEMA Receptacle Configuration.



For Compatibility, Match to NEMA Plug.

		Cool Only					
Model #		ST08R1	ST10R1	ST10R2	ST12R1	ST12R2	ST14R2
Heating/Cooling Performance	Cooling Capacity (BTU/Hr)	8,000	10,000	10,000	12,000	12,000	14,000
	Electric Heating (BTUH)	N/A	N/A	N/A	N/A	N/A	N/A
	Current	7	8.3	4.5	10	5.2	6.9
	Input Power	783	943	943	1142	1142	1,505
	Refrigerant Type	R410a	R410a	R410a	R410a	R410a	R410a
	Refrigerant Charge Amount	500g	590g	590g	620g	620g	610g
	Design Pressure (High/Low)	520/300 PSIG	520/300 PSIG	520/300 PSIG	520/300 PSIG	520/300 PSIG	520/300 PSIG
General Performance	EER	10.6	10.6	10.6	10.5	10.5	9.3
	Airflow CFM (H/M/L)	253/218/190	270/235/204	275/241/210	287/260/234	278/258/235	296/275/253
	Room Area	251-350 sq. ft.	351-450 sq. ft.	351-450 sq. ft.	451-550 sq. ft.	451-550 sq. ft.	551-700 sq. ft.
	Max. Indoor Sound Level	56dBA	57dBA	59dBA	60dBA	61dBA	61dBA
Electrical Specifications	Voltage	115V	115V	230/208V	115V	230/208V	230/208V
	Frequency	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz
	NEMA Plug Configuration	5-15P	5-15P	6-15P	5-15P	6-15P	6-15P
	Power Cord Length	6 Ft.	6 Ft.	6 Ft.	6 Ft.	6 Ft.	6 Ft.
Dimensions	Net Weight	68 Lbs.	68 Lbs.	69 Lbs.	77 Lbs.	76 Lbs.	75 Lbs.
	Product Dims	24-1/4" x 20-1/4" x 14-1/2"	24-1/4" x 20-1/4" x 14-1/2"	24-1/4" x 20-1/4" x 14-1/2"	24-1/4" x 20-1/4" x 14-1/2"	24-1/4" x 20-1/4" x 14-1/2"	24-1/4" x 20-1/4" x 14-1/2"
	Package Dims	28" x 26-9/16" x 16-15/16"	28" x 26-9/16" x 16-15/16"	28" x 26-9/16" x 16-15/16"	28" x 26-9/16" x 16-15/16"	28" x 26-9/16" x 16-15/16"	28" x 26-9/16" x 16-15/16"

For additional information, contact 1-800-431-3000

Seasons is a registered trademark of HD Supply Facilities Maintenance, Ltd.

Dimensions and specifications are subject to change without notice. Rev 8/20/2021



## THROUGH-THE-WALL AC & HEAT/COOL

Models: ST08R1 ST08R1-H  
 ST10R1 ST10R2  
 ST10R2-H ST12R1  
 ST12R2 ST12R2-H  
 ST14R2 ST14R2-H



NEMA Receptacle Configuration.



For Compatibility, Match to NEMA Plug.

		Heat/Cool			
Model #		ST08R1-H	ST10R2-H	ST12R2-H	ST14R2-H
Heating/Cooling Performance	Cooling Capacity (BTU/Hr)	8,000	10,000/9,800	12,000/11,700	14,000/13,600
	Electric Heating (BTUH)	4,200	10,600/8,600	10,600/8,600	10,600/8,600
	Current	7.8	4.6/5.0	5.5/5.9	6.9/7.5
	Input Power	833	1042/1022	1263/1232	1505/1431
	Refrigerant Type	R410a	R410a	R410a	R410a
	Refrigerant Charge Amount	420g	510g	620g	610g
	Design Pressure (High/Low)	520/300 PSIG	520/300 PSIG	520/300 PSIG	520/300 PSIG
General Performance	EER	9.6	9.6	9.5	9.3
	Airflow CFM (H/M/L)	270/235/202	293/275/253	287/264/241	283/269/249
	Room Area	251-350 sq. ft.	351-450 sq. ft.	451-550 sq. ft.	551-700 sq. ft.
	Max. Indoor Sound Level	56dBA	59dBA	60dBA	61dBA
Electrical Specifications	Voltage	115V	230/208V	230/208V	230/208V
	Frequency	60Hz	60Hz	60Hz	60Hz
	NEMA Plug Configuration	5-15P	6-20P	6-20P	6-20P
	Power Cord Length	6 Ft.	6 Ft.	6 Ft.	6 Ft.
Dimensions	Net Weight	68 Lbs.	71 Lbs.	78 Lbs.	79 Lbs.
	Product Dims	24-1/4" x 20-1/4" x 14-1/2"	24-1/4" x 20-1/4" x 14-1/2"	24-1/4" x 20-1/4" x 14-1/2"	24-1/4" x 20-1/4" x 14-1/2"
	Package Dims	28" x 26-9/16" x 16-15/16"	28" x 26-9/16" x 16-15/16"	28" x 26-9/16" x 16-15/16"	28" x 26-9/16" x 16-15/16"

For additional information, contact 1-800-431-3000

Seasons is a registered trademark of HD Supply Facilities Maintenance, Ltd.

Dimensions and specifications are subject to change without notice. Rev 8/20/2021