



Window Air Conditioner Cool Only

Model: SW06R1 SW08R1
 SW12R1 SW10R1
 SW18R2 SW15R1
 SW25R2



All models except SW25R2



SW25R2



**Window Air Conditioner Cooling Only
 Fits Standard Double Hung Windows**

Specifications

Voltage (Unit Specific)	115 or 230/208 Vac
Frequency	60 Hz
Plug Rewired	LCDI NEMA Type
Control Panel	Digital Display & Interface
Temperature Display	Fahrenheit or Celsius
Timer Settings	Up to 24 Hours
Fans Speeds	High/Medium/Low
Refrigerant	Eco-Friendly R-32
Filter	Reusable
Directional Air Louvers	4-Way Manual Control
Wireless Remote	Included (excluding mech. model)
Installation Hardware	Included

Mode Selection

Choose between fan, cooling, dehumidifying & automatic operation.

Sleep Feature

Slowly increases room temperature by 4°F when activated and returns to the original temperature setting after 7 hours.

Energy Saver Feature

Optimally manages system operation to minimize power consumption.

Follow-Me Feature

Automatically adjusts thermostatic performance based on location of the remote.

Check Filter Indicator

Light illuminates to notify when the filter needs to be cleaned or replaced.

Auto-Restart

If power loss occurs, the system will automatically resume operation based on previous settings.

Optimal Conditions for Cooling

Outdoor Temperature: 64-109°F

Indoor Temperature: 62-90°F

Certifications

CSA
CEC & DOE Listed

Warranty

2-Year Limited Warranty on Entire Unit
5-Year Limited Warranty on Sealed System



Window Air Conditioner

Model: SW06R1 SW08R1
 SW12R1 SW10R1
 SW18R2 SW15R1
 SW25R2




NEMA Receptacle Configuration.





For Compatibility, Match to NEMA Plug.



Model #	SW06R1	SW08R1	SW10R1	SW12R1	SW15R1	SW18R2	SW25R2	
Cooling Performance	Capacity (BTU/Hr)	6,000	8,000	10,000	12,000	14,500	18,000/17,700	25,000/24,700
	Current	4.5A	5.9A	8.03A	9.72A	11.8A	7.2/7.6A	12.2/13A
	Input Power	490W	667W	925W	1000W	1280W	1525/1500W	2427/2398W
	Refrigerant Type	R32	R32	R32	R32	R32	R32	R32
	Refrigerant Charge Amount	220g	300g	350g	420g	500g	700g	830g
	Design Pressure (High/Low)	520/300 PSIG	520/300 PSIG	520/300 PSIG	520/300 PSIG	520/300 PSIG	520/300 PSIG	520/300 PSIG
General Performance	CEER	12.1	12.0	12.0	12.0	11.3	11.8	10.3
	Airflow CFM (H/M/L)	169/145/132	197/166/149	321/285/252	310/278/247	298/265/229	363/328/301	461/443/421
	Room Area	151-200 sq. ft.	251-350 sq. ft.	351-450 sq. ft.	451-550 sq. ft.	551-700 sq. ft.	701-1000 sq. ft.	1001-1500 sq. ft.
	Max. Indoor Sound Level	56dBA	59dBA	61dBA	61 dBA	61 dBA	57.5 dBA	59.3 dBA
Electrical Specifications	Voltage	115V	115V	115V	115V	115V	230/208V	230/208V
	Frequency	60 Hz.	60 Hz.	60 Hz.	60 Hz.	60 Hz.	60 Hz.	60 Hz.
	NEMA Plug Configuration	5-15P	5-15P	5-15P	5-15P	5-15P	6-15P	6-20P
	Power Cord Length	6-1/2 Ft.	6-1/2 Ft.	6-1/2 Ft.	6-1/2 Ft.	6-1/2 Ft.	6-1/2 Ft.	6-1/2 Ft.
Dimensions	Net Weight	42 Lbs.	47 Lbs.	58 Lbs.	67 Lbs.	71 Lbs.	117 Lbs.	130 Lbs.
	Product dims	15.75" x 18.54" x 13.39"	15.75" x 18.54" x 13.39"	18.98" x 21.46" x 14.65"	18.98" x 21.46" x 14.65"	18.98" x 21.46" x 14.65"	23.62" x 25.39" x 17.91"	26.50" x 26.54" x 18.62"
	Window Opening Width	23"-36"	23"-36"	23"-36"	23"-36"	23"-36"	28"-40-1/2"	31"-42"
	Window Opening Height	14" Min.	14" Min.	15-1/2" Min.	15-1/2" Min.	15-1/2" Min.	18-1/2" Min.	19-1/2" Min.





SW06R1 / SW08R1



SW10R1 / SW12R1 / SW15R1



SW18R2



SW25R2

