



Telephone: (845) 365-8200 * Website: www.dynarex.com
Toll Free: (888) DYNAREX * Website: www.thcnet.com
Fax: (845) 365-8201

Reviewed on 9/15/16

Safety Data Sheet

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product Identifiers:	Dynarex Instant Cold Pack with Urea (Non-Toxic), Dynarex Reorder # 4517 & 4518
Other means of identification:	Non-Toxic Instant Cold Pack
Recommended use of the chemical	Instant Cold Pack for thermal therapy Single Use For relief of pain and swelling caused by sprains, strains, contusions, minor burns, toothaches and insect bites
And restrictions on use	CAUTION: <ul style="list-style-type: none">• For external use only. Adult supervision recommended.• Do not puncture. If bag breaks and fluid contacts skin or eyes, immediately flush area with large amounts of water.• Do not swallow contents. If contents are accidentally swallowed, drink large amounts of water (not milk) and contact a Poison Control Center or physician.• Cold therapy should not be used by individuals with circulatory problems, unless under the direct supervision of a physician.
Name of the Manufacturer:	Dynarex Corporation
Manufacturer's Address:	10 Glenshaw Street Orangeburg, NY 10962
Emergency Phone No.:	Toll Free: 1-888-DYNAREX Phone: (845) 365-8200 Fax: (845) 365-8201 At other times, contact the local Poison Control Center



Telephone: (845) 365-8200 * **Website:** www.dynarex.com
Toll Free: (888) DYNAREX * **Website:** www.thcnet.com
Fax: (845) 365-8201

SECTION 2. HAZARDS IDENTIFICATION

2.1. Hazard classification
 Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements
Signal word
 Not applicable.
Symbols
 Not applicable.
Pictograms
 Not applicable.
Precautionary Statements
 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified
 None.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS	% Weight	EXPOSURE GUIDELINE		
		Limits	Agency	Type
None				
OTHER COMPONENTS	% Weight	EXPOSURE GUIDELINE		
		Limits	Agency	Type
Urea CAS# 57-13-6	40-70	Not Established		
Water CAS# 7732-18-5	30-60	Not Established		

Note: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or you local agencies, for further information.

SECTION 4. FIRST AID MEASURES

Eye: If irritation or redness develops, move victim away from exposure and into fresh air. Flush eyes with clean water. If symptoms persist, seek medical attention.

Skin: Remove contaminated shoes and clothing and cleanse affected area(s) thoroughly by washing with mild soap and



Telephone: (845) 365-8200 * **Website:** www.dynarex.com
Toll Free: (888) DYNAREX * **Website:** www.thcnet.com
Fax: (845) 365-8201

water. If irritation or redness develops and persists, seek medical attention.

Inhalation (Breathing): If respiratory symptoms develop, move victim away from source of exposure and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, clear airway and immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

Ingestion (Swallowing): First aid is not normally required; however, if swallowed and symptoms develop, seek medical attention.

SECTION 5. FIRE FIGHTING MEASURES

Flammable Properties: Flash Point: None
OSHA Flammability Class: Not applicable
LEL/UEL: No data
Autoignition Temperature: No data

Unusual Fire & Explosion Hazards: Closed containers exposed to extreme heat can rupture due to pressure buildup.

Extinguishing Media: Use extinguishing agent suitable for type of surrounding fire.

Fire Fighting Instructions: For fires beyond the incipient stage, emergency responders in the immediate hazard area should wear bunker gear. When the potential chemical hazard is unknown, in enclosed or confined spaces, or when explicitly required by DOT, a self-contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8). Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Move undamaged containers from immediate hazard area if it can be done with minimal risk. Water spray may be useful in minimizing or dispersing vapors. Cool equipment exposed to fire with water, if it can be done with minimal risk.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Stay upwind and away from spill/release. Notify persons downwind of spill/release, isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant (see Section 8). Prevent spilled material from entering sewers, storm drains, other unauthorized treatment drainage systems, and natural waterways. Dike far ahead of spill for later recovery or disposal. Spilled material may be absorbed into an appropriate absorbent material. Notify appropriate federal, state, and local agencies. Immediate cleanup of any spill is recommended.

SECTION 7. HANDLING AND STORAGE

Handling:

Do not enter confined spaces such as tanks or pits without following proper entry procedures such as ASTM D-4276 and 29CFR 1910.146. The use of appropriate respiratory protection is advised when concentrations exceed any established exposure limits (see Section 2 and 8). Wash thoroughly after handling. Do not wear contaminated clothing or shoes. Use good personal hygiene practice.

Storage: Keep container(s) tightly closed. Do not heat or contact with strong oxidizers. Use and store this material in cool, dry, well-ventilated areas. Do not store at temperatures below 60°F. Store only in approved containers. Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage.



Telephone: (845) 365-8200 * **Website:** www.dynarex.com
Toll Free: (888) DYNAREX * **Website:** www.thcnet.com
Fax: (845) 365-8201

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls: If current ventilation practices are not adequate to minimize exposure, additional ventilation or exhaust systems may be required.

Personal Protective Equipment (PPE):

Respiratory: Respiratory protection is not usually required.

Skin: The use of gloves impermeable to the specific material handled is advised to prevent skin contact, possible irritation, and absorption (see glove manufacturer literature for information on permeability).

Eye/Face: Approved eye protection to safeguard against potential eye contact, irritation, or injury is recommended. Depending on conditions of use, a face shield may be necessary.

Other Protective Equipment: A source of clean water should be available in the work area for flushing eyes and skin. Impervious clothing should be worn as needed.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Note: Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm Hg (1 atm).

Flash Point: None to boiling

Flammable/Explosive Limits (%): No data

Autoignition Temperature: No data

Appearance: White solid in water bag

Physical State: solid/Liquid

Odor: None

pH: No data

Vapor Pressure (mm Hg): No data

Vapor Density (air=1): 0.6 H₂O, >1 Aerosol

Boiling Point: >212°F

Freezing/Melting Point: No data

Solubility in Water: 100%

Specific Gravity: 1.14

Percent Volatile: 50 wt%

Evaporation Rate (nBuAc=1): <1

SECTION 10. STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions of storage and handling.

Conditions To Avoid: None known

Incompatible Materials: Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products: If involved in a fire, oxides of carbon and nitrogen may be generated, exposure to heat may generate ammonia fumes.

Hazardous Polymerization: Will not occur.



Telephone: (845) 365-8200 * Website: www.dynarex.com
Toll Free: (888) DYNAREX * Website: www.thcnet.com
Fax: (845) 365-8201

SECTION 11. TOXICOLOGICAL INFORMATION

No definitive information available on carcinogenicity, mutagenicity, target organs or developmental toxicity.

SECTION 12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13. DISPOSAL CONSIDERATIONS

This material, if discarded as produced, is not a RCRA "listed" or "characteristic" hazardous waste. Use resulting in chemical or physical change or contamination may subject it to regulation as a hazardous waste. Along with properly characterizing all waste materials consult state and local regulations regarding the proper disposal of this material.

SECTION 14. TRANSPORT INFORMATION

Hazard Class or Division: Not classified as hazardous.

SECTION 15. REGULATORY INFORMATION

This material contains the following chemicals subject to the reporting requirements of **SARA 313** and 40 CFR 372.

--None--

Warning: This material contains the following chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm, and are subject to the requirements of **California Proposition 65** (CA Health & Safety Code Section 25249.5)

--None Known--

This material has not been identified as a carcinogen by NTP, IARC, or OSHA.

EPA (CERCLA) Reportable Quantity: --None--



Telephone: (845) 365-8200 * **Website:** www.dynarex.com
Toll Free: (888) DYNAREX * **Website:** www.thcnet.com
Fax: (845) 365-8201

SECTION 16. OTHER INFORMATION

Disclaimer:

This Safety Data Sheet, which takes into consideration the requirements of Directive 76/768/EC and subsequent amendments and Directive 1999/45/EC plus subsequent amendments, has been prepared in accordance with Directive (EC) 1907/2006. It is believed to be correct and corresponds to the latest scientific/technical knowledge but all data, instructions, recommendations and/or suggestions are made without guarantee. No warranty, expressed or implied, is made and Dynarex Corp. assumes no legal responsibility or liability resulting from its use.