

PRODUCT SPECIFICATIONS

1 OF 1

PRODUCT DESCRIPTION

Aztec Plumbing Wax rings are made with a special blend of petroleum waxes to make a perfect seal between your toilet bowl and the floor drain. They fit 3" and 4" waste lines. Meets Fed. Spec. A-A-3110



PHYSICAL AND CHEMICAL PROPERTIES

Specific gravity	0.742 – 0.873
Melting point	158 - 203
Shelf life	1 year from manufacture date
Solubility in water	Insoluble
Odor	Mild petroleum

DIRECTIONS FOR USE

- Make sure that the wax ring is at room temperature (about 70 F).
- Remove wax ring of the wrapping.
- Place the wax ring firmly around the discharge opening and press to assure adhesion to the toilet.
- Gently twist to spread the wax and make a perfect seal.
- Tight the bolts carefully to prevent cracking or breaking the toilet bowl.

DESCRIPTION	PACK	CARTON WEIGHT
Bowl wax ring without flange	48	
Reinforced bowl wax ring without flange (for back outlet toilets)	48	
Bowl wax ring with flange	24	
Reinforced bowl wax ring with flange	30	
Extra thick bowl wax ring with flange	24	
Reinforced extra thick bowl wax ring with flange	24	
Extra thick bowl wax ring without flange	24	
Reinforced urinal wax ring	24	

- All products can be manufactured in polyethylene sheets or plastic trays.
- Any specification can be adjusted for particular needs.
- Toilet Bolt Sets can be included in any product.

For more information visit our website at www.aztec-plumbing.com or contact your sales representative.