PRODUCT SPEC SHEET LED LIGHT FIXTURES





Product Overview



Package Contents: (4) LED Downlights, (4) Medium Socket Base Adaptors, (12) Friction Clips (pre-installed)

PRODUCT DESCRIPTION

4 in. Matte White Integrated LED Recessed Trim with Selectable Color Temperature (4-Pack)

| Model # | F |
|----------------|---|
| NS01fA10ER4-24 | |
| Part # | |
| 312481 | |

| Fixture Category | |
|------------------------------|------|
| Recessed | |
| USN# | |
| 325871363 | |
| s clock look of recorded lie | th+i |

| Certifications | | | | |
|----------------|--|--|--|--|
| UL, T24 | | | | |
| Pack Size | | | | |
| 4 | | | | |

The Maintenance Warehouse 4in. Color temperature select LED downlight is an easy way to upgrade existing can lights to the sleek look of recessed lighting and LED energy efficient technology. These LED downlights are compatible with most dimmer switches and are equipped with a unique color temperature (CCT) changing technology. Now you can select your color temperature depending on your needs or preferences with the flip of a switch located on the back of the downlight. Test different color temperatures before installation and never be dissatisfied with CCT again. Color temperature of these LED downlights ranges from Warm White (2700K) to Daylight (5000K), with three options in between: Soft White (3000K), Neutral White (3500K) and Bright White (4000K).

| Benefits | Construction | Wattage | Installation | Lumens |
|---|--------------|---------|----------------|--------|
| Using only 9-Watts of energy but produce brightness | Metal | 9W | Friction Clips | 650 |
| comparable to a 65-watt incandescent bulb, these LED | | | | |

•Compatible with 4in. cans 72.2 lumens per Watt


•Integrated switch to select color temperature

| Lamp Life | Fixture Type | Beam Angle | Correlated Color Temperature | Color Rendering Index | Dimming |
|-------------|----------------------------------|------------|--|--------------------------|-------------|
| 50000 hours | Integrated LED 65W Equivalent | 90.5 deg | 5 way: CCT Select 2700K/3000K/3500K/4000K/5 000K | 90 CRI | Down to 10% |


| Trim | Finish | Rating | Electrical | Compliance | Warranty |
|-------|--------|----------|------------|------------|----------|
| Metal | White | IC Rated | 120V | UL, T24 | 5 years |

Wet Rated

Dimensional Diagrams



Luminous Intensity Distribution Diagram



AVERAGE BEAM ANGLE (50%):90.5 DEG