



LED WRAP

- White steel housing
- Frosted white prismatic acrylic diffuser

LED

- 120V TRIAC dimmable (D1)
- 120-277V universal-voltage driver (MV)
- 120-277V, 0-10V DC dimmable (D2)
- 50,000 hr. LED life, 90 CRI

Warm White	LED	Source Lumens	CCT	L	W	H
LWLO7242500L30D1	30W	2500	3000K	24"	7"	2-3/8"
LWLO7483000L30D1	36W	3000	3000K	48"	7"	2-3/8"
LWLO7485000L30D1	60W	5000	3000K	48"	7"	2-3/8"
LWLO7242500L30D2	30W	2500	3000K	24"	7"	2-3/8"
LWLO7483000L30D2	36W	3000	3000K	48"	7"	2-3/8"
LWLO7485000L30D2	60W	5000	3000K	48"	7"	2-3/8"

Cool White	LED	Source Lumens	CCT	L	W	H
LWLO7242500L40D1	30W	2500	4000K	24"	7"	2-3/8"
LWLO7483000L40D1	36W	3000	4000K	48"	7"	2-3/8"
LWLO7483600L40MV	30W	3600	4000K	48"	7"	2-1/2"
LWLO7485000L40D1	60W	5000	4000K	48"	7"	2-3/8"
LWLO7242500L40D2	30W	2500	4000K	24"	7"	2-3/8"
LWLO7483000L40D2	36W	3000	4000K	48"	7"	2-3/8"
LWLO7485000L40D2	60W	5000	4000K	48"	7"	2-3/8"
LWLO7487200L40MV	52W	6200	4000K	48"	11-1/2"	2-1/2"



LED WRAP CHASSIS

- White steel housing
- Frosted white prismatic acrylic diffuser

CHASSIS WITHOUT BALLAST

- For use with Type B, ballast bypass, LED tubes
- Single ended or double ended
- Lamp(s) not included

Prismatic	Lamp Qty.	L	W	H	White	Lamp Qty.	L	W	H
LWLO724SP	2	24"	7"	2-3/8"	LWLO724SW	2	24"	7"	2-3/8"
LWLO748SP	2	48"	7"	2-3/8"	LWLO748SW	2	48"	7"	2-3/8"
LWLO1148SP	4	48"	11-1/2"	2-3/8"	LWLO1148SW	4	48"	11-1/2"	2-3/8"

