

MasterColor CDM ED17 Protected

MasterColor CDM 150W/940 ED17P P CL ALTO+FB

Direct retrofit with immediate energy savings!Range of protected, high-efficiency long life ceramic metal halide lamps with a stable color over lifetime and a crisp, sparkling light to be used in open fixtures.

Product data

• General Characteristics

Base Medium [Single Contact Medium

Screw]

Brass [Brass Base] ED17P [Protected] Base Information Bulb

Bulb Material Hard Glass **Bulb Finish**

Operating Position Universal [Any or Universal (U)]

General Lighting Main Application

• Light Technical Characteristics

940 [CCT of 4000K] Color Code 87 (min), 90 (nom) Ra8

Color Rendering Index

Color Designation Deluxe Cool White

Color Temperature

4000 K 4150 K

Color Temperature technical

Initial Lumens

12000 Lm

Luminous Efficacy

80 Lm/W

Lamp

Lumen Maintenance -87 %

10% life

Lumen Maintenance -75 %

40% life

Design Mean Lumens 9000 Lm

Chromaticity Coor-

0.369 (min), 0.378 (nom), 0.387 (max)

dinate X

0.360 (min), 0.366 (nom), 0.372 (max) Chromaticity Coor-

dinate Y

• Electrical Characteristics

Watts 150 W Lamp Voltage 95 V Lamp Current 1.8 A

Ignition Time Re-ignition Time [min]

10 (max) s 12 (max) min

11.4 (max) mg

• Environmental Characteristics

Mercury (Hg)

Content

Picogram per Lumen 63.3 p/LuHr

Hour

• UV-related Characteristics

PET (NIOSH) 304 h.klx Damage Factor D/fc 0.281 -

• Luminaire Design Requirements

Cap-Base Tempera-

190 (max) C

ture

Bulb Temperature 400 (max) C

Product Dimensions

3.44 in Light Center Length

Max Overall Length 5.438 (max) in

(MOL) - C

Diameter D 2.125 in

Footnotes

Footnotes HID 902 [Exclusive to Philips Lighting

Company.]



MasterColor CDM ED17 Protected

• Product Data

Product number 377242

Full product name MasterColor CDM 150W/940 ED17P

P CL ALTO+FB

Short product name MHC150/U/MP/4K ALTO 12PK

Pieces per Sku 1

Warnings and Safety

• R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope ot the lamp is broken or puntured. Do not use where people will

eop_pck_cfg 12 Skus/Case 12

 Bar code on pack
 46677377243


 Bar code on case
 50046677377248

 Logistics code(s)
 928601171701

 eop_net_weight_pp
 0.070 kg

remain for more than a few minutes unless adequate shielding or other safety precuations are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

Dimensional drawing



MasterColor CDM 150W/940 ED17P P CL ALTO+FB

Product	C (Max)	D (Norm)
MHC P 150W/940 E26 ED17P U ALTO+FB	5.438	2.125



E26



Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.