



Project / Job Name:

Location:

Fixture Type:

Notes:

S18405 - 4.5 Watt LED PL 2-PIN; G23 Base;
27K/30K/35K/40K/50K CCT Selectable; 120-277 Volt;
Type B; Ballast Bypass



GENERAL

Company	SATCO
EA Height	6.89
EA Width	0.98
EA Length	1.46
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Polycarbonate (PC)
Status	Active
Style	Transitional
Most Current Generation	S29880
Surge Protection	Built-in surge protection - 1.5KV
Total Harmonic Distortion	<20%
CCT Selectable	True
Wattage Selectable	False
Finish Family	White
Amps	0.038-0.016A
Has Camera	False
IOT Enabled	False
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	5w/7w/9w

ELECTRICAL

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	360
Color Temp	Warm White to Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	450L/475L/500L/500L/475L
Volts	120V-277V
Watts	4.5W

PHYSICAL

Lamp Base	G23 (2-Pin)
Finish	Frost
Housing Color	White
ANSI Base	G23
Lamp Type	PL
MOD Lamps	1.27
MOL	6.5

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	True

PACKAGING

UPC	045923184055
Case Cube	0.5292
Case Height	8.46
Case Length	17.72
Case Quantity	50
Case UPC	10045923184052
Case Weight	8.05
Case Width	6.1
EA Cube	0.0057
EA Height	6.89
EA Length	1.46
EA Quantity	1
EA Weight	0.12
EA Width	0.98
Inner Cube	0.0761
Inner Height	7.48
Inner Length	5.31
Inner Quantity	10
Inner UPC	20045923184059
Inner Weight	1.54
Inner Width	3.31
Pack Type	Box
Web Length	6.5
Web Width	1.27

COMPLIANCE

CA Regulations	Exempt - Base Not Regulated
CA Status	Lawful for sale in California
FCC Compliant	True
Location Rating	Damp
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cETLus - Classified
CA Compliance Text	Lawful for sale
DLC Approved	False
Title 20	Exempt
T24 Compliant	False