





中国认可 国际互认 检验 INSPECTION CNAS IB0551



Report No.: 回常用处现 报告编号: GDLK2EBE05SDS

# MATERIAL SAFETY DATA SHEET

# 材料安全数据表

**Product** Rechargeable Li-ion Battery 二次锂离子电池组 产品 Type/Model C1264B8-02 型号 **Issue Date** 2024-12-26 签发日期 **Validity** 2025-01-01~ 2025-12-31 有效期 Compiler 编写 Reviewer 审核 **Approver** 批准

广州邦禾检测技术有限公司

Guangzhou MCM Certification & Testing Co., Ltd.



# Material Safety Data Sheet 材料安全数据表

SECTION 1 - CHEMICAL AND COMPANY IDENTIFICATION 第1节—化学品和公司标识				
Product	Rechargeable Li-ion Battery			
产品	二次锂离子电池组			
Type/Model: 型号	C1264B8-02			
Parameter 参数	14.4V, 7800mAh, 112.32Wh			
Usage	Others			
用途	其他			
Company	Guangdong Pow-Tech New Power Co.,Ltd.			
公司	广东力科新能源有限公司			
Address	No.9, Hengdong 3Rd, Hengkeng Shiling Industry Zone, Liaobu Town, Dongguan,			
地址	Guangdong, P.R. China			
HRAIT	东莞市寮步镇横坑石岭工业区横东三路9号			
Fax 传真				
Zip code 邮编				
E-mail 电子邮箱	zhanghongxing@fairlandgroup.com			
Emergency Tel. 紧急联系电话	13827469671			
Manufacturer	Guangdong Pow-Tech New Power Co.,Ltd.			
制造单位	广东力科新能源有限公司			
Address	No.9, Hengdong 3Rd, Hengkeng Shiling Industry Zone, Liaobu Town, Dongguan,			
地址	Guangdong, P.R. China			
시합·제L	东莞市寮步镇横坑石岭工业区横东三路9号			
Factory	Guangdong Pow-Tech New Power Co.,Ltd.			
生产单位	广东力科新能源有限公司			
Address	No.9, Hengdong 3Rd, Hengkeng Shiling Industry Zone, Liaobu Town, Dongguan,			
地址	Guangdong, P.R. China			
시 <b>라시</b> .	东莞市寮步镇横坑石岭工业区横东三路9号			

GB/T 16483: 2008 03 Page 2 of 11 Pages



### **SECTION 2 - HAZARDS IDENTIFICATION**

# 第2节一危害识别

# Classification 分类:

According to Regulation (EC) No 1272/2008 (CLP), the goods are not considered dangerous goods and therefore no SDS is required. The hazards mentioned in this document are in the case of a ruptured battery (Electrolyte leakage).

根据法规(EC) No 1272/2008 (CLP), 该货物不被视为危险货物, 因此不需要提供SDS。

本文件提到的危险是针对电池破裂(电解液泄漏)的情况。

Acute toxicity, Category 3, oral; H301

急毒性-类别3口服; H301

Skin corrosion, Category 1A; H314

皮肤腐蚀-类别1A; H314

Serious eye damage, Categories I; H318

严重眼损伤-类别1; H318

Specific target organ toxicity following repeated exposure, Categories I; H372

特定目标器官毒性 重复接触-类别1; H372

# Label elements 标签要素:

Hazard pictograms 象形图





Signal Word **Danger** 警示词 **危险** 

Hazard	<b>Statements</b>	四份市田
пасаги	Statements	

H301	Toxic if swallowed 吞咽会中毒
H314	Causes severe skin burns and eye damage 造成严重皮肤灼伤和眼损伤
H372	Causes damage to organs through prolonged or repeated exposure 长期或反复接触会对器官造成损害

GB/T 16483: 2008 03 Page 3 of 11 Pages



	Technology & Service	
	ry Statements – Prevention	
预防说明—预		
P270	Do not eat, drink or smoke when using this product 使用本产品时不要进食、饮水或吸烟	
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection 戴防护手套/穿防护服/戴防护眼罩/戴防护面具/戴听力保护装置	
Precautiona 预防声明—响	ry Statements – Response I应	
P301+P330 +P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. 如误吞咽:漱口。不要诱导呕吐	
P303+P361 +P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower]. 如皮肤(或头发)沾染: 立即脱掉所有沾染的衣服。用水清洗患处[或淋浴]。	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing 如误吸入:将人转移到空气新鲜处,保持呼吸舒适体位	
P305+P351 +P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present	
Precautiona 预防声明—存	ry Statements – Storage 储	
PANS	Store locked up 存放处须加锁	
Precautiona 预防声明—处	ry Statements – Disposal 置	
PSOT	Dispose of contents/container, in accordance with local/regional/national/international regulations 处置内装物/容器,根据当地/地区/国家/国际要求	
lazards not d	otherwise classified (HNOC) 未分类的危险	
Not applicable		
	ition 其他信息	
•	latic organisms, may cause long-term adverse effects in the aquatic environment. 主 可能对水生环增造成长期不利影响	

对水生生物有害,可能对水生环境造成长期不利影响。

# Interactions with other chemicals与其他化学物质的相互作用

Use of alcoholic beverages may enhance toxic effect.

使用酒精饮料可能会增强毒性作用

GB/T 16483: 2008 03 Page 4 of 11 Pages



SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENT 第3节—成分信息				
Ingredient	Molecular formula	CAS No.	Weigh	
成分	分子式	CAS 号	含量	
Lithium Cobalt Nickel Manganese Oxide /锂镍钴锰氧化物	LiNiMnCoO <sub>2</sub>	346417-97-8	36.6%	
Graphite/ 石墨	C <sub>24</sub> X <sub>12</sub>	7782-42-5	19.8%	
Polyvinylidene Fluoride (PVDF) /聚偏氟乙烯	(CH <sub>2</sub> -CF <sub>2</sub> ) <sub>n</sub>	24937-79-9	0.4%	
Carboxymethylcellulose /羧甲基纤维素	C <sub>6</sub> H <sub>12</sub> O <sub>6</sub>	9000-11-7	0.3%	
Acetylene black /乙炔黑	H <sub>4</sub> C	1333-86-4	0.9%	
Styrene-Butadiene Rubber (SBR) /丁苯橡胶	(C <sub>8</sub> H <sub>8</sub> .C <sub>4</sub> H <sub>6</sub> ) <sub>x</sub>	9003-55-8	0.4%	
Polypropylene (PP) /聚丙烯	(C <sub>3</sub> H <sub>6</sub> ) <sub>n</sub>	9003-07-0	0.7%	
Lithium Hexafluorophosphate /六氟磷酸锂	LiPF <sub>6</sub>	21324-40-3	2.0%	
Ethylene Carbonate /碳酸乙烯酯	C <sub>3</sub> H <sub>4</sub> O <sub>3</sub>	96-49-1	2.0%	
Ethyl methyl carbonate /碳酸甲乙酯	C <sub>4</sub> H <sub>8</sub> O <sub>3</sub>	623-53-0	1.0%	
Dimethyl carbonate /碳酸二甲酯	C <sub>3</sub> H <sub>6</sub> O <sub>3</sub>	616-38-6	6.8%	
Copper /铜	Cu	7440-50-8	7.6%	
Aluminium /铝	Al	7429-90-5	3.5%	
Nickel /镍	Ni	7440-02-0	0.7%	
Iron /铁	Fe	7439-89-6	17.3%	

# **SECTION 4 - FIRST AID MEASURES**

# 第4节一急救措施

# Eye Exposure 眼睛接触

In case of contact with eyes, flush with copious of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

如果与眼睛接触,用大量的水冲洗至少15分钟。用手指分开眼睑,确保充分的冲洗。寻求医生。

# Skin Exposure 皮肤接触

If the internal battery materials of an opened battery cell come into contact with skin, immediately flush with plenty of water or soap.

如果打开的电池的内部电池材料接触到皮肤,立即用大量的水或肥皂冲洗。

# Inhalation Exposure 吸入

In case of inhaling gas volatilized from inside of the battery, seek immediate medical attention.

如果吸入了电池内部挥发的气体,请立即就医。

# Ingestion Exposure 吞咽

If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel. 如果吞咽,请就医。除非医务人员指示,否则不要催吐。

GB/T 16483: 2008 03 Page 5 of 11 Pages



#### **SECTION 5 - FIRE FIGHTING MEASURES**

# 第5节一消防措施

# Danger characteristic 危险特性

Exposure to excessive heat can cause venting of the liquid electrolyte.

暴露在过热的环境中会导致液体电解质的释放。

Battery may burst and release hazardous decomposition products when exposed to a fire situation.

当暴露在火灾环境中时,电池可能会爆裂并释放出危险的分解产物。

### Hazardous combustion products 有害危险产物

Corrosive and toxic gas may be emitted during fire.

着火期间可能会排放腐蚀性和有毒气体。

### Fire-Fighting method 灭火措施

The staff must equip with filtermask (full mask) or isolated breathing apparatus.

员工必须配备过滤器面罩或隔离式呼吸器。

The staff must wear the clothes which can defense the fire in the upwind direction.

工作人员必须穿能在逆风方向防火的衣服。

Remove the container to the open space as soon as possible.

尽快将容器移到空地上。

Spray water on the containers in the fireplace to keep them cool until finish extinguishment.

把水喷在壁炉里的容器上, 使其降温, 直到熄灭。

### Fire-Fighting media 灭火介质

Plenty of water, dry chemical powder or carbon dioxide.

大量的水,干粉或二氧化碳。

# **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

# 第6节一意外泄漏措施

### Emergency treatment 紧急处理

If the battery material is released, remove personnel from area until the batteries coo<mark>l do</mark>wn and fumes dissipate. 如果电池材料被释放,请将人员从该区域撤离,直到电池冷却和烟雾消散。

Provide maximum ventilation to clear out hazardous gases and avoid skin and eye contact or inhalation of vapors. 提供最大的通风以清除有害气体和避免皮肤和眼睛接触或吸入蒸汽。

Remove spilled liquid with absorbent and incinerate waste.

用吸收剂除去溢出的液体并焚烧废物。

### **SECTION 7 - HANDLING AND STORAGE**

# 第7节一处理和储存

#### Handling 处理

1. Do not allow battery terminates to contact each other, or contact with other metals.

不要让电池端子相互接触或与其他金属接触。

2. Do not put the cell or battery into a fire or heat it. Do not solder the cell directly. Do not use or leave the cell or battery in a place near fire or heaters.

不要将电芯或电池放入火中或加热。不要直接焊接电池。不要将电芯或电池放在靠近火源或加热器等地方。

3. Do not expose the battery to excessive physical shock or vibration.

不要让电池受到过度的物理冲击或振动。

4. Do not immerse, throw, and wet a battery in water.

不要将电池浸入水中、投掷或弄湿。

5. Short-circuiting should be avoided. Short circuit will reduce the life of the battery and can lead to ignition of surrounding materials. Physical contact with to short- circuited battery can cause skin burn.

应避免短路。短路会降低蓄电池的寿命,并可能导致周围材料着火。与短路电池的物理接触会导致皮肤灼伤。

6. The batteries should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container.

GB/T 16483: 2008 03 Page 6 of 11 Pages



不应打开、销毁或焚烧电池,因为电池可能泄漏或破裂,并将密封容器中的成分释放到环境中。

7. Place the cell beyond the child packing and container.

将电池放置在儿童触及不到的地方。

8. Do not connect the battery directly to an electric outlet or cigarette socket in a car.

不要将电池直接连接到汽车的电源插座或香烟插座上。

9. Be sure to use the specified charger for battery, and follow the charging instructions correctly. 请务必使用指定的蓄电池充电器,并正确遵循充电说明。

10. Do not mix old and new batteries together, neither with Ni-Cd, dry batteries or another manufacturer batteries or product.

不要将新旧电池混合在一起使用,也不要与镍镉电池、干电池或其他制造商的电池或产品混合使用。

# Storage 储存

- 1. Batteries should be separated from other materials and stored in a noncombustible, well ventilated, sprinkler-protected structure with sufficient clearance between walls and battery stacks. 电池应与其他材料分开,并存放在不燃、通风良好、有洒水装置保护的结构中,墙壁和电池堆之间应有足够的间隙
- 2. Keep the sample in the cool, dry and well-ventilated place (Recommended control temperature: -20~30 °C, humidity: 45~85%). Do not exposure to direct sunlight for long periods. Keep away from fire and heating sources. Keep away from prohibited compounds and store them in different storage rooms. 将样品置于阴凉、干燥、通风良好的地方(建议控制温度-20~30℃,湿度: 45~85%)。不要长时间暴露在阳光直射下。远离火源和热源。远离禁配物,与禁配物分别存放于不同库室。
- 3. Equip with relevant types and quantities of the extinguishment instruments. The storage place should be equipped with suitable shelter materials for divulgence handling.

  配备相应种类和数量的灭火器材。储存场所应配备适当的掩蔽材料,以便进行泄漏处理。
- 4. For rechargeable battery, charge the battery every 6 months to the amount specified by the manufacture, even if the battery is not used.

  对于可充电电池,即使不使用电池,也应每6个月将电池充电至制造商规定的电量。

# SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

# 第8节一暴露控制与个人防护措施

# Engineering Control 工程控制

Keep away from heat and open flame. Supply with sufficient partial air exhaust. Store in a cool, dry place. 远离热源和明火。提供足够的局部排气。存放在阴凉干燥的地方。

# Respiratory Protection 呼吸保护

Not necessary under conditions of normal use. Wear self-contained breathing filtermask if the density exceed in the air. Wear breathing apparatus under the condition of emergency rescue or evacuation.

在正常使用条件下不需要。如果环境内气体密度超过空气中的密度,请佩戴自给式呼吸过滤器。在紧急救援或疏散的情况下,佩戴呼吸器。

### Eyes Protection 眼睛保护

Not necessary under conditions of normal use. Wear protective glasses if handling a leaking or ruptured battery. 在正常使用条件下不需要。如果处理泄漏或破裂的电池,请戴上防护眼镜。

### Skin and Body Protection 皮肤和身体保护

Not necessary under conditions of normal use. Wear fireproofing, gas defense clothes in case of handling a leaking or ruptured battery.

在正常使用条件下不需要。在处理泄漏或破裂的电池时,穿上防火防毒服。

### Hands Protection 手部保护

Not necessary under conditions of normal use. Wear chemical resistant rubber glove.

在正常使用条件下不需要。耐磨耐化学腐蚀橡胶手套。

### Other Protections 其他保护

No smoking, dining and drinking water in the workplace. Keep good habit of hygiene.

工作场所禁止吸烟、就餐和饮水。保持良好的卫生习惯。

GB/T 16483: 2008 03 Page 7 of 11 Pages



SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES 第9节—理化性质				
Appearance and properties	Solid			
外观与性状	固体			
Smell	Odorless	pH value (indicate concentration)	NA	
气味	无特殊气味	pH值(指明浓度)	INA	
Melting/freezing point	NA	(initial)boiling point & boiling range	NA	
熔点/凝固点	14/4	(初)沸点和沸程	14/4	
Relative vapor density (air =1)	ND	Saturated vapor pressure	NA	
相对蒸气密度(空气=1)	IND	饱和蒸气压	14/4	
Odor threshold	ND	Evaporation rate	NA	
气味临界值	IND	蒸发速率		
Relative density (water =1)	ND	Flash point	NA	
相对密度(水=1)	110	闪点	107	
Viscosity	NA	Decomposition temperature	ND	
<u> </u>	10/1	分解温度 Upper explosion limit	110	
Partition coefficient: n-octanol/water	Partition coefficient: n-octanol/water		NA	
n-辛醇/水分配系数		爆炸上限		
Ignition temperature	ND	Lower explosion limit	NA	
引燃温度	140	爆炸下限		
Solubility	Insoluble in water	Flammability	ND	
溶解性	不溶于水	易燃性	110	
Remark NA= Not applicable; ND= No Data				
备注 NA=不适用; ND=无信息				

# **SECTION 10 - STABILITY AND REACTIVITY**

第10节一稳定性与反应性

# Stability 稳定性

### Distribution of Ban 禁配物

Explosives, inflammables, strong oxidants and corrosives.

爆炸品、易燃物、强氧化剂和腐蚀剂。

# Conditions to Avoid 应避免的条件

Fire source, heating source, disassemble, external short circuit, crushes, deformation, high temperature above 100°C, direct sunlight and high humidity, immerse in water or overcharge.

火源、热源、拆卸、外部短路、压碎、变形、100°C以上高温、阳光直射、高湿度、浸水或过充。

# Hazardous Polymerization 危险聚合

Will not occur.

不会发生。

# Hazardous Decomposition Products 有害分解产物

Metal oxides, carboxyl compound such as CO, CO<sub>2</sub>, etc.

金属氧化物,碳化合物例如一氧化碳、二氧化碳,等等。

GB/T 16483: 2008 03 Page 8 of 11 Pages



	Technology & Service
SECTION 11 - TOXICOLOGICAL INFORMATIO 第11节一毒理学信息	ON
Acute Toxicity 急性毒性	No Data 无信息
Sub-acute and Chronic Toxicity 亚急性和慢性毒性	No Data 无信息
Skin irritation or corrosion 皮肤刺激性或腐蚀性	No Data 无信息
Eye irritation or corrosion 眼睛刺激或腐蚀	No Data 无信息
Skin sensitization 皮肤致敏	No Data 无信息
Respiratory sensitization 呼吸致敏	No Data 无信息
Germ cell mutation 生殖细胞突变性	No Data 无信息
Reproductive toxicity 生殖毒性	No Data 无信息
Specific target organ system toxicity - one exposure 特异性靶器官系统毒性一次接触	No Data 无信息
Specific target organ system toxicity - repeated exposure 特异性靶器官系统毒性反复接触	No Data 无信息
Inhalation hazard 吸入危害	No Data 无信息
Other effects on the organism 其他对生物体的影响	No Data 无信息

SECTION 12 - ECOLOGICAL INFORMATION 第12节—生态信息	
Acute aquatic toxicity 急性水生毒性	No Data 无信息
Chronic aquatic toxicity 慢性水生毒性	No Data 无信息
Durability and degradability 持久性和降解性	No Data 无信息
Potential bioaccumulation 潜在的生物累积性	No Data 无信息
Migration in soils 土壤中的迁移性	No Data 无信息
Other effects on the ecosphere 其他对生态的影响	No Data 无信息

# **SECTION 13 - DISPOSAL CONSIDERATIONS**

第13节一处置注意事项

# Appropriate Method of Substance 物质处理方法

The battery should be completely discharged prior to disposal in order to prevent short circuit.

为了防止短路, 在处理前应将蓄电池完全放电。

The battery contains recyclable materials, and it is suggested recycle.

电池含有可回收材料,建议回收利用。

Refer to National or Local regulations before handling.

操作前请参阅国家或地方法规。

Disposal of the battery should be performed by permitted, professional disposal firms knowledgeable in National or Local regulations of hazardous waste treatment and hazardous waste transportation.

电池的处理应由获得国家或地方法规的许可的具有危险废物处理和危险废物运输的专业处理公司进行。

GB/T 16483: 2008 03 Page 9 of 11 Pages



# **SECTION 14 - TRANSPORT INFORMATION**

第14节一运输信息

The battery has passed the test items of UN Manual of Test and Criteria Section 38.3, and

Report No.: ECT20231208114A.

电池已通过联合国《试验和标准手册》第38.3节的测试项目,报告编号: ECT20231208114A。

# General packaging requirement 一般包装要求:

The cells or batteries must be protected so as to prevent short circuits.

电芯或电池必须加以保护,以防止短路。

The cells or batteries or equipment must be packed in suitable strong outer packaging.

电芯或电池或设备必须包装在合适的坚固的外包装中。

If batteries contained in equipment, equipment must be secured against movement within the outer

3. packaging and be packed so as to prevent accidental activation.

如果由池包含在设备中,设备必须在外包装内固定,防止移动,并进行包装,以防止意外激活。

5	如果电池包含在设备中,设备必须在外包装内固定,防止移动,并进行包装,以防止意外激活。		
No.	UN numbers & Proper Shipping Name, if applicable		
序号	<b>联合国编号及运输专用名</b> ,如适用		
(1)	UN 3480_LITHIUM ION BATTERIES		
(1)	UN 3480_锂离子电池		
(0)	UN 3481_LITHIUN	M ION BATTERIES P	ACKED WITH EQUIPMENT
(2)	UN 3481_锂离子	电池与设备一同打包	
(2)	UN 3481_LITHIUN	M ION BATTERIES C	CONTAINED IN EQUIPMENT
(3)	UN 3481_锂离子®	电池安装在设备中	
(4)	1		
No.	Hazard Class	Packing Group	Packaging requirement
序号	危险等级	包装类别	包装要求
	Air transportation	n, according to IATA	A-DGR 66th Edition (Effective 1 January-31 December 2025)
	空运,依据IATA-D	OGR第66版(2025年	1月1日至12月31日生效)
(4)	Class 9	PG II	Packing Instruction 965, section IA
(1)	第九类危险货物	Ⅱ 级包装	包装说明965-IA
(0)	Class 9	PGII	Packing Instruction 966, section I
(2)	第九类危险货物	Ⅱ 级包装	包装说明966-1
(2)	Class 9	Strong package	Packing Instruction 967, section I
(3) 第九类危险货物 坚固包装		坚固包装	包装说明967-I
	Maritime transpo	rtation, according t	o IMO IMDG Code (Edition 42-24)
	海运,依据IMO IN	/IDG Code (42-24版)	
(1)	Class 9	PG II	Packing Instruction P903; EmS No.: F-A,S-I; Not Marine pollutant
(1)	第九类危险货物	Ⅱ 级包装	包装说明P903;应急处理代码: F-A,S-I; 非海洋污染物
(2)	Class 9	PG II	Packing Instruction P903; EmS No.: F-A,S-I; Not Marine pollutant
(2)	第九类危险货物	Ⅱ 级包装	包装说明P903;应急处理代码: F-A,S-I; 非海洋污染物
(2)	Class 9	PG II	Packing Instruction P903; EmS No.: F-A,S-I; Not Marine pollutant
(3)	第九类危险货物	Ⅱ 级包装	包装说明P903;应急处理代码: F-A,S-I; 非海洋污染物
	Road transportation, according to ADR-2025		
	公路运输,依据AI	DR-2025	
(1)	Class 9	PG II	Packing Instruction P903
(1)	第九类危险货物	Ⅱ 级包装	包装说明P903
(2)	Class 9	PG II	Packing Instruction P903
(2)	第九类危险货物	Ⅱ 级包装	包装说明P903
(2)	Class 9	PG II	Packing Instruction P903
(3)	第九类危险货物	Ⅱ 级包装	包装说明P903
Railway transportation, according to RID-2025		RID-2025	
	铁路运输,依据RID-2025		

GB/T 16483: 2008 03 Page 10 of 11 Pages

M	C	M
Technologic	nav &	Service

			Technology & Service
(1)	Class 9	PG II	Packing Instruction P903
(1)	第九类危险货物	Ⅱ 级包装	包装说明P903
(2)	Class 9	PG II	Packing Instruction P903
(2)	第九类危险货物	Ⅱ 级包装	包装说明P903
(2)	Class 9	PG II	Packing Instruction P903
(3)	第九类危险货物	Ⅱ 级包装	包装说明P903
Remark 备注 //			

# **SECTION 15 - REGULATORY INFORMATION**

第15节一监管信息

Dangerous Goods Regulation (DGR)

Recommendations on the Transport of Dangerous Goods Model Regulations

International Maritime Dangerous Goods (IMDG)

Occupational Safety and Health Act (OSHA)

Toxic Substances Control Act (TSCA)

Code of Federal Regulations (CFR)

Technical Instructions for the Safe Transport of Dangerous Goods

California Proposition 65

Superfund Amendments and Reauthorization Act Title III (302/311/312/313) (SARA)

Globally Harmonized System of Classification and Labeling of Chemicals(GHS)

In accordance with all Federal, State and local laws. 符合所有联邦、州和地方法律。

# **SECTION 16 - ADDITIONAL INFORMATION**

第16节一附加信息

# According standard 标准依据:

GB/T 16483-2008 Safety data sheet for chemical products Content and order of sections ISO 11014:2009(E) Safety data sheet for chemical products – Content and order of sections

# Editing date 编辑日期:

2024-12-18

# Department 编写机构

Guangzhou MCM Certification & Testing Co., Ltd.

广州邦禾检测技术有限公司

Building 2 No. 45 Zhong Er Section of Shiguang Road, Zhongcun Street, Panyu District, Guangzhou City, Guangdong Province, China.

中国 广东省广州市番禺区钟村街市广路钟二路段 45 号 2 栋

Tel.+86-20-3477 7662 或 0086-020-3477 7662

WEB: https://www.mcmtek.com Email: service@mcmtek.com

### Other Information 其他信息

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. We make no warranty of merchantability or any other warranty express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes. In no way shall we be liable for any claims, losses, or damage of any third party or for last profits or any special, indirect, consequential or exemplary damages arising from using the above information.

上述资料被认为是正确的,但并非囊括全部,只作指引之用。我们不对此类信息的适销性或任何其他明示或暗示的保证作出保证,并且我们不承担因使用此类信息而产生的任何责任。用户应自行调查,以确定信息是否适合其特定用途。对于任何第三方的任何索赔、损失或损害,或因使用上述信息而产生的最后利润或任何特殊、间接、后果性或惩戒性损害,我们概不负责。

-- End of the report--

GB/T 16483: 2008 03 Page 11 of 11 Pages