



CLAX MAGIC 70D2 RUST SPOT REMOVER-Iron And Rust

Version Number: 1

Preparation date: 2016-05-13

1. IDENTIFICATION

Product name: CLAX MAGIC 70D2 RUST SPOT REMOVER-Iron And Rust
Product Code: 100905320
SDS #: MS0800939
Recommended use:

- Industrial/Institutional
- Laundry care

Uses advised against: Uses other than those identified are not recommended

Manufacturer, importer, supplier: US Headquarters Sealed Air 8215 Forest Point Blvd. Charlotte, NC 28273-5509 Phone: 1-888-352-2249 SDS Internet Address: https://sds.sealedair.com	Canadian Headquarters Sealed Air - Canada 3755 Laird Road Mississauga, Ontario L5L 0B3 Phone: 1-800-668-7171
--	--

Emergency telephone number: 1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

Classification for the undiluted product

Skin corrosion/irritation	Category 1B
Serious eye damage/eye irritation	Category 1



Signal Word: Danger.

Precautionary Statements

CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE.

Causes burns/ serious damage to mouth, throat and stomach. Keep container tightly closed. Avoid contact with eyes, skin and clothing. Wash affected areas thoroughly after handling. Wear chemical-splash goggles, chemical-resistant gloves and protective footwear. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Immediately call a Poison Center (1-800-851-7145) or physician. Dispose of in accordance with all federal, state and local applicable regulations. SUPPLEMENTAL INFORMATION: Mix only with water. DO NOT MIX WITH AMMONIA, BLEACH OR OTHER CHLORINATED COMPOUNDS. Can react to release hazardous gases. May vigorously react with strong alkaline products resulting in spattering and excessive heat.

Health hazards not otherwise classified (HHNOC) - Not applicable

Physical hazards not otherwise classified (PHNOC) - Not applicable

CLAX MAGIC 70D2 RUST SPOT
REMOVER-Iron And Rust

1 of 5

Classification for the diluted product @ RTU

This product is intended to be used neat.

Precautionary Statements

See undiluted product information above.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Classified Ingredients**

Ingredient(s)	CAS #	Weight %
Oxalic acid	6153-56-6	5 - 10%
Dipropylene glycol methyl ether	34590-94-8	3 - < 5%
Alcohol ethoxylates	68439-46-3	1 - < 3%

*Exact percentages are being withheld as trade secret information

4. FIRST AID MEASURES**Undiluted Product:**

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes.

Skin: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion: IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water.

Most Important Symptoms/Effects: No information available.

Immediate medical attention and special treatment needed Not applicable.

Diluted Product:

This product is intended to be used neat.

Eyes: See undiluted product information above.

Skin: See undiluted product information above.

Inhalation: See undiluted product information above.

Ingestion: See undiluted product information above.

5. FIRE-FIGHTING MEASURES

Specific methods: No special methods required

Suitable extinguishing media: Not applicable.

Specific hazards: Not applicable.

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Extinguishing media which must not be used for safety reasons: No information available.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: No information available.

Environmental precautions and clean-up methods: Clean-up methods - large spillage. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Use a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. All precautions for handling the product must be used in handling the empty container and residue. Product residue may remain on/in empty containers. Mix only with water. DO NOT MIX WITH AMMONIA, BLEACH, OR OTHER CHLORINATED COMPOUNDS. Can react to release hazardous gases. May vigorously react with strong alkaline products resulting in spattering and excessive heat. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage: Protect from freezing. Keep tightly closed in a cool, dry, well-ventilated area out of direct sunlight.

Aerosol Level (if applicable): Not applicable

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines:

Ingredient(s)	CAS #	ACGIH	OSHA
Oxalic acid	6153-56-6	2 mg/m ³ (STEL) 1 mg/m ³ (TWA)	-
Dipropylene glycol methyl ether	34590-94-8	150 ppm (STEL) 100 ppm (TWA)	Skin 100 ppm (TWA) 600 mg/m ³ (TWA)
Alcohol ethoxylates	68439-46-3	-	-

Undiluted Product:

Engineering measures to reduce exposure:

None known

Personal Protective Equipment

Eye protection:

Chemical-splash goggles.

Hand protection:

Chemical-resistant gloves.

Skin and body protection:

Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear.

Respiratory protection:

In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Hygiene measures:

Handle in accordance with good industrial hygiene and safety practice.

Diluted Product:

This product is intended to be used neat.

Personal Protective Equipment

Eye protection:

No personal protective equipment required under normal use conditions.

Hand protection:

No personal protective equipment required under normal use conditions.

Skin and body protection:

No personal protective equipment required under normal use conditions.

Respiratory protection:

No personal protective equipment required under normal use conditions.

Hygiene measures:

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

Evaporation Rate: No information available

Odor threshold: No information available.

Melting point/range: Not determined

Autoignition temperature: No information available

Solubility in other solvents: No information available

Density: 8.52 lbs/gal 1.022 Kg/L

Bulk density: No information available

Flash point: > 200 °F > 93.3 °C

Dilution Flash Point: > 200 °F > 93.3 °C

Elemental Phosphorus: 0.00 % by wt.

pH: 0.9

Dilution pH: 0.9 @ RTU

Metal Corrosion: Not determined

Explosion limits: - upper: Not determined - lower: Not determined

Color: Clear Colorless

Odor: Characteristic

Boiling point/range: Not determined

Decomposition temperature: Not determined

Solubility: Completely Soluble

Relative Density (relative to water): 1.022

Vapor density: No information available

Vapor pressure: No information available.

Partition coefficient (n-octanol/water): No information available

Viscosity: No information available

VOC: 3 % *

VOC % by wt. at use dilution 3 % *

Flammability (Solid or Gas): Not applicable

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Reactivity:

Not Applicable

Stability:

The product is stable

Possibility of hazardous reactions:

May vigorously react with strong alkaline products resulting in spattering and excessive heat.

Hazardous decomposition products:

None reasonably foreseeable.

Materials to avoid:

Strong bases. Ammonia. Do not mix with chlorinated products (such as bleach). Do not mix with any other product or chemical unless specified in the use directions.

Conditions to avoid: No information available.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Skin contact, Inhalation, Ingestion, Eye contact

Delayed, immediate, or chronic effects and symptoms from short and long-term exposure

Skin contact: Corrosive. Causes severe burns. Symptoms may include burns, blisters, redness and pain (which may be delayed).

Eye contact: Corrosive. Causes serious eye damage. Symptoms may include pain, burning sensation, redness, watering, blurred vision or loss of vision.

Ingestion: Causes burns/ serious damage to mouth, throat and stomach. Symptoms may include stomach pain and nausea.

Inhalation: May cause irritation and corrosive effects to nose, throat and respiratory tract. Symptoms may include coughing and difficulty breathing.

Sensitization: No known effects.

Target Organs (SE): None known

Target Organs (RE): None known

Numerical measures of toxicity

ATE - Oral (mg/kg): 4300

ATE - Dermal (mg/kg): >5000

12. ECOLOGICAL INFORMATION

Ecotoxicity: No information available.

Persistence and Degradability: No information available.

Bioaccumulation: No information available.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products: This product, as sold, if discarded or disposed, is a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Dispose in compliance with all Federal, state, provincial, and local laws and regulations.

Contaminated Packaging: Do not re-use empty containers.

RCRA Hazard Class (undiluted product): D002 Corrosive Waste

RCRA Hazard Class (diluted product): Not Applicable

14. TRANSPORT INFORMATION

DOT/TDG/IMDG: Proper shipping descriptions can vary by pack size. Please refer to the Diversey HazMat Library, <http://naextranet.diversey.com/dot/>, for up to date shipping information.

DOT (Ground) Bill of Lading Description: LTD. QTY.

IMDG (Ocean) Bill of Lading Description: UN3265, CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S., (oxalic acid), 8, III, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65.

RIGHT TO KNOW (RTK)

Ingredient(s)	CAS #	MARTK:	NJRTK:	PARTK:	RIRTK:
Water	7732-18-5	-	-	-	-
Oxalic acid	6153-56-6	X	X	X	-

Dipropylene glycol methyl ether	34590-94-8	X	X	X	-
Alcohol ethoxylates	68439-46-3	-	-	-	-
Sulfuric acid	7664-93-9	X	X	X	X

CERCLA/ SARA

Ingredient(s)	CAS #	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
Dipropylene glycol methyl ether	34590-94-8	3 - < 5%			X
Sulfuric acid	7664-93-9	< 0.1%	1000	1000	X

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
Dipropylene glycol methyl ether	X		

SARA 311/312 Hazard Categories

Immediate: X
Delayed: -
Fire: -
Reactivity: -

Canadian Regulations

Ingredient(s)	CAS #	NPRI
Sulfuric acid	7664-93-9	X

16. OTHER INFORMATION

NFPA (National Fire Protection Association)

Rating Scale: (Low Hazard) 0 - 4 (Extreme Hazard)

Health 3
Flammability 0
Instability 0

Version Number: 1
Preparation date: 2016-05-13

Reason for revision: Not applicable
Prepared by: NAPRAC

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.