

FISSURED™

Square Lay-in & Tegalur
medium texture

Declare.
GREENGUARD
Gold Certified
(details below)

LEED® WELL™ LBC

UP TO 41% RECYCLED CONTENT

Calculate sustainability with Green Genie®
armstrongceilings.com/greengenie

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT



Fissured™ Angled Tegalur panels with Prelude® XL® 15/16" suspension system

Economical panels; Directional with standard acoustical performance. \$\$\$\$

KEY SELECTION ATTRIBUTES

- Economical
- Directional fissured image

COLOR



VISUAL SELECTION

PERFORMANCE SELECTION


Dots represent high level of performance.

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	NRC	CAC	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
FISSURED™ Square Lay-in 15/16" Square Lay-in	1	756	24 × 24 × 5/8" □	0.55	30	N/A	Class A	0.79	N/A	Std	*	Std	Std	*	1-Yr
		896	24 × 24 × 5/8" □	0.55	35	N/A	Fire Guard™	0.79	N/A	Std	*	Std	Std	*	1-Yr
		755	24 × 48 × 5/8" □	0.55	30	N/A	Class A	0.79	N/A	Std	*	Std	Std	*	1-Yr
		895	24 × 48 × 5/8" □	0.55	35	N/A	Fire Guard™	0.79	N/A	Std	*	Std	Std	*	1-Yr
FISSURED™ Tegalur 15/16" Angled Tegalur	12	705	24 × 24 × 5/8" □	0.55	30	N/A	Class A	0.79	N/A	Std	*	Std	Std	*	1-Yr
		815	24 × 24 × 5/8" □	0.55	35	N/A	Fire Guard™	0.79	N/A	Std	*	Std	Std	*	1-Yr
Made-to-Order Sizes			5/8" Thick – 15/16" Square Lay-in & Tegalur	N/A	N/A	N/A	Class A	0.79	N/A	Std	*	Std	Std	*	1-Yr
			Width Length												
			12" - 30" 18" - 72"												

4-6 WEEKS order to ship

Red Numbers are Fire Guard items.
¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).
Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification
Type III, Form 2, Pattern C D
Fire Class A

Humidity/Sag Resistance
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Insulation Value
755, 756, 895, 896 – R Factor – 1.5 (BTU units)
R Factor – 0.26 (Watts units)
705, 815 – R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG UL 2818



1-Year Limited Warranty
Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
705 – 0.69 lbs/SF; 64 SF/ctn 815 – 1.08 lbs/SF; 48 SF/ctn
755 – 0.66 lbs/SF; 96 SF/ctn 895, 896 – 1.09 lbs/SF; 64 SF/ctn
756 – 0.67 lbs/SF; 64 SF/ctn

Minimum Order Quantity
1 carton, excludes made-to-order panels

Metric Items Available
756M, 896M, 755M, 895M, 705M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.