

Liberty

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile	
Size*	6" x 48" / 152.4mm x 1219.2mm 12" x 24" / 304.8mm x 609.6mm	
Overall Thickness*	1/6" / 4.0mm	
Wearlayer	11 mil / 0.27mm - Also features our Tuff Shield finish technology for superior scratch and stain resistance qualities.	
Construction	Layered plank consisting of wearlayer, film and backing.	
Edge	Square	
Standard Colors	6" x 48": 6 standard colors 12" x 24": 4 standard colors	
Installation Method	Floating utilizing the Unilin® locking system	
Wear Limited Warranty	30-Year Residential / 20-Year Light Commercial	
Recycled Content	This product contains no recycled content. 100% recyclable post-use.	
Packaging	6" x 48": 15.22 ft ² (1.41 m ²) per carton 8 pieces per carton 90 cartons per pallet 16 pallets per 20' container	12" x 24": 23.23 ft ² (2.16 m ²) per carton 12 pieces per carton 72 cartons per pallet 16 pallets per 20' container
Weight Per Carton	24.5 lbs / 11.11 kg	32.81 lbs / 14.92 kg
Product Testing		
Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed



***All measurements are nominal.**

Please visit www.earthwerks.com for full warranty details and adhesive/application recommendations.

