

EUROSTYLE COLLECTION

SPECIFICATIONS



- 120-277V INPUT VOLTAGE, 50/60Hz
- CONSTANT CURRENT AT 700 mA
- DRIVER UL CLASS 2, POWER FACTOR > .90
- AMBIENT OPERATING TEMPERATURE -40°C (-40°F) TO +40°C (105°F)
- ESTIMATED 50,000 HRS L₇₀*
- THERMALLY PROTECTED LED ARRAY
- POWDERCOATED ALUMINUM BACK PAN
- MOLDED OF DURABLE NON-CORROSIVE UV RESISTANT RESINS
- WALL OR CEILING MOUNT
- UL/CUL LISTED FOR WET LOCATION
- STANDARD PACK QTY: 12





RoHS compliant





FE362



FE361



FE363



EXAMPLE # **FE361-L1800C-BFP**

STYLE #	SOURCE/WATTAGE	COLOR TEMP	BODY	DIFFUSER	OPTION
FE361 = ROUND FE362 = GRILL FE363 = GRID	L1800C = 8 CREE LED ARRAY (18W) 22W POWER INPUT 1824 LUMENS 82 LUMENS PER WATT**	4000K CRI = 74 (TYP)	B = BLACK W = WHITE	F = FROSTED	O = OCCUPANCY SENSOR P = PHOTOCELL Photocells are only available for 120V applications

L1800C LED REPLACEMENT PARTS
L18C-DC-700-08-R = 8 CREE LED ARRAY
IG1800-DMV-1 = LED DRIVER

* DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

** ESTIMATED FROM LED SOURCE

