00010079001 English Page 1 of 6





24 Hour Emergency Phone Numbers: Medical/Poison Control:

In U.S.: Call 1-800-222-1222

Outside U.S.: Call your local poison

control center

Transportation/National Response Center:

1-800-535-5053 1-352-323-3500

NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this MSDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.

Section 1 - Chemical Product / Company Information

This Material Safety Data Sheet is available in Canadian French and Hispanic American Spanish upon request.

On peut demader cette fiche signalétique (MSDS) a la langue française-canadienne.

Los Datos de Serguridad del Producto pueden obtenerse en Espanol si lo riquiere.

Product Name: Kwik Seal 3.0 Kwik Dry Technology Crystal Clear Revision Date: 02/25/2009

Product UPC Number: 070798007956 Supersedes: New

Product Use/Class: MS Polymer Caulk MSDS Number: 00010079001

Manufacturer: DAP Inc.

2400 Boston Street Suite 200 Baltimore. MD 21224-4723

888-327-8477 (non-emergency matters)

Section 2 - Hazards Identification

Emergency Overview: A crystal clear paste product with a slight odor. WARNING! May cause eye, skin, nose, throat and respiratory tract irritation. Harmful if swallowed or absorbed through the skin.

Refer to other MSDS sections for other detailed information.

Effects Of Overexposure - Eye Contact: May cause eye irritation.

Effects Of Overexposure - Skin Contact: Harmful if absorbed through the skin. May cause skin irritation. Prolonged or repeated skin contact can result in sensitization and dermatitis.

Effects Of Overexposure - Inhalation: May be harmful if inhaled. Inhalation of high concentrations may cause headache, nausea, and dizziness. Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes). Inhalation may cause mild irritation to the respiratory tract (nose, mouth, mucous membranes). May cause blurred vision. Prolonged, repeated, or high exposures may cause irritation to the respiratory tract (nose, mouth, mucous membranes). May be harmful if inhaled.

Effects Of Overexposure - Ingestion: Harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Effects Of Overexposure - Chronic Hazards: Repeated or prolonged exposure may cause skin, respiratory, kidney and liver damage. Prolonged and repeated skin contact may cause irritation and possibly dermatitis.

A mixture of diisodecyl phthalate and diisononyl phthalate has been tested in a two-generation toxicity study in laboratory animals. No effects on reproductive parameters were seen. However, a small but statistically significant increase in early

00010079001 English Page 2 of 6

offspring mortality was seen at high oral doses. The significance of this to humans is uncertain.

Primary Route(s) Of Entry: Skin Contact, Inhalation, Eye Contact

Medical Conditions which May be Aggravated by Exposure: None known.

Carcinogenicity:

None

Section 3 - Composition / Information On Ingredients					
Chemical Name	CASRN	Wt%			
Proprietary Phthalate Esters	68515-49-1	15-40			
Amorphous silicon dioxide	68611-44-9	5-10			
Silica, amorphous	7631-86-9	0.5-1.5			
Gamma-Aminopropyltrimethoxysilane	13822-56-5	0.5-1.5			

Section 4 - First Aid Measures

First Aid - Eye Contact: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

First Aid - Skin Contact: Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical aid if symptoms persist. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Remove and wash contaminated clothing.

First Aid - Inhalation: If inhaled, remove to fresh air. If breathing is difficult, leave the area to obtain fresh air. If continued breathing difficulty is experienced, get medical attention immediately. First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

First Aid - Ingestion: First Aid: If swallowed, get medical attention immediately. If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately. If ingested, drink 2 glasses of water. Immediately see a physician. Never give anything by mouth to an unconscious person. If ingested, irrigate the stomach.

Note to Physician: None.

COMMENTS: If over-exposure occurs, call your poison control center at 1 -800 -222 - 1222.

Section 5 - Fire Fighting Measures

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam, Water Fog

Unusual Fire And Explosion Hazards: No special protective measures against fire required.

Special Firefighting Procedures: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Wear proper protective equipment as specified in Section 8. Use absorbent material or scrape up dried material and place in container.

00010079001 English Page 3 of 6

Section 7 - Handling And Storage

Handling: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Open all windows and doors or use other means to ensure cross-ventilation and fresh air entry during application and drying. Odor is not an adequate warning for hazardous conditions. Use only with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing. Wash thoroughly after handling. Remove contact lenses before using. Do not handle contact lenses until all sealant has been cleaned from fingertips, nails and cuticles. Residual sealant may transfer to contact lenses and cause severe eye irritation.

Storage: Do not store at temperatures above 120 degrees F. Store containers away from excessive heat and freezing. Close container after each use. Store away from caustics and oxidizers.

Section 8 - Exposure Controls / Personal Protection								
Chemical Name	CASRN	ACGIH TWA	ACGIH STEL	ACGIH CEIL	OSHA TWA	OSHA STEL	OSHA CEIL	Skin
Proprietary Phthalate Esters	68515-49-1	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.	No
Amorphous silicon dioxide	68611-44-9	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.	No
Silica, amorphous	7631-86-9	10 MGM3	N.E.	N.E.	5 MGM3	N.E.	N.E.	No
Gamma-Aminopropyltrimethoxysilane	13822-56-5	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.	No

Precautionary Measures: Please refer to other sections and subsections of this MSDS.

Engineering Controls: Good general ventilation should be sufficient to control airborne levels. Ensure adequate ventilation, especially in confined areas. Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH-approved air purifying respirator with an organic vapor cartridge or canister may be necessary under certain circumstances where airborne concentrations are expected to exceed exposure limits. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Skin Protection: Rubber gloves. Natural rubber, butyl rubber and polyvinyl chloride gloves are not suitable protection against phthalates such as diisodecyl phthalate and diisononyl phthalate; neoprene is recommended.

Eye Protection: Goggles or safety glasses with side shields.

Other protective equipment: Not required under normal use.

Hygienic Practices: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

Important: Listed Permissible Exposure Levels (PEL) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); these limits may vary between states.

Note: An employee's skin exposure to substances having a "YES" in the "SKIN" column in the table above shall be prevented or reduced to the extent necessary under the circumstances through the use of gloves, coveralls, goggles or other appropriate personal protective equipment, engineering controls or work practices.

Section 9 - Physical And Chemical Properties

Boiling Range:Not EstablishedVapor Density:Heavier Than AirOdor:SlightOdor Threshold:Not Established

Color: Crystal clear Evaporation Rate: Slower Than n-Butyl Acetate

Solubility in H2O: Not Established Specific Gravity: 1.0

Freeze Point: Not Established pH: Between 7.0 and 12.9

 Vapor Pressure:
 Not Established
 Viscosity:
 Not Established

 Physical State:
 Paste
 Flammability:
 Non-Flammable

 Flack Point Fig.
 Organization (September 200)
 Mothods
 Control of the control of the

Flash Point, F: Greater than 200 Method: (Seta Closed Cup)
Lower Explosive Limit, %: Not Established
Upper Explosive Limit, %:Not Established

00010079001 English Page 4 of 6

When reported, vapor pressure of this product has been calculated theoretically based on its constituent makeup and has not been determined experimentally.

(See section 16 for abbreviation legend)

Section 10 - Stability And Reactivity

Conditions To Avoid: Excessive heat and freezing.

Incompatibility: Incompatible with strong bases and oxidizing agents.

Hazardous Decomposition Products: Normal decomposition products, i.e., COx, NOx.

Hazardous Polymerization: Hazardous polymerization will not occur under normal conditions.

Stability: Stable under recommended storage conditions.

Section 11 - Toxicological Information

Product LD50: Not Established Product LC50: Not Established

Significant Data with Possible Relevance to Humans: None.

Section 12 - Ecological Information

Ecological Information: Ecological injuries are not known or expected under normal use.

Section 13 - Disposal Information

Disposal Information: Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

EPA Waste Code if Discarded (40 CFR Section 261): This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261.

Section 14 - Transportation Information

DOT Proper Shipping Not Regulated. Packing Group: N.A.

Name:

DOT Technical Name:N.A.Hazard Subclass:N.A.DOT Hazard Class:N.A.DOT UN/NA Number:None

Note: The shipping information provided is applicable for domestic ground transport only. Different categorization may apply if shipped via other modes of transportation and/or to non-domestic destinations.

Section 15 - Regulatory Information

CERCLA - SARA Hazard Category:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

00010079001 English Page 5 of 6

Immediate Health Hazard, Chronic Health Hazard

SARA Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

None

Toxic Substances Control Act:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product:

Chemical Name	CAS Number
Proprietary polyether	Proprietary

Pennsylvania Right-to-Know:

The following non-hazardous ingredients are present in the product at greater than 3%:

Chemical Name	CAS Number
Proprietary polyether	Proprietary

California Proposition 65:

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Section 16 - Other Information

HMIS Ratings:

Health: 1 Flammability: 1 Reactivity: 0 Personal Protection: X

Volatile Organic Compounds (VOC), less water less exempts: g/L: 0.2 lb/gal: 0.0 wt:wt%: 0.0

Volatile Organic Compounds (VOC), less water less exempts, less LVP-VOCs: wt:wt%: 0.9

REASON FOR REVISION: Periodic Update

Legend: N.A. – Not Applicable ACGIH – American Conference of Governmental Industrial Hygienists

N.E. – Not Established SARA – Superfund Amendments and Reauthorization Act of 1986

N.D. - Not Determined NJRTK - New Jersey Right-to-Know Law

VOC - Volatile Organic Compound OSHA - Occupational Safety and Health Administration

PEL – Permissible Exposure Limit HMIS – Hazardous Materials Identification System

TLV – Threshold Limit Value NTP – National Toxicology Program

CEIL – Ceiling Exposure Limit STEL – Short Term Exposure Limit

LD50 – Lethal Dose 50 LC50 – Lethal Concentration 50

F – Degree Fahrenheit MSDS – Material Safety Data Sheet

C – Degree Celsius CASRN – The Chemical Abstracts Service Registry Number

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.

<End of MSDS>