

MATERIAL SAFETY DATA SHEET

NPCA

FOR COATINGS, RESINS AND RELATED MATERIALS
(Approved by US Department of Labor Essentially Similar to Form OSHA 20)

Date Issued 12/29/05

SECTION I

MANUFACTURERS NAME

GARDNER-GIBSON CORPORATION

STREET ADDRESS

4161 E. 7TH AVENUE

EMERGENCY TELEPHONE NUMBER

1-800-424-9300

PRODUCT CLASS

CRACK STOPPER-CRACK A JOINT FILLER

CITY, STATE, AND ZIP CODE

TAMPA, FL 33605

MANUFACTURER'S CODE

IDENTIFICATION

0569-GA

TRADE NAME

GARDNER

SECTION II- HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV PPM	TLV Mg/M3	LEL	VAPOR PRESSURE
MINERAL SPIRITS CAS # - 8052-41-3	<3%	100	5000		
ETHYLENE GLYCOL CAS #- 107-21-1	<1%	50	4700		
BUTYL BENZYL PHTHALATE CAS #- 85-68-7	*	*	20400		
CAS #-					
CAS #-					

ADDITIONAL INFORMATION- * NOT ESTABLISHED

Hazardous Materials Identification System (HMIS)

Health
1

Flammability
0

Reactivity
0

Personal Protection
C

SECTION III – PHYSICAL DATA

BOILING RANGE: 210°F -215°F VAPOR DENSITY HEAVIER LIGHTER, THAN AIR

EVAPORATION RATE FASTER SLOWER, THAN
ETHER PERCENT VOTILE BY VOLUME 20 % WEIGHT PER GALLON
BY VOLUME 9.9 LBS

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY - NR

FLASH POINT- WATER BASED

EXTINGUISHING MEDIA- N/A

UNUSUAL FIRE AND EXPLOSION HAZARDS- PRODUCT WILL NOT BURN AS SUPPLIED. DRIED FILM MAY BURN IF SUBJECT TO SOURCE OF IGNITION.

SPECIAL FIRE FIGHTING PROCEDURES- N/A

SECTION V – REACTIVITY DATA

STABILITY: UNSTABLE STABLE CONDITIONS TO AVOID: NONE

INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZERS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON DIOXIDE, CARBON MONOXIDE

HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR

CONDITIONS TO AVOID: NONE

SECTION VI-HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE-CHRONIC: PROLONGED/REPEATED SKIN CONTACT MAY CAUSE DERMATITIS . ACUTE:-
SKIN: PROLONGED/REPEATED CONTACT MAY CAUSE IRRITATION TO SENSITIVE SKIN. EYES: MAY IRRITATE.
CARCINOGENICITY: NO

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ).

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm.
Read and follow label directions and information given on Material Safety Data Sheets and use care when handling or using all petroleum products.

EMERGENCY FIRST AID PROCEDURE-SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. INGESTION: CONTACT A PHYSICIAN.

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: DIKE SPILL AREA. RECOVER FREE LIQUID. ADD ABSORBENT TO AREA.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.

SECTION VIII – SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: N/A

VENTILATION: USE WITH ADEQUATE VENTILATION.

PROTECTIVE GLOVES: N/A

EYE PROTECTION: N/A

OTHER PROTECTIVE EQUIPMENT: N/A

SECTION IX – REGULATORY INFORMATION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN COOL PLACE

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN OR CLOTHING.